

# SAFETY DATA SHEET



## MasterFinish RL 220

Version 2.0      Revision Date: 08/15/2023      SDS Number: 000000260374      Date of last issue: 07/28/2023  
Date of first issue: 01/09/2023

---

### SECTION 1. IDENTIFICATION

Product name : MasterFinish RL 220  
Product code : 000000000055516322 000000000055516322  
Other means of identification : No data available

#### Manufacturer or supplier's details

Company name of supplier : Master Builders Solutions Canada Inc.  
Address : 1800 CLARK BLVD  
Brampton ON L6T 4M7  
Emergency telephone : ChemTel: +1-813-248-0585;  
National Emergency Telephone Number : USA: +1-800-255-3924 ChemTel contract no. MIS9240420

#### Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals  
Restrictions on use : Reserved for industrial and professional use.

---

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the Hazardous Products Regulations

Aspiration hazard : Category 1  
Flammable liquids : Category 3  
Skin corrosion/irritation : Category 2  
Serious eye damage/eye irritation : Category 2A  
Germ cell mutagenicity : Category 1B  
Carcinogenicity : Category 1B  
Specific target organ toxicity - repeated exposure : Category 1 (Central nervous system)  
Short-term (acute) aquatic hazard : Category 3  
Long-term (chronic) aquatic hazard : Category 3

# SAFETY DATA SHEET

## MasterFinish RL 220

Version 2.0      Revision Date: 08/15/2023      SDS Number: 000000260374      Date of last issue: 07/28/2023  
Date of first issue: 01/09/2023

---

### GHS label elements

Hazard pictograms



Signal Word

: Danger

Hazard Statements

: H226 Flammable liquid and vapor.  
H319 Causes serious eye irritation.  
H315 Causes skin irritation.  
H304 May be fatal if swallowed and enters airways.  
H350 May cause cancer.  
H340 May cause genetic defects.  
H372 Causes damage to organs (Central nervous system) through prolonged or repeated exposure.  
H402 Harmful to aquatic life.  
H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements

: **Prevention:**  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
P201 Obtain special instructions before use.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P260 Do not breathe dusts or mists.  
P202 Do not handle until all safety precautions have been read and understood.  
P273 Avoid release to the environment.  
P243 Take action to prevent static discharges.  
P241 Use explosion-proof electrical/ ventilating/ lighting/ .? / equipment.  
P270 Do not eat, drink or smoke when using this product.  
P264 Wash face, hands and any exposed skin thoroughly after handling.  
P233 Keep container tightly closed.  
P242 Use only non-sparking tools.  
P240 Ground and bond container and receiving equipment.  
**Response:**  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P314 Get medical advice/ attention if you feel unwell.  
P308 + P311 IF exposed or concerned: Call a POISON CENTER/ doctor.  
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
P332 + P313 If skin irritation occurs: Get medical advice/ attention.  
P331 Do NOT induce vomiting.  
P337 + P313 If eye irritation persists: Get medical advice/ atten-

# SAFETY DATA SHEET

## MasterFinish RL 220

Version 2.0      Revision Date: 08/15/2023      SDS Number: 000000260374      Date of last issue: 07/28/2023  
Date of first issue: 01/09/2023

tion.  
P362 + P364 Take off contaminated clothing and wash it before reuse.

P370 + P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.

### Storage:

P405 Store locked up.  
P403 + P235 Store in a well-ventilated place. Keep cool.

### Disposal:

P501 Dispose of contents/container to appropriate hazardous waste collection point.

### Other hazards

None known.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Aromatic hydrocarbons

### Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Stoddard solvent	Stoddard solvent	8052-41-3	$\geq 50 - < 100$
2-butoxyethanol	Ethanol, 2-butoxy-	111-76-2	$\geq 7 - < 10$
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	$\geq 5 - < 10$
1,2,4-trimethylbenzene	Benzene, 1,2,4-trimethyl-	95-63-6	$\geq 1 - < 5$
Trimethylbenzene	Benzene, trimethyl-	25551-13-7	$\geq 0.3 - < 5$
Distillates (petroleum), solvent-dewaxed light paraffinic	Distillates (petroleum), solvent-dewaxed light paraffinic	64742-56-9	$\geq 1 - < 5$
naphthalene	Naphthalene	91-20-3	$\geq 0.3 - < 1$
cumene	Benzene, (1-methylethyl)-	98-82-8	$\geq 0 - < 1$
ethylbenzene	Benzene, ethyl-	100-41-4	$\geq 0 - < 1$

## SECTION 4. FIRST AID MEASURES

General advice : First aid personnel should pay attention to their own safety. Immediately remove contaminated clothing.

If inhaled : If difficulties occur after vapour/aerosol has been inhaled, remove to fresh air and seek medical attention.

# SAFETY DATA SHEET

## MasterFinish RL 220

Version 2.0      Revision Date: 08/15/2023      SDS Number: 000000260374      Date of last issue: 07/28/2023  
Date of first issue: 01/09/2023

---

- In case of skin contact : After contact with skin, wash immediately with plenty of water and soap.  
Under no circumstances should organic solvent be used.  
If irritation develops, seek medical attention.
- In case of eye contact : Remove contact lenses, if present.  
Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.
- If swallowed : Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.  
Do NOT induce vomiting.
- Most important symptoms and effects, both acute and delayed : May be fatal if swallowed and enters airways.  
Causes skin irritation.  
Causes serious eye irritation.  
May cause genetic defects.  
May cause cancer.  
Causes damage to organs through prolonged or repeated exposure.
- Notes to physician : Treat symptomatically.
- 

### SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Foam  
Water spray  
Dry powder  
Carbon dioxide (CO<sub>2</sub>)
- Unsuitable extinguishing media : water jet
- Specific hazards during fire fighting : See SDS section 10 - Stability and reactivity.
- Hazardous combustion products : harmful vapours  
nitrogen oxides  
fumes/smoke  
carbon black  
carbon oxides
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.
- Special protective equipment for fire-fighters : Wear a self-contained breathing apparatus.
-

**MasterFinish RL 220**

Version 2.0      Revision Date: 08/15/2023      SDS Number: 000000260374      Date of last issue: 07/28/2023  
Date of first issue: 01/09/2023

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Do not breathe vapour/aerosol/spray mists.  
Wear eye/face protection.  
If exposed to high vapour concentration, leave area immediately.  
Use personal protective clothing.  
Handle in accordance with good building materials hygiene and safety practice.
  
- Environmental precautions : Contain contaminated water/firefighting water.  
Do not discharge into drains/surface waters/groundwater.
  
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

**SECTION 7. HANDLING AND STORAGE**

- Advice on protection against fire and explosion : Keep away from open flames, hot surfaces and sources of ignition.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).
  
- Advice on safe handling : Avoid aerosol formation.  
Avoid inhalation of mists/vapours.  
Avoid skin contact.  
Avoid contact with eyes.
  
- Conditions for safe storage : No smoking.  
Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
Electrical installations / working materials must comply with the technological safety standards.
  
- Further information on storage conditions : Avoid all sources of ignition: heat, sparks, open flame.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Ingredients with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
naphthalene	91-20-3	TWA	10 ppm 52 mg/m3	CA AB OEL
		STEL	15 ppm 79 mg/m3	CA AB OEL

**SAFETY DATA SHEET**



**MasterFinish RL 220**

Version 2.0      Revision Date: 08/15/2023      SDS Number: 000000260374      Date of last issue: 07/28/2023  
 Date of first issue: 01/09/2023

		TWA	10 ppm	CA BC OEL
		TWAEV	10 ppm	CA QC OEL
		TWA	10 ppm	ACGIH
1,2,4-trimethylbenzene	95-63-6	TWA	25 ppm 123 mg/m3	CA AB OEL
		TWAEV	25 ppm 123 mg/m3	CA QC OEL
		TWA	25 ppm	CA BC OEL
		TWA	10 ppm	ACGIH
2-butoxyethanol	111-76-2	TWA	20 ppm 97 mg/m3	CA AB OEL
		TWA	20 ppm	CA BC OEL
		TWAEV	20 ppm	CA QC OEL
		TWA	20 ppm	ACGIH
Stoddard solvent	8052-41-3	TWA	100 ppm 572 mg/m3	CA AB OEL
		TWA	290 mg/m3	CA BC OEL
		STEL	580 mg/m3	CA BC OEL
		TWAEV	100 ppm 525 mg/m3	CA QC OEL
		TWA	525 mg/m3	CA ON OEL
		TWA	100 ppm	ACGIH
Trimethylbenzene	25551-13-7	TWA value	25 ppm	ACGIHTLV
		TWA value	25 ppm 125 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		REL value	25 ppm 125 mg/m3	NIOSH
		TWA	25 ppm 123 mg/m3	CA AB OEL
		TWAEV	25 ppm 123 mg/m3	CA QC OEL
		TWA	25 ppm	CA BC OEL
		TWA	25 ppm	ACGIH
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	TWA (Mist)	5 mg/m3	CA AB OEL
		STEL (Mist)	10 mg/m3	CA AB OEL
		TWAEV (Mist)	5 mg/m3	CA QC OEL
		STEV (Mist)	10 mg/m3	CA QC OEL
		TWA (Mist)	1 mg/m3	CA BC OEL
		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
Distillates (petroleum), solvent-dewaxed light paraffinic	64742-56-9	TWA value (Inhalable fraction)	5 mg/m3	ACGIHTLV
		TWA (Mist)	5 mg/m3	CA AB OEL
		STEL (Mist)	10 mg/m3	CA AB OEL
		TWAEV (Mist)	5 mg/m3	CA QC OEL
		STEV (Mist)	10 mg/m3	CA QC OEL
		TWA (Mist)	1 mg/m3	CA BC OEL

# SAFETY DATA SHEET



## MasterFinish RL 220

Version 2.0      Revision Date: 08/15/2023      SDS Number: 000000260374      Date of last issue: 07/28/2023  
Date of first issue: 01/09/2023

		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
--	--	------------------------------------	---------	-------

**Engineering measures** : Ensure adequate ventilation.

### Personal protective equipment

**Respiratory protection** : When workers are facing concentrations above the occupational exposure limits they must use appropriate certified respirators.  
Use NIOSH approved respiratory protection.

**Hand protection**

**Remarks** : Wear chemical resistant protective gloves. Manufacturer's directions for use should be observed because of great diversity of types.

**Eye protection** : Tightly fitting safety goggles (chemical goggles).

**Skin and body protection** : Body protection must be chosen based on level of activity and exposure.

**Protective measures** : Do not inhale gases/vapours/aerosols.  
Avoid contact with the skin, eyes and clothing.  
Avoid exposure - obtain special instructions before use.  
Handle in accordance with good building materials hygiene and safety practice.  
Wearing of closed work clothing is recommended.

**Hygiene measures** : When using, do not eat, drink or smoke.  
Hands and/or face should be washed before breaks and at the end of the shift.  
At the end of the shift the skin should be cleaned and skin-care agents applied.  
Remove contaminated clothing immediately and clean before re-use or dispose it if necessary.  
Gloves must be inspected regularly and prior to each use.  
Replace if necessary (e.g. pinhole leaks).

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance** : liquid

**Color** : clear

**Odor** : aromatic

**Odor Threshold** : No data available

**pH** : No data available

# SAFETY DATA SHEET



## MasterFinish RL 220

Version 2.0      Revision Date: 08/15/2023      SDS Number: 000000260374      Date of last issue: 07/28/2023  
Date of first issue: 01/09/2023

---

Melting point : No applicable information available.

Freezing point : No applicable information available.

Boiling point : 161 °C

Flash point : 39.8 °C

Evaporation rate : not determined

Flammability (liquids) : Combustible liquid.

Upper explosion limit / Upper flammability limit : 6.0 %(V)

Lower explosion limit / Lower flammability limit : 1.0 %(V)

Vapor pressure : No data available

Relative vapor density : 4.5

Relative density : No applicable information available.

Density : approx. 1 g/cm<sup>3</sup>

Solubility(ies)  
Water solubility : slightly soluble

Solubility in other solvents : No applicable information available.

Partition coefficient: n-octanol/water : No applicable information available.

Autoignition temperature : 232 °C

Decomposition temperature : No decomposition if stored and handled as prescribed/indicated.

Viscosity  
Viscosity, dynamic : not determined

Viscosity, kinematic : not determined

Explosive properties : Not explosive

Oxidizing properties : Based on its structural properties the product is not classified as oxidizing.

Sublimation point : No applicable information available.



# SAFETY DATA SHEET



## MasterFinish RL 220

Version 2.0      Revision Date: 08/15/2023      SDS Number: 000000260374      Date of last issue: 07/28/2023  
Date of first issue: 01/09/2023

---

Molecular weight : Not applicable

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity : No hazardous reactions if stored and handled as prescribed/indicated.

Chemical stability : The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions : The product is stable if stored and handled as prescribed/indicated.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Strong acids  
Strong bases  
Strong oxidizing agents  
Strong reducing agents

Hazardous decomposition products : Traces of the substances/groups of substances are released as decomposition products of the dry substance.  
carbon oxides  
nitrogen oxides  
Hydrocarbons

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Acute toxicity

Not classified based on available information.

#### Skin corrosion/irritation

Causes skin irritation.

#### Serious eye damage/eye irritation

Causes serious eye irritation.

#### Respiratory or skin sensitization

#### Skin sensitization

Not classified based on available information.

#### Respiratory sensitization

Not classified based on available information.

#### Germ cell mutagenicity

May cause genetic defects.

#### Carcinogenicity

May cause cancer.

<b>IARC</b>	Group 1: Carcinogenic to humans	
	benzene	71-43-2
	Group 2B: Possibly carcinogenic to humans	
	ethylbenzene	100-41-4

# SAFETY DATA SHEET



## MasterFinish RL 220

Version 2.0      Revision Date: 08/15/2023      SDS Number: 000000260374      Date of last issue: 07/28/2023  
Date of first issue: 01/09/2023

---

Group 2B: Possibly carcinogenic to humans  
cumene      98-82-8  
Group 2B: Possibly carcinogenic to humans  
naphthalene      91-20-3

### Reproductive toxicity

Not classified based on available information.

### STOT-single exposure

Not classified based on available information.

### STOT-repeated exposure

Causes damage to organs (Central nervous system) through prolonged or repeated exposure.

### Aspiration toxicity

May be fatal if swallowed and enters airways.

### Product:

May also damage the lung at swallowing (aspiration hazard).

### Further information

### Product:

Remarks : Health injuries are not known or expected under normal use. The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

---

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

### Product:

### Ecotoxicology Assessment

Acute aquatic toxicity : Harmful to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

### Persistence and degradability

No data available

### Bioaccumulative potential

No data available

### Mobility in soil

No data available

### Other adverse effects

### Product:

Additional ecological information : Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual

# SAFETY DATA SHEET



## MasterFinish RL 220

Version 2.0      Revision Date: 08/15/2023      SDS Number: 000000260374      Date of last issue: 07/28/2023  
Date of first issue: 01/09/2023

---

components.

---

### SECTION 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

- Waste from residues : Dispose of in accordance with national, state and local regulations.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Do not discharge into drains/surface waters/groundwater.
- Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

---

### SECTION 14. TRANSPORT INFORMATION

#### International Regulations

##### UNRTDG

- UN number : UN 1993  
Proper shipping name : FLAMMABLE LIQUID, N.O.S.  
Class : 3  
Packing group : III  
Labels : 3

##### IATA-DGR

- UN/ID No. : UN 1993  
Proper shipping name : Flammable liquid, n.o.s.  
(STODDARD SOLVENT)  
Class : 3  
Packing group : III  
Labels : Flammable Liquids  
Packing instruction (cargo aircraft) : 366  
Packing instruction (passenger aircraft) : 355

##### IMDG-Code

- UN number : UN 1993  
Proper shipping name : FLAMMABLE LIQUID, N.O.S.  
(STODDARD SOLVENT)  
Class : 3  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-E  
Marine pollutant : no

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### Domestic regulation

#### TDG

# SAFETY DATA SHEET



## MasterFinish RL 220

Version 2.0      Revision Date: 08/15/2023      SDS Number: 000000260374      Date of last issue: 07/28/2023  
Date of first issue: 01/09/2023

---

UN number : UN 1993  
Proper shipping name : FLAMMABLE LIQUID, N.O.S.  
  
(STODDARD SOLVENT)  
Class : 3  
Packing group : III  
Labels : 3  
ERG Code : 128  
Marine pollutant : no

---

### SECTION 15. REGULATORY INFORMATION

**The ingredients of this product are reported in the following inventories:**

TSCA : All substances listed as active on the TSCA inventory  
  
DSL : All components of this product are on the Canadian DSL

---

### SECTION 16. OTHER INFORMATION

#### Full text of other abbreviations

29 CFR 1910.1000 (Table Z-1-A) : OSHA - Table Z-1-A (29 CFR 1910.1000)  
ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
ACGIHTLV : American Conference of Governmental Industrial Hygienists - threshold limit values (US)  
CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)  
CA BC OEL : Canada. British Columbia OEL  
CA ON OEL : Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.  
CA QC OEL : Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for air-borne contaminants  
  
NIOSH : NIOSH Pocket Guide to Chemical Hazards (US)  
29 CFR 1910.1000 (Table Z-1-A) / TWA value : Time Weighted Average (TWA):  
ACGIH / TWA : 8-hour, time-weighted average  
ACGIHTLV / TWA value : Time Weighted Average (TWA):  
CA AB OEL / TWA : 8-hour Occupational exposure limit  
CA AB OEL / STEL : 15-minute occupational exposure limit  
CA BC OEL / TWA : 8-hour time weighted average  
CA BC OEL / STEL : short-term exposure limit  
CA ON OEL / TWA : Time-Weighted Average Limit (TWA)  
CA QC OEL / TWA/EV : Time-weighted average exposure value  
CA QC OEL / STEV : Short-term exposure value  
NIOSH / REL value : Recommended exposure limit (REL):

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with

# SAFETY DATA SHEET



## MasterFinish RL 220

Version	Revision Date:	SDS Number:	Date of last issue: 07/28/2023
2.0	08/15/2023	000000260374	Date of first issue: 01/09/2023

---

x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECl - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Revision Date : 08/15/2023  
Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CA / EN