

## MasterFlow 649 GROUT PART B

Version 2.0      Revision Date: 11/22/2021      SDS Number: 000000261487      Date of last issue: 08/28/2020  
Date of first issue: 08/28/2020

---

**SECTION 1. IDENTIFICATION**

Product name : MasterFlow 649 GROUT PART B  
Product code : 000000000051680977 000000000051680977  
Other means of identification : MFlow 649 GRT PTB

**Manufacturer or supplier's details**

Company name of supplier : Master Builders Solutions Canada Inc.  
Address : 1800 CLARK BLVD  
Brampton ON L6T 4M7  
Emergency telephone : ChemTel: +1-813-248-0585;  
National Emergency Telephone Number : USA: +1-800-255-3924 ChemTel contract no. MIS9240420

**Recommended use of the chemical and restrictions on use**

Recommended use : Injection or grouting applications  
Restrictions on use : Reserved for industrial and professional use.

---

**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with the Hazardous Products Regulations**

Specific target organ toxicity : Category 3  
- single exposure

**GHS label elements**

Hazard pictograms : 

Signal Word : Danger

Hazard Statements : H331 Toxic if inhaled.  
H314 Causes severe skin burns and eye damage.  
H302 Harmful if swallowed.  
H317 May cause an allergic skin reaction.  
H335 May cause respiratory irritation.  
H361d Suspected of damaging the unborn child.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.

Precautionary Statements : **Prevention:**

## MasterFlow 649 GROUT PART B

Version	Revision Date:	SDS Number:	Date of last issue: 08/28/2020
2.0	11/22/2021	000000261487	Date of first issue: 08/28/2020

---

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P261 Avoid breathing mist or vapors.  
P264 Wash skin thoroughly after handling.  
P270 Do not eat, drink or smoke when using this product.  
P271 Use only outdoors or in a well-ventilated area.  
P272 Contaminated work clothing must not be allowed out of the workplace.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:**

P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell. Rinse mouth.  
P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.  
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.  
P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  
P363 Wash contaminated clothing before reuse.  
P391 Collect spillage.

**Storage:**

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
P405 Store locked up.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

None known.

---

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture  
Chemical nature : curing agent

## MasterFlow 649 GROUT PART B

Version 2.0      Revision Date: 11/22/2021      SDS Number: 000000261487      Date of last issue: 08/28/2020  
 Date of first issue: 08/28/2020

**Components**

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Fatty acids, tall-oil, reaction products with tetraethylenepentamine	Fatty acids, tall-oil, reaction products with tetraethylene-pentamine	68953-36-6	$\geq 70 - < 90$
2,2'-iminodi(ethylamine)	Diethylenetri-amine	111-40-0	$\geq 0 - < 20$
3,6,9-triazaundecamethylene-1,11-diamine	Tetraethylene-pentamine	112-57-2	$\geq 5 - < 10$
N,N'-bis(3-aminopro- pyl)ethylenediamine	1,3-Propanedia- mine, N,N''-1,2-ethanediylbis-	10563-26-5	$\geq 0 - < 20$
triethylenetetramine	1,2-Ethanediamine, N,N'-bis(2-aminoethyl)-	112-24-3	$\geq 0 - < 20$
2,4,6-tris(dimethylaminomethyl)phenol	Phenol, 2,4,6-tris[(dimethylamino)methyl]-	90-72-2	$\geq 1 - < 5$
N,N-Bis(2-amino-ethyl)ethylenediamine	1,2-Ethanediamine, N,N-bis(2-aminoethyl)-	4097-89-6	$\geq 0 - < 5$
Salicylic acid	Benzoic acid, 2-hydroxy-	69-72-7	$\geq 0 - < 1$
Fatty acids, C18-unsatd., trimers, compds. with oleylamine	Fatty acids, C <sup>18</sup> -unsatd., trimers, compds. with oleylamine	147900-93-4	$\geq 0.1 - < 1$
N-(2-aminoethyl)-1,3-propanediamine	1,3-Propanedia- mine, N-(2-aminoethyl)-	13531-52-7	$\geq 0 - \leq 5$

Actual concentration is withheld as a trade secret

**SECTION 4. FIRST AID MEASURES**

- General advice : First aid personnel should pay attention to their own safety. Immediately remove contaminated clothing.
- If inhaled : If difficulties occur after vapour/aerosol has been inhaled, remove to fresh air and seek medical attention.
- In case of skin contact : After contact with skin, wash immediately with plenty of water and soap. Under no circumstances should organic solvent be used. If irritation develops, seek medical attention.

**MasterFlow 649 GROUT PART B**

Version	Revision Date:	SDS Number:	Date of last issue: 08/28/2020
2.0	11/22/2021	000000261487	Date of first issue: 08/28/2020

---

- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.  
Keep eye wide open while rinsing.  
Remove contact lenses.  
Seek medical advice.
- If swallowed : Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.  
Do not induce vomiting unless told to by a poison control center or doctor.
- Most important symptoms and effects, both acute and delayed : Toxic if inhaled.  
Causes severe skin burns and eye damage.  
Harmful if swallowed.  
May cause an allergic skin reaction.  
May cause respiratory irritation.  
Suspected of damaging the unborn child.
- Notes to physician : Treat symptomatically.
- 

**SECTION 5. FIRE-FIGHTING MEASURES**

- Suitable extinguishing media : Foam  
Water spray  
Dry powder  
Carbon dioxide (CO<sub>2</sub>)
- Unsuitable extinguishing media : water jet
- Hazardous combustion products : nitrogen oxides  
Carbon oxides  
fumes/smoke  
carbon black  
corrosive gases/vapours
- Further information : The degree of risk is governed by the burning substance and the fire conditions.  
Contaminated extinguishing water must be disposed of in accordance with official regulations.
- Special protective equipment for fire-fighters : Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.
- 

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Use personal protective clothing.  
Do not breathe vapour/aerosol/spray mists.  
Handle in accordance with good building materials hygiene and safety practice.
- Environmental precautions : Contain contaminated water/firefighting water.  
Do not discharge into drains/surface waters/groundwater.
-

## MasterFlow 649 GROUT PART B

Version	Revision Date:	SDS Number:	Date of last issue: 08/28/2020
2.0	11/22/2021	000000261487	Date of first issue: 08/28/2020

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Pick up with suitable appliance and dispose of.

**SECTION 7. HANDLING AND STORAGE**

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Advice on safe handling : Handle and open container with care.  
Wear personal protective equipment.  
Avoid contact with skin and eyes.  
Avoid aerosol formation.  
Keep container tightly sealed.  
Keep away from sources of ignition - No smoking.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame.  
Protect from direct sunlight.  
Store protected against freezing.

Recommended storage temperature : > 4 °C

Further information on storage stability : PROTECT FROM FREEZING DURING THE COLD-SEASON (BELOW 40°F / 5°C ).

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION****Ingredients with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
2,2'-iminodi(ethylamine)	111-40-0	TWA value	1 ppm	ACGIHTLV
		REL value	1 ppm 4 mg/m3	NIOSH
		TWA value	1 ppm 4 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA	1 ppm 4.2 mg/m3	CA AB OEL
		TWA	1 ppm	CA BC OEL
		TWAEV	1 ppm	CA QC OEL

## MasterFlow 649 GROUT PART B

Version 2.0      Revision Date: 11/22/2021      SDS Number: 000000261487      Date of last issue: 08/28/2020  
 Date of first issue: 08/28/2020

			4.2 mg/m <sup>3</sup>	
		TWA	1 ppm	ACGIH
triethylenetetramine	112-24-3	TWA	0.5 ppm 3 mg/m <sup>3</sup>	CA ON OEL

**Engineering measures** : Ensure adequate ventilation.

**Personal protective equipment**

**Respiratory protection** : Wear appropriate certified respirator when exposure limits may be exceeded.  
Use NIOSH approved respiratory protection.

**Hand protection**

**Remarks** : Wear chemical resistant protective gloves. Manufacturer's directions for use should be observed because of great diversity of types.

**Eye protection** : Tightly fitting safety goggles (chemical goggles) and face shield.

**Skin and body protection** : Body protection must be chosen depending on activity and possible exposure, e.g. head protection, apron, protective boots, chemical-protection suit.

**Protective measures** : Do not inhale gases/vapours/aerosols.  
Avoid contact with the skin, eyes and clothing.  
Handle in accordance with good building materials hygiene and safety practice.

**Hygiene measures** : When using, do not eat, drink or smoke.  
Hands and/or face should be washed before breaks and at the end of the shift.  
At the end of the shift the skin should be cleaned and skin-care agents applied.  
Gloves must be inspected regularly and prior to each use.  
Replace if necessary (e.g. pinhole leaks).

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

**Appearance** : liquid

**Color** : amber

**Odor** : ammonia-like

**Odor Threshold** : not determined

**pH** : No data available

**Melting point** : No data available

## MasterFlow 649 GROUT PART B

Version      Revision Date:      SDS Number:      Date of last issue: 08/28/2020  
2.0          11/22/2021          000000261487      Date of first issue: 08/28/2020

---

Freezing point	:	No data available
Boiling point	:	> 200 °C
Flash point	:	163 °C
		The product has not been tested. The statement has been derived from the properties of the individual components.
Evaporation rate	:	No data available
Flammability (liquids)	:	Not classified as a flammability hazard
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	< 0.01 hPa (20 °C)
Relative vapor density	:	Heavier than air.
Relative density	:	No data available
Density	:	0.96 g/cm <sup>3</sup> (20 °C)
Solubility(ies)		
Water solubility	:	insoluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	not applicable for mixtures
Autoignition temperature	:	321 °C
		The product has not been tested. The statement has been derived from the properties of the individual components.
Decomposition temperature	:	No decomposition if stored and handled as prescribed/indicated.
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	No data available
Explosive properties	:	Not explosive
Oxidizing properties	:	Based on its structural properties the product is not classified as oxidizing.

## MasterFlow 649 GROUT PART B

Version	Revision Date:	SDS Number:	Date of last issue: 08/28/2020
2.0	11/22/2021	000000261487	Date of first issue: 08/28/2020

---

Sublimation point : No data available

Molecular weight : Not applicable

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No hazardous reactions if stored and handled as prescribed/indicated.

Chemical stability : The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions : The product is stable if stored and handled as prescribed/indicated.

Conditions to avoid : See SDS section 7 - Handling and storage.

Incompatible materials : Oxidizing agents  
strong alkalis  
Acids

Hazardous decomposition products : No hazardous decomposition products if stored and handled as prescribed/indicated.

---

**SECTION 11. TOXICOLOGICAL INFORMATION****Acute toxicity**

Harmful if swallowed.

Toxic if inhaled.

**Product:**

Acute oral toxicity : Acute toxicity estimate: 1,948 mg/kg  
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: 8.26 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: Calculation method

**Skin corrosion/irritation**

Causes severe skin burns and eye damage.

**Serious eye damage/eye irritation**

Causes serious eye damage.

**Respiratory or skin sensitization****Skin sensitization**

May cause an allergic skin reaction.

**Respiratory sensitization**

Not classified based on available information.



## MasterFlow 649 GROUT PART B

Version 2.0      Revision Date: 11/22/2021      SDS Number: 000000261487      Date of last issue: 08/28/2020  
Date of first issue: 08/28/2020

---

**Germ cell mutagenicity**

Not classified based on available information.

**Carcinogenicity**

Not classified based on available information.

**Reproductive toxicity**

Suspected of damaging the unborn child.

**STOT-single exposure**

May cause respiratory irritation.

**STOT-repeated exposure**

Not classified based on available information.

**Aspiration toxicity**

Not classified based on available information.

**Further information****Product:**

Remarks : The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Product:****Ecotoxicology Assessment**

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

**Components:****Fatty acids, tall-oil, reaction products with tetraethylenepentamine:**

M-Factor (Acute aquatic toxicity) : 10

M-Factor (Chronic aquatic toxicity) : 1

**Persistence and degradability**

No data available

**Bioaccumulative potential**

No data available

**Mobility in soil**

No data available

## MasterFlow 649 GROUT PART B

Version	Revision Date:	SDS Number:	Date of last issue: 08/28/2020
2.0	11/22/2021	000000261487	Date of first issue: 08/28/2020

**Other adverse effects****Product:**

Additional ecological information : Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues : Dispose of in accordance with local authority regulations. Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

**SECTION 14. TRANSPORT INFORMATION****International Regulations****UNRTDG**

UN number : UN 2735

Proper shipping name : AMINES, LIQUID, CORROSIVE, N.O.S.  
(DIETHYLENETRIAMINE, TRIETHYLENETETRAMINE, FATTY ACIDS, TALL-OIL, REACTION PRODUCTS WITH TETRAETHYLENEPENTAMINE)

Class : 8

Packing group : II

Labels : 8

**IATA-DGR**

UN/ID No. : UN 2735

Proper shipping name : AMINES, LIQUID, CORROSIVE, N.O.S.  
(DIETHYLENETRIAMINE, TRIETHYLENETETRAMINE)

Class : 8

Packing group : II

Labels : Corrosive

Packing instruction (cargo aircraft) : 855

Packing instruction (passenger aircraft) : 851

**IMDG-Code**

UN number : UN 2735

Proper shipping name : AMINES, LIQUID, CORROSIVE, N.O.S.  
(DIETHYLENETRIAMINE, TRIETHYLENETETRAMINE, FATTY ACIDS, TALL-OIL, REACTION PRODUCTS WITH TETRAETHYLENEPENTAMINE)

Class : 8

Packing group : II

Labels : 8

## MasterFlow 649 GROUT PART B

Version	Revision Date:	SDS Number:	Date of last issue: 08/28/2020
2.0	11/22/2021	000000261487	Date of first issue: 08/28/2020

EmS Code : F-A, S-B  
 Marine pollutant : yes

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**Domestic regulation****TDG**

UN number : UN 2735  
 Proper shipping name : AMINES, LIQUID, CORROSIVE, N.O.S.  
 (DIETHYLENETRIAMINE, TRIETHYLENETETRAMINE,  
 FATTY ACIDS, TALL-OIL, REACTION PRODUCTS WITH  
 TETRAETHYLENEPENTAMINE)  
 Class : 8  
 Packing group : II  
 Labels : 8  
 ERG Code : 153  
 Marine pollutant : no

**Special precautions for user**

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

**SECTION 15. REGULATORY INFORMATION****The ingredients of this product are reported in the following inventories:**

TSCA : All substances listed as active on the TSCA inventory  
 DSL : All components of this product are on the Canadian DSL

**SECTION 16. OTHER INFORMATION****Full text of other abbreviations**

29 CFR 1910.1000 (Table Z-1-A) : OSHA - Table Z-1-A (29 CFR 1910.1000)  
 ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
 ACGIHTLV : American Conference of Governmental Industrial Hygienists - threshold limit values (US)  
 CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)  
 CA BC OEL : Canada. British Columbia OEL  
 CA ON OEL : Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.  
 CA QC OEL : Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants  
 NIOSH : NIOSH Pocket Guide to Chemical Hazards (US)  
 29 CFR 1910.1000 (Table Z-1-A) / TWA value : Time Weighted Average (TWA):

## MasterFlow 649 GROUT PART B

Version	Revision Date:	SDS Number:	Date of last issue: 08/28/2020
2.0	11/22/2021	000000261487	Date of first issue: 08/28/2020

ACGIH / TWA	:	8-hour, time-weighted average
ACGIHTLV / TWA value	:	Time Weighted Average (TWA):
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA ON OEL / TWA	:	Time-Weighted Average Limit (TWA)
CA QC OEL / TWAEV	:	Time-weighted average exposure value
NIOSH / REL value	:	Recommended exposure limit (REL):

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Revision Date	:	11/22/2021
Date format	:	mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CA / EN