

## MasterTop TC 493 white PART A

Version            Revision Date:            SDS Number:            Date of last issue: -  
1.0                10/09/2020                000000261544            Date of first issue: 10/09/2020

---

**SECTION 1. IDENTIFICATION**

Product name                                : MasterTop TC 493 white PART A  
Product code                                : 000000000055515845 000000000055515845  
Other means of identification            : No data available

**Manufacturer or supplier's details**

Company name of supplier                : Master Builders Solutions Canada Inc.  
Address                                        : 1800 CLARK BLVD  
    : Brampton ON L6T 4M7  
Emergency telephone                      : ChemTel: +1-813-248-0585;

**Recommended use of the chemical and restrictions on use**


Recommended use                          : Product for construction chemicals  
Restrictions on use                         : Reserved for industrial and professional use.

---

**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with the Hazardous Products Regulations**

FLAMMABLE LIQUIDS                      : Category 3

**GHS label elements**

Hazard pictograms                        : 

Signal Word                                 : Warning

Hazard Statements                         : H226 Flammable liquid and vapour.

Precautionary Statements                : **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
P243 Take action to prevent static discharges.  
P241 Use explosion-proof [electrical/ ventilating/ lighting/ .?] equipment.  
P233 Keep container tightly closed.  
P240 Ground and bond container and receiving equipment.  
P242 Use only non-sparking tools.

**Response:**

## MasterTop TC 493 white PART A

Version 1.0      Revision Date: 10/09/2020      SDS Number: 000000261544      Date of last issue: -  
 Date of first issue: 10/09/2020

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
 P370 + P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.

**Storage:**

P403 + P235 Store in a well-ventilated place. Keep cool.

**Disposal:**

P501 Dispose of contents/container to appropriate hazardous waste collection point.

**Other hazards**

No data available.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical nature : No data available.

**Components**

Chemical name	CAS-No.	Concentration (% w/w)
Titanium dioxide	13463-67-7	>= 25 - < 50
n-Butyl acetate	123-86-4	>= 7 - < 10
aluminium hydroxide	21645-51-2	>= 0 - < 3
ethylbenzene	100-41-4	>= 0 - < 0.2

**SECTION 4. FIRST AID MEASURES**

- General advice : Move out of dangerous area.  
 Show this material safety data sheet to the doctor in attendance.  
 Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.  
 If symptoms persist, call a physician.
- In case of skin contact : If on skin, rinse well with water.  
 If on clothes, remove clothes.
- In case of eye contact : Flush eyes with water as a precaution.  
 Remove contact lenses.  
 Protect unharmed eye.  
 Keep eye wide open while rinsing.  
 If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
 Do not give milk or alcoholic beverages.  
 Never give anything by mouth to an unconscious person.  
 If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and : None known.

## MasterTop TC 493 white PART A

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/09/2020	000000261544	Date of first issue: 10/09/2020

delayed

Notes to physician : Treat symptomatically.

**SECTION 5. FIRE-FIGHTING MEASURES**

- Suitable extinguishing media : Water spray  
Foam  
Dry powder  
Carbon dioxide (CO<sub>2</sub>)
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.
- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

**SECTION 7. HANDLING AND STORAGE**

- Advice on protection against fire and explosion : Product is not explosive.
- Do not spray on a naked flame or any incandescent material.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).

## MasterTop TC 493 white PART A

Version 1.0      Revision Date: 10/09/2020      SDS Number: 000000261544      Date of last issue: -  
 Date of first issue: 10/09/2020

- Keep away from open flames, hot surfaces and sources of ignition.
- Advice on safe handling : Avoid formation of aerosol.  
 For personal protection see section 8.  
 Smoking, eating and drinking should be prohibited in the application area.  
 Take precautionary measures against static discharges.  
 Provide sufficient air exchange and/or exhaust in work rooms.  
 Open drum carefully as content may be under pressure.  
 Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : no smoking  
 Keep container tightly closed in a dry and well-ventilated place.  
 Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
 Observe label precautions.  
 Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage conditions : Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame.  
 Protect from direct sunlight.
- Materials to avoid : Observe VCI storage rules.
- Further information on storage stability : No data available

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
n-Butyl acetate	123-86-4	STEL value	150 ppm	ACGIHTLV
		TWA value	50 ppm	ACGIHTLV
		REL value	150 ppm 710 mg/m <sup>3</sup>	NIOSH
		STEL value	200 ppm 950 mg/m <sup>3</sup>	NIOSH
		PEL	150 ppm 710 mg/m <sup>3</sup>	29 CFR 1910.1000 (Table Z-1)
		STEL value	200 ppm 950 mg/m <sup>3</sup>	29 CFR 1910.1000 (Table Z-1-A)
		TWA value	150 ppm 710 mg/m <sup>3</sup>	29 CFR 1910.1000 (Table Z-1-A)
		TWA	150 ppm	CA AB OEL

## MasterTop TC 493 white PART A

Version 1.0      Revision Date: 10/09/2020      SDS Number: 000000261544      Date of last issue: -  
 Date of first issue: 10/09/2020

			713 mg/m3	
		STEL	200 ppm 950 mg/m3	CA AB OEL
		TWA	20 ppm	CA BC OEL
		TWAEV	150 ppm 713 mg/m3	CA QC OEL
		STEV	200 ppm 950 mg/m3	CA QC OEL
		TWA	50 ppm	ACGIH
		STEL	150 ppm	ACGIH
Titanium dioxide	13463-67-7	TWA value	10 mg/m3	ACGIHTLV
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Total dust)	10 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA	10 mg/m3	CA AB OEL
		TWA (Total dust)	10 mg/m3	CA BC OEL
		TWA (respirable dust fraction)	3 mg/m3	CA BC OEL
		TWAEV (total dust)	10 mg/m3	CA QC OEL
		TWA	10 mg/m3 (Titanium dioxide)	ACGIH
aluminium hydroxide	21645-51-2	TWA value (Respirable fraction)	1 mg/m3	ACGIHTLV
		TWAEV (total dust)	10 mg/m3	CA QC OEL
		TWA (Respirable)	1 mg/m3 (Aluminum)	CA BC OEL
		TWA (Respirable particulate matter)	1 mg/m3 (Aluminum)	ACGIH

**Engineering measures** : No applicable information available.

**Personal protective equipment**

Respiratory protection : Wear respiratory protection if ventilation is inadequate.

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water  
Tightly fitting safety goggles

Skin and body protection : Impervious clothing  
Choose body protection according to the amount and con-

## MasterTop TC 493 white PART A

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/09/2020	000000261544	Date of first issue: 10/09/2020

---

centration of the dangerous substance at the work place.

Protective measures : Do not inhale gases/vapours/aerosols.  
 Avoid contact with the skin, eyes and clothing.  
 Avoid exposure - obtain special instructions before use.  
 Handle in accordance with good building materials hygiene and safety practice.  
 Wearing of closed work clothing is recommended.

Hygiene measures : Wash hands before breaks and at the end of workday.

---

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

Color : various colours

Odor : strong, ester-like

Odor Threshold : No data available

pH : not applicable insoluble

Freezing point : No applicable information available.

Melting point : No applicable information available.

Boiling point : 138 °C

Flash point : 38 °C

Method: Flash Point by Tag Closed Tester.

Evaporation rate : No applicable information available.

Flammability (solid, gas) : not determined

Upper explosion limit / Upper flammability limit : 13.1 %(V)  
 The product has not been tested. The statement has been derived from the properties of the individual components.

Lower explosion limit / Lower flammability limit : 1 %(V)  
 The product has not been tested. The statement has been derived from the properties of the individual components.

Vapor pressure : 3.5 hPa (25 °C)  
 The product has not been tested. The statement has been derived from the properties of the individual components.

Relative vapor density : Heavier than air.

## MasterTop TC 493 white PART A

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/09/2020	000000261544	Date of first issue: 10/09/2020

---

Relative density	:	No applicable information available.
Density	:	11 lb/USg (20 °C)
Bulk density	:	not applicable
Solubility(ies)		
Water solubility	:	insoluble
Solubility in other solvents	:	No applicable information available.
Partition coefficient: n-octanol/water	:	No data available.
Autoignition temperature	:	533 °C The product has not been tested. The statement has been derived from the properties of the individual components.
Decomposition temperature	:	No decomposition if stored and handled as prescribed/indicated.
Viscosity		
Viscosity, dynamic	:	No applicable information available.
Viscosity, kinematic	:	No applicable information available.
Explosive properties	:	Not explosive Not explosive
Oxidizing properties	:	Based on its structural properties the product is not classified as oxidizing.
Sublimation point	:	No applicable information available.
Molecular weight	:	No data available

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	No decomposition if stored and applied as directed. Vapors may form explosive mixture with air.
Conditions to avoid	:	Avoid all sources of ignition: heat, sparks, open flame.  Heat, flames and sparks.
Incompatible materials	:	Strong acids Strong bases Strong oxidizing agents Strong reducing agents

## MasterTop TC 493 white PART A

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/09/2020	000000261544	Date of first issue: 10/09/2020

---

Hazardous decomposition products : No hazardous decomposition products if stored and handled as prescribed/indicated.

---

**SECTION 11. TOXICOLOGICAL INFORMATION****Acute toxicity**

Not classified based on available information.

**Product:**

Acute oral toxicity : Remarks: No applicable information available.

ATE: > 5,000 mg/kg

Acute inhalation toxicity : Remarks: No applicable information available.

ATE: > 20.0000 mg/l

Remarks: Determined for vapor

ATE: > 5.0000 mg/l

Remarks: Determined for mist

Acute dermal toxicity : Remarks: No applicable information available.

ATE: > 5,000 mg/kg

**Skin corrosion/irritation**

Not classified based on available information.

**Serious eye damage/eye irritation**

Not classified based on available information.

**Respiratory or skin sensitization****Skin sensitization**

Not classified based on available information.

**Respiratory sensitization**

Not classified based on available information.

**Germ cell mutagenicity**

Not classified based on available information.

**Carcinogenicity**

Not classified based on available information.

**Reproductive toxicity**

Not classified based on available information.

**STOT-single exposure**

Not classified based on available information.

**STOT-repeated exposure**

Not classified based on available information.



## MasterTop TC 493 white PART A

Version 1.0      Revision Date: 10/09/2020      SDS Number: 000000261544      Date of last issue: -  
Date of first issue: 10/09/2020

---

**Aspiration toxicity**

Not classified based on available information.

**Product:**

No aspiration hazard expected.

**Further information****Product:**

Remarks : Solvents may degrease the skin.

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity**

No data available

**Persistence and degradability**

No data available

**Bioaccumulative potential****Components:****Titanium dioxide:**

Partition coefficient: n-octanol/water : Remarks: not applicable

**n-Butyl acetate:**

Partition coefficient: n-octanol/water : Pow: 200 (25 °C)  
log Pow: 2.3 (25 °C)  
pH: 7  
Method: Partition coefficient (n-octanol/water), HPLC method.  
GLP: yes

**aluminium hydroxide:**

Partition coefficient: n-octanol/water : Remarks: The value has not been determined because the substance is inorganic.

**ethylbenzene:**

Partition coefficient: n-octanol/water : Pow: 4,170 (20 °C)  
log Pow: 3.6 (20 °C)  
pH: 7.8  
Method: Partition coefficient  
GLP: yes

**Mobility in soil**

No data available

**Other adverse effects****Product:**

## MasterTop TC 493 white PART A

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/09/2020	000000261544	Date of first issue: 10/09/2020

---

Additional ecological information : There is a high probability that the product is not acutely harmful to aquatic organisms. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

---

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues : Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of in accordance with national, state and local regulations. Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

---

**SECTION 14. TRANSPORT INFORMATION****International Regulations****UNRTDG**

UN number : UN 1993  
 Proper shipping name : FLAMMABLE LIQUID, N.O.S. (METHOXYPROPYLACETATE)  
 Class : 3  
 Packing group : III  
 Labels : 3

**IATA-DGR**

UN/ID No. : UN 1993  
 Proper shipping name : FLAMMABLE LIQUID, N.O.S. (METHOXYPROPYLACETATE)  
 Class : 3  
 Packing group : III  
 Labels : Flammable Liquids  
 Packing instruction (cargo aircraft) : 366  
 Packing instruction (passenger aircraft) : 355

**IMDG-Code**

UN number : UN 1993  
 Proper shipping name : FLAMMABLE LIQUID, N.O.S. (METHOXYPROPYLACETATE)  
 Class : 3  
 Packing group : III  
 Labels : 3  
 EmS Code : F-E, S-E  
 Marine pollutant : no

## MasterTop TC 493 white PART A

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/09/2020	000000261544	Date of first issue: 10/09/2020

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**Domestic regulation****TDG**

UN number	: UN 1993
Proper shipping name	: FLAMMABLE LIQUID, N.O.S. (METHOXYPROPYLACETATE)
Class	: 3
Packing group	: III
Labels	: 3
ERG Code	: 128
Marine pollutant	: no

**Special precautions for user**

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

**SECTION 15. REGULATORY INFORMATION****The ingredients of this product are reported in the following inventories:**

DSL	: On the inventory, or in compliance with the inventory
-----	---

**SECTION 16. OTHER INFORMATION****Full text of other abbreviations**

29 CFR 1910.1000 (Table Z-1-A)	: OSHA - Table Z-1-A (29 CFR 1910.1000)
29 CFR 1910.1000 (Table Z-1)	: OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR 1910.1000
ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
ACGIHTLV	: American Conference of Governmental Industrial Hygienists - threshold limit values (US)
CA AB OEL	: Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	: Canada. British Columbia OEL
CA QC OEL	: Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
NIOSH	: NIOSH Pocket Guide to Chemical Hazards (US)
29 CFR 1910.1000 (Table Z-1-A) / STEL value	: Short Term Exposure Limit (STEL):
29 CFR 1910.1000 (Table Z-1-A) / TWA value	: Time Weighted Average (TWA):
29 CFR 1910.1000 (Table Z-1) / PEL	: Permissible exposure limit
ACGIH / TWA	: 8-hour, time-weighted average
ACGIH / STEL	: Short-term exposure limit
ACGIHTLV / STEL value	: Short Term Exposure Limit (STEL):
ACGIHTLV / TWA value	: Time Weighted Average (TWA):

## MasterTop TC 493 white PART A

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/09/2020	000000261544	Date of first issue: 10/09/2020

CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA AB OEL / STEL	:	15-minute occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA QC OEL / TWA EV	:	Time-weighted average exposure value
CA QC OEL / STEV	:	Short-term exposure value
NIOSH / REL value	:	Recommended exposure limit (REL):
NIOSH / STEL value	:	Short Term Exposure Limit (STEL):

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Revision Date : 10/09/2020

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT

**MasterTop TC 493 white PART A**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/09/2020	000000261544	Date of first issue: 10/09/2020

---

PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

CA / EN