

MasterProtect[®] FL 100

Ready-mixed filler suitable for interior and exterior surfaces

DESCRIPTION

MasterProtect FL 100 is a ready to use filler for use on all common building surfaces. It gives a high quality, even surface for painting.

MasterProtect FL 100 is specifically manufactured for the painter to repair and touch up exterior and interior surfaces, both new and old, prior to painting. It is designed for filling joints, hairline cracks etc. by hand application. Unlike conventional fillers, **MasterProtect FL 100** has elastic properties, does not flake off, is permanent and retains its adhesion

ADVANTAGES

- Tough durable filler
- Weather resistant
- Alkali resistant
- Easy to apply
- Quick drying
- High crack resistance
- Excellent adhesion

AREA OF USE

MasterProtect FL 100 is suitable for exterior as well as interior surfaces. When dry,

MasterProtect FL 100 is weather resistant and bonds extremely well to cement and gypsum based plasters and gypsum boards.

It is used as a thin coat filler for patching hairline cracks in walls, ceilings, soffits, repair to damaged plasterwork, paintwork and exposed concrete.

PACKAGING

MasterProtect FL 100 is supplied in 25kg units.

TYPICAL PROPERTIES

Binders	Styrene acrylate
Fillers	Fine precisely graded fillers
Specific gravity	1.65 ±0.05
Toxicity	Non-toxic
Colour	White

PREPARATION OF SURFACE

Ensure that the surface is free from dust, dirt, form oil and contamination. Ridges and undulations must also be removed.

When applying filler to old painted surfaces first wash down with soda / water solution, rinse and allow to dry before filling.

N.B. The use of penetrating primer is recommended on dusting or flaking surfaces, for further information contact Master Builders Solutions Egypt Technical Department.

APPLICATION & CLEANING TOOLS

Apply the filler in a thin, even layer; if the area under repair requires a thick coat. Apply several thin layers, allowing each layer to dry before adding the next.

Lightly sandpaper over the dry final surface before painting preferably within 9 hours of application.

Clean tools and equipment with water after use

COVERAGE

Apply the filler in a thin even layer between 0.5-1.5kg/m² (dependent on substrate conditions). Apply multiple coats if necessary, allowing to dry between layers. Lightly sand down the final surface before overcoating within 24 hours of application. Applied material must not exceed 1mm per coat.

STORAGE AND SHELF LIFE

Store bags in a clean dry area protected from direct sunlight and extreme heat and cold.

Shelf life is 12 months, in original unopened packaging.

MasterProtect[®] FL 100

HEALTH AND SAFETY

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.

NOTE

Field service, where provided, does not constitute supervisory responsibility. For additional information contact your local Master Builders Solutions representative.

Master Builders Solutions reserves the right to have the true cause of any difficulty determined by accepted test methods.

QUALITY AND CARE

All products originating from Master Builders Solutions's Egypt facility are manufactured under a management system independently certified to conform to the requirements of the quality, environmental and occupational health & safety standards ISO 9001:2015, ISO 14001:2015 & OHSAS 18001:2007 standards.

* Properties listed are based on laboratory controlled tests.

® Registered trademark of a MBCC Group member in many countries of the world

Master_Builders_Solutions _CC-EG/Pr_FL100_07_16/v1/10_18

