

# SENERFLEX<sup>®</sup> BELGIAN LACE Finish

## DESCRIPTION

Factory-mixed, 100% acrylic polymer finish coat with advanced technology to improve long-term performance and dirt pick-up resistance. SENERFLEX BELGIAN LACE Finish has a fine "worm-hole" appearance which is achieved by the random aggregate sizes in the finish. The small "worm-hole" look can be circular, random vertical or horizontal.



## FEATURES & BENEFITS

- 100% acrylic polymer chemistry - long-term durability and weather resistance
- Integral colour - reduced maintenance and recoating
- Weather resistant - Repels water and resists wind-driven rain
- Protects - Seals existing, non-moving hairline cracks
- Breathable - Doesn't blister, peel or flake

## PRIMARY USES

- Provides an aesthetically pleasing surface colour and texture for the Exterior Insulation and Finish System.
- Can also be utilized as a textured coating for poured concrete or unit masonry, conventional; stucco, **Classic PB System**, **Secondary Weather Barrier System** and **Channel Adhesive System**, certain insulating concrete forms, and veneer plaster or gypsum wallboard (interior applications only).

## PACKAGING

SENERFLEX BELGIAN LACE Finish is available in 25kg units.

## COLOURS

Available in a wide variety of standard and custom colours.

## COVERAGE

Approximately 11.6m<sup>2</sup> per unit.

## MIXING

- Thoroughly mix the factory-prepared SENERFLEX BELGIAN LACE Finish with a mixer until thoroughly blended.
- A small amount of clean, potable water may be added to adjust workability.
- Additives are not permitted.
- Close container when not in use.
- Clean tools with soap and water immediately after use.

## APPLICATION

- Substrate shall be dry, clean, sound and free of releasing agents, paint or other residue or coatings. Verify substrate is flat, free of fins or planar irregularities greater than 6.4mm in 3m.
- Apply SENERFLEX BELGIAN LACE Finish directly to the TINTED PRIMER with a clean, stainless steel trowel.  
**Note:** In order to minimize the possibility of Base Coat read-through with 330 Maxi-White in BELGIAN LACE, we recommend the use of TINTED PRIMER. Base Coat read-through with SENERFLEX BELGIAN LACE Finish in maxi-white is very applicator dependent.
- Apply and level SENERFLEX BELGIAN LACE Finish during the same operation to minimum obtainable thickness consistent with uniform coverage.
- Maintain a wet edge on SENERFLEX BELGIAN LACE Finish by applying and texturing continually over the wall surface.

# SENERFLEX® BELGIAN LACE Finish

- Work SENERFLEX BELGIAN LACE Finish to corners, joints or other natural breaks and do not allow material to set up within an uninterrupted wall area.
- Float SENERFLEX BELGIAN LACE Finish to achieve final texture.

Note : Minor colour deviations caused by the use of natural stone granular material are possible in different batches. Therefore, only use material from the same batch number for continuous surfaces. Mix the last few pails from one batch with a different batch to minimise any colour differences.

## WATCHPOINTS

- Protect SENERFLEX materials during transportation and installation to avoid physical damage.
- Do not apply SENERFLEX materials in ambient temperatures below 4°C. Provide supplementary heat during installation and drying period (at least 24 hours after installation and until dry) when temperatures less than 4°C prevail.
- Do not apply SENERFLEX materials to frozen surfaces.
- Samples of SENERFLEX BELGIAN LACE Finish are available for colour approval only. Samples for job approval must be made in the field by the applicator, and approved prior to ordering.

## STORAGE & SHELF LIFE

Store SENERFLEX materials in a cool, dry place protected from freezing. Store at no less than 4°C. Protect from extreme heat and direct sunlight. Shelf life is 9 months when unopened and stored as directed.

## SAFETY PRECAUTIONS

As with all chemical products, care should be taken during use and storage to avoid contact with eyes mouth, skin and foodstuffs. If accidentally ingested, seek immediate medical attention. Reseal containers after use. For further information, refer to material safety data sheet.

## NOTE

Field service, where provided, does not constitute supervisory responsibility. For additional information contact your local BASF representative. BASF reserves the right to have the true cause of any difficulty determined by accepted test methods.

## QUALITY AND CARE

All products originating from BASF's Dubai, UAE facility are manufactured under a management system independently certified to conform to the requirements of the quality, environmental and occupational health & safety standards ISO 9001, ISO 14001 and ISO 45001.

\* Properties listed are based on laboratory controlled tests.

® = Registered trademark of the BASF-Group in many countries.

BASF\_CC-UAE/Snf\_BelgLace\_14\_08/v4/10\_17

## STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this BASF publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.

## NOTE

Field service where provided does not constitute supervisory responsibility. Suggestions made by BASF either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not BASF, are responsible for carrying out procedures appropriate to a specific application.