

MasterTile® 530

Coloured, latex modified cement grout for ceramic, glass mosaic, porcelain and non-moisture sensitive natural stones tiles

DESCRIPTION

MasterTile 530 is a fine coloured latex modified powder which, when mixed with water, gives a smooth, easily applied creamy paste for clean grouting of ceramic tiles. It sets to a decorative water resistant finish.

ADVANTAGES

- Water-resistant (suitable for swimming pools).
- Available in a range of colours.
- Resistant to cracking in joints up to 6mm wide.
- Ideal for internal and exterior applications.
- Formulated for Middle East conditions.

PACKAGING

MasterTile 530 is available in 10kg and 25kg sacks.

COMPOSITION

MasterTile 530 is a blend of hydrophobic cement, fillers and organic additives.

STANDARDS

BS 5980 - Cementitious Adhesives and Grouts
ANSI 118.7 (Polymer Modified Cement Grouts)
BS EN 13888 CG2

APPLICATION PROCEDURES

Allow at least 24 hours between fixing tiles and grouting. Mix grout powder with water to give a smooth, thick consistency.

Leave to stand for 15 minutes before using. Apply to tile joints with a squeegee, brush or sponge. Remove surplus grout with a damp sponge. When grouting is completed, polish tiles with a dry cloth.

WATER ADDITION

8.3 litres per 25kg bag
3.3 litres per 10kg bag

WATCHPOINTS

Certain types of tile may stain when in contact with coloured cement grouts, it is therefore advisable to consult the tile manufacturer and carry out trials before use.

For natural stone tiles susceptible to staining, please contact BASF Technical Services.

COVERAGE

1 kg is sufficient for approximately 4 square metres using standard 150 x 150mm tiles.

STORAGE

Store out of direct sunlight, clear of the ground on pallets protected from rainfall. Avoid excessive compaction.

Shelf life is 1 year when stored as above, in original, unopened bags.

SAFETY PRECAUTIONS

As with all chemical products, care should be taken during use and storage to avoid contact with eyes, mouth, skin and foodstuffs (which may also be tainted with vapour until product is fully cured). Treat splashes to eyes and skin immediately. If accidentally ingested, seek immediate medical attention. Reseal containers after use.

NOTE

Field service, where provided, does not constitute supervisory responsibility. For additional information contact your local BASF representative. BASF reserves the right to have the true cause of any difficulty determined by accepted test methods.

MasterTile[®] 530

QUALITY AND CARE

All products originating from MBCC's Dubai, UAE facility are manufactured under a management system independently certified to conform to the requirements of the quality, environmental and occupational health & safety standards ISO 9001, ISO 14001 and OHSAS 18001.

® = Registered trademark of the MBCC-Group in many countries.

MBCC_CC-UAE/Tile_530_09_01/v4/10_16

STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this MBCC publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.

NOTE

Field service where provided does not constitute supervisory responsibility. Suggestions made by MBCC either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not MBCC, are responsible for carrying out procedures appropriate to a specific application.