

# SAFETY DATA SHEET



## MasterFinish RL 220

Version 2.0      Revision Date: 08/15/2023      SDS Number: 000000260374      Date of last issue: 07/28/2023  
Date of first issue: 01/09/2023

---

### SECTION 1. IDENTIFICATION

Product name : MasterFinish RL 220  
Product code : 000000000050701518 000000000050701518

#### Manufacturer or supplier's details

Company name of supplier : Master Builders-Admixtures US,LLC  
Address : 23700 Chagrin Blvd  
Beachwood OH 44122  
Emergency telephone : ChemTel: +1-813-248-0585  
National Emergency Telephone Number : USA: +1-800-255-3924 ChemTel contract no. MIS9240420

#### Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals  
Restrictions on use : Reserved for industrial and professional use.

---

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Aspiration hazard : Category 1  
Flammable liquids : Category 3  
Skin corrosion/irritation : Category 2  
Serious eye damage/eye irritation : Category 2A  
Germ cell mutagenicity : Category 1B  
Carcinogenicity : Category 1B  
Specific target organ toxicity - repeated exposure : Category 1 (Central nervous system)  
Short-term (acute) aquatic hazard : Category 3  
Long-term (chronic) aquatic hazard : Category 3


#### GHS label elements

# SAFETY DATA SHEET

## MasterFinish RL 220

Version 2.0      Revision Date: 08/15/2023      SDS Number: 000000260374      Date of last issue: 07/28/2023  
Date of first issue: 01/09/2023

---

- Hazard pictograms : 
- Signal Word : Danger
- Hazard Statements : H226 Flammable liquid and vapor.  
H319 Causes serious eye irritation.  
H315 Causes skin irritation.  
H304 May be fatal if swallowed and enters airways.  
H350 May cause cancer.  
H340 May cause genetic defects.  
H372 Causes damage to organs (Central nervous system) through prolonged or repeated exposure.  
H402 Harmful to aquatic life.  
H412 Harmful to aquatic life with long lasting effects.
- Precautionary Statements : **Prevention:**  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
P201 Obtain special instructions before use.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P260 Do not breathe dusts or mists.  
P202 Do not handle until all safety precautions have been read and understood.  
P273 Avoid release to the environment.  
P243 Take action to prevent static discharges.  
P241 Use explosion-proof electrical/ ventilating/ lighting/ .? / equipment.  
P270 Do not eat, drink or smoke when using this product.  
P264 Wash face, hands and any exposed skin thoroughly after handling.  
P233 Keep container tightly closed.  
P242 Use only non-sparking tools.  
P240 Ground and bond container and receiving equipment.
- Response:**  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P314 Get medical advice/ attention if you feel unwell.  
P308 + P311 IF exposed or concerned: Call a POISON CENTER/ doctor.  
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
P332 + P313 If skin irritation occurs: Get medical advice/ attention.  
P331 Do NOT induce vomiting.  
P337 + P313 If eye irritation persists: Get medical advice/ attention.  
P362 + P364 Take off contaminated clothing and wash it before

## MasterFinish RL 220

Version 2.0      Revision Date: 08/15/2023      SDS Number: 000000260374      Date of last issue: 07/28/2023  
 Date of first issue: 01/09/2023

reuse.

P370 + P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.

**Storage:**

P405 Store locked up.

P403 + P235 Store in a well-ventilated place. Keep cool.

**Disposal:**

P501 Dispose of contents/container to appropriate hazardous waste collection point.

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical nature : Aromatic hydrocarbons

**Components**

Chemical name	CAS-No.	Concentration (% w/w)
Stoddard solvent	8052-41-3	>= 50 - < 100
2-butoxyethanol	111-76-2	>= 7 - < 10
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	>= 5 - < 10
1,2,4-trimethylbenzene	95-63-6	>= 1 - < 5
Trimethylbenzene	25551-13-7	>= 0.3 - < 5
Distillates (petroleum), solvent-dewaxed light paraffinic	64742-56-9	>= 1 - < 5
naphthalene	91-20-3	>= 0.3 - < 1
cumene	98-82-8	>= 0 - < 1
ethylbenzene	100-41-4	>= 0 - < 1

**SECTION 4. FIRST AID MEASURES**

- General advice : First aid personnel should pay attention to their own safety. Immediately remove contaminated clothing.
- If inhaled : If difficulties occur after vapour/aerosol has been inhaled, remove to fresh air and seek medical attention.
- In case of skin contact : After contact with skin, wash immediately with plenty of water and soap. Under no circumstances should organic solvent be used. If irritation develops, seek medical attention.
- In case of eye contact : Remove contact lenses, if present. Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.
- If swallowed : Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention. Do NOT induce vomiting.

**MasterFinish RL 220**

Version 2.0      Revision Date: 08/15/2023      SDS Number: 000000260374      Date of last issue: 07/28/2023  
Date of first issue: 01/09/2023

---

Most important symptoms and effects, both acute and delayed : May be fatal if swallowed and enters airways.  
Causes skin irritation.  
Causes serious eye irritation.  
May cause genetic defects.  
May cause cancer.  
Causes damage to organs through prolonged or repeated exposure.

Notes to physician : Treat symptomatically.

---

**SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media : Foam  
Water spray  
Dry powder  
Carbon dioxide (CO<sub>2</sub>)

Unsuitable extinguishing media : water jet

Specific hazards during fire fighting : See SDS section 10 - Stability and reactivity.

Hazardous combustion products : harmful vapours  
nitrogen oxides  
fumes/smoke  
carbon black  
carbon oxides

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.

Special protective equipment for fire-fighters : Wear a self-contained breathing apparatus.

---

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures : Do not breathe vapour/aerosol/spray mists.  
Wear eye/face protection.  
If exposed to high vapour concentration, leave area immediately.  
Use personal protective clothing.  
Handle in accordance with good building materials hygiene and safety practice.

Environmental precautions : Contain contaminated water/firefighting water.  
Do not discharge into drains/surface waters/groundwater.

---

# SAFETY DATA SHEET

## MasterFinish RL 220

Version 2.0      Revision Date: 08/15/2023      SDS Number: 000000260374      Date of last issue: 07/28/2023  
Date of first issue: 01/09/2023

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Keep away from open flames, hot surfaces and sources of ignition.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).

Advice on safe handling : Avoid aerosol formation.  
Avoid inhalation of mists/vapours.  
Avoid skin contact.  
Avoid contact with eyes.

Conditions for safe storage : No smoking.  
Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Avoid all sources of ignition: heat, sparks, open flame.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
naphthalene	91-20-3	TWA	10 ppm	ACGIH
		TWA	10 ppm 50 mg/m <sup>3</sup>	NIOSH REL
		ST	15 ppm 75 mg/m <sup>3</sup>	NIOSH REL
		TWA	10 ppm 50 mg/m <sup>3</sup>	OSHA Z-1
		TWA	10 ppm 50 mg/m <sup>3</sup>	OSHA P0
		STEL	15 ppm 75 mg/m <sup>3</sup>	OSHA P0
1,2,4-trimethylbenzene	95-63-6	TWA	25 ppm 125 mg/m <sup>3</sup>	NIOSH REL
		TWA	25 ppm 125 mg/m <sup>3</sup>	OSHA P0
		TWA	10 ppm	ACGIH

# SAFETY DATA SHEET

## MasterFinish RL 220

Version 2.0      Revision Date: 08/15/2023      SDS Number: 000000260374      Date of last issue: 07/28/2023  
 Date of first issue: 01/09/2023

2-butoxyethanol	111-76-2	TWA	20 ppm	ACGIH
		TWA	5 ppm 24 mg/m <sup>3</sup>	NIOSH REL
		TWA	50 ppm 240 mg/m <sup>3</sup>	OSHA Z-1
		TWA	25 ppm 120 mg/m <sup>3</sup>	OSHA P0
Stoddard solvent	8052-41-3	TWA	100 ppm	ACGIH
		TWA	350 mg/m <sup>3</sup>	NIOSH REL
		C	1,800 mg/m <sup>3</sup>	NIOSH REL
		TWA	500 ppm 2,900 mg/m <sup>3</sup>	OSHA Z-1
		TWA	100 ppm 525 mg/m <sup>3</sup>	OSHA P0
Trimethylbenzene	25551-13-7	TWA value	25 ppm	ACGIH TLV
		TWA value	25 ppm 125 mg/m <sup>3</sup>	29 CFR 1910.1000 (Table Z-1-A)
		REL value	25 ppm 125 mg/m <sup>3</sup>	NIOSH
		TWA	25 ppm	ACGIH
		TWA	25 ppm 125 mg/m <sup>3</sup>	OSHA P0
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	TWA (Inhalable particulate matter)	5 mg/m <sup>3</sup>	ACGIH
Distillates (petroleum), solvent-dewaxed light paraffinic	64742-56-9	TWA value (Inhalable fraction)	5 mg/m <sup>3</sup>	ACGIH TLV
		TWA (Inhalable particulate matter)	5 mg/m <sup>3</sup>	ACGIH

**Engineering measures** : Ensure adequate ventilation.

### Personal protective equipment

**Respiratory protection** : When workers are facing concentrations above the occupational exposure limits they must use appropriate certified respirators.  
 Use NIOSH approved respiratory protection.

### Hand protection

**Remarks** : Wear chemical resistant protective gloves. Manufacturer's directions for use should be observed because of great diversity of types.

**Eye protection** : Tightly fitting safety goggles (chemical goggles).

**Skin and body protection** : Body protection must be chosen based on level of activity and exposure.

**Protective measures** : Do not inhale gases/vapours/aerosols.  
 Avoid contact with the skin, eyes and clothing.

# SAFETY DATA SHEET



## MasterFinish RL 220

Version 2.0      Revision Date: 08/15/2023      SDS Number: 000000260374      Date of last issue: 07/28/2023  
Date of first issue: 01/09/2023

---

Avoid exposure - obtain special instructions before use.  
Handle in accordance with good building materials hygiene and safety practice.  
Wearing of closed work clothing is recommended.

Hygiene measures : When using, do not eat, drink or smoke.  
Hands and/or face should be washed before breaks and at the end of the shift.  
At the end of the shift the skin should be cleaned and skin-care agents applied.  
Remove contaminated clothing immediately and clean before re-use or dispose it if necessary.  
Gloves must be inspected regularly and prior to each use.  
Replace if necessary (e.g. pinhole leaks).

---

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : clear

Odor : aromatic

Odor Threshold : No data available

pH : No data available

Melting point : No applicable information available.

Boiling point : 322 °F / 161 °C

Flash point : 103 °F / 39 °C

Evaporation rate : not determined

Flammability (liquids) : Combustible liquid.

Upper explosion limit / Upper flammability limit : 6.0 %(V)

Lower explosion limit / Lower flammability limit : 1.0 %(V)

Vapor pressure : No data available

Relative vapor density : 4.5

Relative density : No applicable information available.

# SAFETY DATA SHEET



## MasterFinish RL 220

Version 2.0      Revision Date: 08/15/2023      SDS Number: 000000260374      Date of last issue: 07/28/2023  
Date of first issue: 01/09/2023

---

Density : approx. 1 g/cm<sup>3</sup>

Solubility(ies)  
Water solubility : slightly soluble

Solubility in other solvents : No applicable information available.

Partition coefficient: n-octanol/water : No applicable information available.

Autoignition temperature : 450 °F / 232 °C

Decomposition temperature : No decomposition if stored and handled as prescribed/indicated.

Viscosity  
Viscosity, dynamic : not determined

Viscosity, kinematic : not determined

Explosive properties : Not explosive

Oxidizing properties : Based on its structural properties the product is not classified as oxidizing.

Sublimation point : No applicable information available.

Molecular weight : Not applicable

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity : No hazardous reactions if stored and handled as prescribed/indicated.

Chemical stability : The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions : The product is stable if stored and handled as prescribed/indicated.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Strong acids  
Strong bases  
Strong oxidizing agents  
Strong reducing agents

Hazardous decomposition products : Traces of the substances/groups of substances are released as decomposition products of the dry substance.  
carbon oxides  
nitrogen oxides  
Hydrocarbons



## MasterFinish RL 220

Version	Revision Date:	SDS Number:	Date of last issue: 07/28/2023
2.0	08/15/2023	000000260374	Date of first issue: 01/09/2023

**SECTION 11. TOXICOLOGICAL INFORMATION****Acute toxicity**

Not classified based on available information.

**Skin corrosion/irritation**

Causes skin irritation.

**Serious eye damage/eye irritation**

Causes serious eye irritation.

**Respiratory or skin sensitization****Skin sensitization**

Not classified based on available information.

**Respiratory sensitization**

Not classified based on available information.

**Germ cell mutagenicity**

May cause genetic defects.

**Carcinogenicity**

May cause cancer.

<b>IARC</b>	Group 1: Carcinogenic to humans benzene	71-43-2
	Group 2B: Possibly carcinogenic to humans ethylbenzene	100-41-4
	Group 2B: Possibly carcinogenic to humans cumene	98-82-8
	Group 2B: Possibly carcinogenic to humans naphthalene	91-20-3
<b>OSHA</b>	OSHA specifically regulated carcinogen benzene	71-43-2
<b>NTP</b>	Reasonably anticipated to be a human carcinogen cumene	98-82-8
	Reasonably anticipated to be a human carcinogen naphthalene	91-20-3
	Known to be human carcinogen benzene	71-43-2

**Reproductive toxicity**

Not classified based on available information.

**STOT-single exposure**

Not classified based on available information.

**STOT-repeated exposure**

Causes damage to organs (Central nervous system) through prolonged or repeated exposure.

**Aspiration toxicity**

May be fatal if swallowed and enters airways.

# SAFETY DATA SHEET



## MasterFinish RL 220

Version 2.0      Revision Date: 08/15/2023      SDS Number: 000000260374      Date of last issue: 07/28/2023  
Date of first issue: 01/09/2023

---

### **Product:**

May also damage the lung at swallowing (aspiration hazard).

### **Further information**

### **Product:**

Remarks : Health injuries are not known or expected under normal use. The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

---

## SECTION 12. ECOLOGICAL INFORMATION

### **Ecotoxicity**

### **Product:**

#### **Ecotoxicology Assessment**

Acute aquatic toxicity : Harmful to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

#### **Persistence and degradability**

No data available

#### **Bioaccumulative potential**

No data available

#### **Mobility in soil**

No data available

#### **Other adverse effects**

### **Product:**

Additional ecological information : Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### **Disposal methods**

Waste from residues : Dispose of in accordance with national, state and local regulations. Do not contaminate ponds, waterways or ditches with chemical or used container. Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

---

# SAFETY DATA SHEET



## MasterFinish RL 220

Version 2.0      Revision Date: 08/15/2023      SDS Number: 000000260374      Date of last issue: 07/28/2023  
Date of first issue: 01/09/2023

### SECTION 14. TRANSPORT INFORMATION

#### International Regulations

##### UNRTDG

UN number : UN 1993  
Proper shipping name : FLAMMABLE LIQUID, N.O.S.  
Class : 3  
Packing group : III  
Labels : 3

##### IATA-DGR

UN/ID No. : UN 1993  
Proper shipping name : Flammable liquid, n.o.s.  
(STODDARD SOLVENT)  
Class : 3  
Packing group : III  
Labels : Flammable Liquids  
Packing instruction (cargo aircraft) : 366  
Packing instruction (passenger aircraft) : 355

##### IMDG-Code

UN number : UN 1993  
Proper shipping name : FLAMMABLE LIQUID, N.O.S.  
(STODDARD SOLVENT)  
Class : 3  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-E  
Marine pollutant : no

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### Domestic regulation

##### 49 CFR

UN/ID/NA number : UN 1993  
Proper shipping name : Flammable liquids, n.o.s.  
(STODDARD SOLVENT)  
Class : 3  
Packing group : III  
Labels : FLAMMABLE LIQUID  
ERG Code : 128  
Marine pollutant : no

### SECTION 15. REGULATORY INFORMATION

#### CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
xylene	1330-20-7	100	1674
benzene	71-43-2	10	2511

# SAFETY DATA SHEET



## MasterFinish RL 220

Version 2.0      Revision Date: 08/15/2023      SDS Number: 000000260374      Date of last issue: 07/28/2023  
Date of first issue: 01/09/2023

naphthalene	91-20-3	100	25113
ethylbenzene	100-41-4	1000	41855
toluene	108-88-3	1000	41855

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

1,2,4-trimethylbenzene      95-63-6

2-butoxyethanol      111-76-2

The following components are subject to reporting levels established by SARA Title III, Section 313:

naphthalene      91-20-3

ethylbenzene      100-41-4

### US State Regulations

#### Pennsylvania Right To Know

1,2,4-trimethylbenzene      95-63-6  
2-butoxyethanol      111-76-2  
Stoddard solvent      8052-41-3  
Trimethylbenzene      25551-13-7  
Distillates (petroleum), solvent-dewaxed heavy paraffinic      64742-65-0  
Distillates (petroleum), solvent-dewaxed light paraffinic      64742-56-9

#### New Jersey Right To Know

1,2,4-trimethylbenzene      95-63-6  
2-butoxyethanol      111-76-2  
Stoddard solvent      8052-41-3  
Trimethylbenzene      25551-13-7  
naphthalene      91-20-3  
ethylbenzene      100-41-4

#### California Prop. 65

WARNING: This product can expose you to chemicals including cumene, which is/are known to the State of California to cause cancer, and toluene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

#### The ingredients of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

DSL : All components of this product are on the Canadian DSL

## SECTION 16. OTHER INFORMATION

### Further information

# SAFETY DATA SHEET

## MasterFinish RL 220


Version  
2.0

Revision Date:  
08/15/2023

SDS Number:  
000000260374

Date of last issue: 07/28/2023  
Date of first issue: 01/09/2023

### NFPA 704:



### HMIS® IV:

HEALTH		
FLAMMABILITY		
PHYSICAL HAZARD		

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

### Full text of other abbreviations

29 CFR 1910.1000 (Table Z-1-A)	: OSHA - Table Z-1-A (29 CFR 1910.1000)
ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
ACGIHTLV	: American Conference of Governmental Industrial Hygienists - threshold limit values (US)
NIOSH	: NIOSH Pocket Guide to Chemical Hazards (US)
NIOSH REL	: USA. NIOSH Recommended Exposure Limits
OSHA P0	: USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
OSHA Z-1	: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
29 CFR 1910.1000 (Table Z-1-A) / TWA value	: Time Weighted Average (TWA):
ACGIH / TWA	: 8-hour, time-weighted average
ACGIHTLV / TWA value	: Time Weighted Average (TWA):
NIOSH / REL value	: Recommended exposure limit (REL):
NIOSH REL / TWA	: Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	: STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
NIOSH REL / C	: Ceiling value not be exceeded at any time.
OSHA P0 / TWA	: 8-hour time weighted average
OSHA P0 / STEL	: Short-term exposure limit
OSHA Z-1 / TWA	: 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Har-

# SAFETY DATA SHEET



## MasterFinish RL 220

Version	Revision Date:	SDS Number:	Date of last issue: 07/28/2023
2.0	08/15/2023	000000260374	Date of first issue: 01/09/2023

---

monized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 08/15/2023

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN