

RES 200E

reFINE EIFS Procedures

Procedure for Recoating EIFS

INTRODUCTION

The appearance of EIFS walls can be quickly refreshed by applying an appropriate coating. Master Builders Solutions Color Coat is specifically formulated for EIFS. This 100% acrylic coating minimizes changes to existing finishes. Alternately, Master Builders Solutions Tersus Color Coat can be used to impart a hydrophobic surface that repels dirt and helps buildings remain cleaner and more visually appealing.

If hairline cracks less than approximately 1/32" are present, two coats of Master Builders Solutions Senerlastic Coating can be used to provide a high-build crack bridging coating.

EQUIPMENT

- Appropriate personal protective equipment
- Rollers, roller screens, pans, pails
- Paint brushes
- Spray equipment

MATERIALS:

- Master Builders Solutions Color Coat, Senerlastic Coating or Tersus Color Coat
- Masking tape and materials for overspray protection

PROCEDURE

1. Thoroughly clean all surfaces that will be coated, and allow to dry.
2. Inspect sealant joints and repair as needed.
3. Protect areas that may be subject to overspray.
4. Apply Master Builders Solutions Color Coat, Senerlastic Coating or Tersus Color Coat according to Finestone instructions (see relevant Finestone Product Bulletins).

TECHNICAL SUPPORT

Consult Master Builders Solutions Technical Services Department at +1 (800) 589-1336 for specific recommendations concerning all other applications. Consult the Wall Systems website at finestone.master-builders-solutions.com/en, for additional information about products and systems and for updated literature.