

MasterFlow 648CP GROUT ACCELERATOR

Version 1.0 Revision Date: 09/15/2020 SDS Number: 000000259961 Date of last issue: -
Date of first issue: 09/15/2020

SECTION 1. IDENTIFICATION

Product name : MasterFlow 648CP GROUT ACCELERATOR
Product code : 000000000051358790 000000000051358790

Manufacturer or supplier's details

Company name of supplier : Master Builders-Admixtures US,LLC
Address : 23700 CHAGRIN BLVD
Beachwood OH 44122
Emergency telephone : ChemTel: +1-813-248-0585 USA: +1-800-255-3924 Contract
Number MIS9240420

Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals
Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with 29 CFR 1910.1200**

FLAMMABLE LIQUIDS : 4
Acute toxicity (Inhalation - vapour) : 3
Acute toxicity (Oral) : 4
Acute toxicity (Dermal) : 4
Skin corrosion/irritation : 2
Serious eye damage/eye irritation : Category 2A
Specific target organ toxicity - single exposure : 3
Short-term (acute) aquatic hazard : 3

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H227 Combustible liquid.
H319 Causes serious eye irritation.
H315 Causes skin irritation.
H312 Harmful in contact with skin.
H331 Toxic if inhaled.
H302 Harmful if swallowed.

MasterFlow 648CP GROUT ACCELERATOR

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/15/2020	000000259961	Date of first issue: 09/15/2020

H335 May cause respiratory irritation.

H402 Harmful to aquatic life.

Precautionary Statements :

Prevention:

P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P260 Do not breathe dust or mist.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P273 Avoid release to the environment.

P270 Do not eat, drink or smoke when using this product.

P264 Wash face, hands and any exposed skin thoroughly after handling.

Response:

P337 + P311 If eye irritation persists: Call a POISON CENTER or doctor/physician.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P303 + P352 IF ON SKIN (or hair): Wash with plenty of soap and water.

P361 Take off immediately all contaminated clothing.

P301 + P330 IF SWALLOWED: rinse mouth.

P332 + P313 If skin irritation occurs: Get medical advice/ attention.

P370 + P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.

Storage:

P233 Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/container to appropriate hazardous waste collection point.

Other hazards

No data available.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**Components**

Chemical name	CAS-No.	Concentration (% w/w)
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2	>= 25 - < 50
furfuryl alcohol	98-00-0	>= 25 - < 50
Bis[(dimethylamino)methyl]phenol	71074-89-0	>= 7 - < 10

MasterFlow 648CP GROUT ACCELERATOR

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/15/2020	000000259961	Date of first issue: 09/15/2020

SECTION 4. FIRST AID MEASURES

- General advice : First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Immediately remove contaminated clothing. Move out of dangerous area. Consult a physician. Show this material safety data sheet to the doctor in attendance. Symptoms of poisoning may appear several hours later. Do not leave the victim unattended.
- If inhaled : Keep patient calm, remove to fresh air, seek medical attention. Call a physician or poison control center immediately. If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : Immediately wash thoroughly with soap and water, seek medical attention. Take victim immediately to hospital. If on skin, rinse well with water. If on clothes, remove clothes.
- In case of eye contact : Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist. Immediately flush eye(s) with plenty of water. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
- If swallowed : Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention. Induce vomiting immediately and call a physician. Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : Harmful if swallowed or in contact with skin. Causes skin irritation. Causes serious eye irritation. Toxic if inhaled. May cause respiratory irritation.
- Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Foam
Dry powder
Carbon dioxide (CO₂)
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.

MasterFlow 648CP GROUT ACCELERATOR

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/15/2020	000000259961	Date of first issue: 09/15/2020

- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.
- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.
Evacuate personnel to safe areas.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
Keep in suitable, closed containers for disposal.
-

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Avoid all sources of ignition: heat, sparks, open flame.

Do not spray on a naked flame or any incandescent material.
Keep away from open flames, hot surfaces and sources of ignition.
- Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapors/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Provide sufficient air exchange and/or exhaust in work rooms.
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : Prevent unauthorized access.
no smoking
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
-

MasterFlow 648CP GROUT ACCELERATOR

Version 1.0 Revision Date: 09/15/2020 SDS Number: 000000259961 Date of last issue: -
Date of first issue: 09/15/2020

Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame. Protect from direct sunlight.

Materials to avoid : Observe VCI storage rules.

Further information on storage stability : No data available

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
furfuryl alcohol	98-00-0	REL value	10 ppm 40 mg/m ³	NIOSH
		STEL value	15 ppm 60 mg/m ³	NIOSH
		PEL	50 ppm 200 mg/m ³	29 CFR 1910.1000 (Table Z-1)
		TWA value	10 ppm 40 mg/m ³	29 CFR 1910.1000 (Table Z-1-A)
		STEL value	15 ppm 60 mg/m ³	29 CFR 1910.1000 (Table Z-1-A)
		TWA value	0.2 ppm	ACGIHTLV
		TWA	0.2 ppm	ACGIH
		TWA	10 ppm 40 mg/m ³	NIOSH REL
		ST	15 ppm 60 mg/m ³	NIOSH REL
		TWA	50 ppm 200 mg/m ³	OSHA Z-1
		TWA	10 ppm 40 mg/m ³	OSHA P0
		STEL	15 ppm 60 mg/m ³	OSHA P0

Personal protective equipment

Respiratory protection : Wear appropriate certified respirator when exposure limits may be exceeded.

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

MasterFlow 648CP GROUT ACCELERATOR

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/15/2020	000000259961	Date of first issue: 09/15/2020

Skin and body protection	:	Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Protective measures	:	Do not inhale gases/vapours/aerosols. Avoid contact with the skin, eyes and clothing. Avoid exposure - obtain special instructions before use. Handle in accordance with good building materials hygiene and safety practice. Wearing of closed work clothing is recommended.
Hygiene measures	:	Avoid contact with skin, eyes and clothing. When using do not eat or drink. When using do not smoke. Wash hands before breaks and immediately after handling the product.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	liquid
Color	:	amber
Odor	:	ammonia-like, slight odour
Odor Threshold	:	No data available
pH	:	neutral to slightly alkaline
Melting point	:	No applicable information available.
Boiling point	:	640 °F / 338 °C
Flash point	:	167 °F / 75 °C
Evaporation rate	:	No applicable information available.
Flammability (solid, gas)	:	not determined
Upper explosion limit / Upper flammability limit	:	16.3 %(V)
Lower explosion limit / Lower flammability limit	:	1.8 %(V)
Vapor pressure	:	No applicable information available.
Relative vapor density	:	Heavier than air.
Relative density	:	No applicable information available.
Density	:	1.03 g/cm ³ (68 °F / 20 °C)
Bulk density	:	not applicable
Solubility(ies)	:	

MasterFlow 648CP GROUT ACCELERATOR

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/15/2020	000000259961	Date of first issue: 09/15/2020

Water solubility	:	slightly soluble
Solubility in other solvents	:	No applicable information available.
Partition coefficient: n-octanol/water	:	No data available.
Autoignition temperature	:	No data available
Decomposition temperature	:	No decomposition if stored and handled as prescribed/indicated.
Viscosity		
Viscosity, dynamic	:	No data available.
Viscosity, kinematic	:	No applicable information available.
Explosive properties	:	Not explosive Not explosive
Oxidizing properties	:	Based on its structural properties the product is not classified as oxidizing.
Sublimation point	:	No applicable information available.
Molecular weight	:	No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	No decomposition if stored and applied as directed. Vapors may form explosive mixture with air.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Strong acids Strong bases Strong oxidizing agents Strong reducing agents
Hazardous decomposition products	:	carbon oxides nitrogen oxides Aldehydes

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity**

Harmful if swallowed or in contact with skin.
Toxic if inhaled.

Product:

Acute oral toxicity	:	Remarks: No applicable information available.
Acute inhalation toxicity	:	Remarks: No applicable information available.

MasterFlow 648CP GROUT ACCELERATOR

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/15/2020	000000259961	Date of first issue: 09/15/2020

Acute dermal toxicity : Remarks: No applicable information available.

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks : May cause skin irritation in susceptible persons.

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks : May cause irreversible eye damage.

Respiratory or skin sensitization**Skin sensitization**

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Product:

Remarks : Can sensitize the skin and/or respiratory tract of allergic persons.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Further information**Product:**

Remarks : No data available

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity**

No data available

MasterFlow 648CP GROUT ACCELERATOR

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/15/2020	000000259961	Date of first issue: 09/15/2020

Persistence and degradability

No data available

Bioaccumulative potential**Components:****2,4,6-tris(dimethylaminomethyl)phenol:**

Partition coefficient: n-octanol/water : Pow: 0.219 (70.7 °F / 21.5 °C)
 log Pow: -0.66 (70.7 °F / 21.5 °C)
 Method: other (measured)
 GLP: yes

Bis[(dimethylamino)methyl]phenol:

Partition coefficient: n-octanol/water : log Pow: 1.02 (77 °F / 25 °C)
 Method: other (calculated)

Mobility in soil

No data available

Other adverse effects**Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
 Harmful to aquatic life.

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Do not contaminate ponds, waterways or ditches with chemical or used container.
 Dispose of in accordance with national, state and local regulations.
 Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

SECTION 14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

UN number : UN 2735
 Proper shipping name : AMINES, LIQUID, CORROSIVE, N.O.S.
 (2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL)
 Class : 8
 Packing group : III
 Labels : 8

IATA-DGR

UN/ID No. : UN 2735

MasterFlow 648CP GROUT ACCELERATOR

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/15/2020	000000259961	Date of first issue: 09/15/2020

Proper shipping name : AMINES, LIQUID, CORROSIVE, N.O.S.
(2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL)

Class : 8

Packing group : III

Labels : Corrosive

Packing instruction (cargo aircraft) : 856

Packing instruction (passenger aircraft) : 852

IMDG-Code

UN number : UN 2735

Proper shipping name : AMINES, LIQUID, CORROSIVE, N.O.S.
(2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL)

Class : 8

Packing group : III

Labels : 8

EmS Code : F-A, S-B

Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation**49 CFR**

UN/ID/NA number : UN 2735

Proper shipping name : AMINES, LIQUID, CORROSIVE, N.O.S.
(2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL)

Class : 8

Packing group : III

Labels : CORROSIVE

ERG Code : 153

Marine pollutant : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION**US State Regulations****Pennsylvania Right To Know**

furfuryl alcohol 98-00-0
listed

New Jersey Right To Know

furfuryl alcohol 98-00-0
listed

California Prop. 65

MasterFlow 648CP GROUT ACCELERATOR

Version 1.0 Revision Date: 09/15/2020 SDS Number: 000000259961 Date of last issue: -
 Date of first issue: 09/15/2020

WARNING: This product can expose you to chemicals including furfuryl alcohol, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.


The ingredients of this product are reported in the following inventories:

TSCA : On the inventory, or in compliance with the inventory


SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

- 29 CFR 1910.1000 (Table Z-1-A) : OSHA - Table Z-1-A (29 CFR 1910.1000)
- 29 CFR 1910.1000 (Table Z-1) : OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR 1910.1000
- ACGIH : USA. ACGIH Threshold Limit Values (TLV)
- ACGIHTLV : American Conference of Governmental Industrial Hygienists - threshold limit values (US)
- NIOSH : NIOSH Pocket Guide to Chemical Hazards (US)
- NIOSH REL : USA. NIOSH Recommended Exposure Limits
- OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
- OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
- 29 CFR 1910.1000 (Table Z-1-A) / STEL value : Short Term Exposure Limit (STEL):
- 29 CFR 1910.1000 (Table Z-1-A) / TWA value : Time Weighted Average (TWA):
- 29 CFR 1910.1000 (Table Z-1) / PEL : Permissible exposure limit
- ACGIH / TWA : 8-hour, time-weighted average
- ACGIHTLV / TWA value : Time Weighted Average (TWA):

MasterFlow 648CP GROUT ACCELERATOR

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/15/2020	000000259961	Date of first issue: 09/15/2020

NIOSH / REL value	:	Recommended exposure limit (REL):
NIOSH / STEL value	:	Short Term Exposure Limit (STEL):
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA P0 / TWA	:	8-hour time weighted average
OSHA P0 / STEL	:	Short-term exposure limit
OSHA Z-1 / TWA	:	8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 09/15/2020

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

MasterFlow 648CP GROUT ACCELERATOR

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/15/2020	000000259961	Date of first issue: 09/15/2020

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

US / EN