

MasterPel[®] 100

Water-Repellent and Efflorescence Control Admixture With Dispersing Properties

Description

MasterPel 100 multi-purpose admixture is specially formulated and designed for water-repellent and efflorescence control in a variety of concrete masonry and hardscaping applications. This unique formula is based on a chemistry that is different from the conventional water-repellent admixtures in the manufactured concrete product industry.

Applications

Recommended for use in

- Concrete masonry units
- Segmental retaining wall units
- Concrete roof tiles
- Concrete bricks

Features

- Increased water repellency versus conventional water-repellent admixtures
- Enhances color and reduces efflorescence potential
- Improved cement dispersion and extrusion characteristics

Benefits

- Significantly reduces secondary efflorescence, improves primary efflorescence control
- Improves color vibrancy and pigment efficiency
- Increases production rate
- Adds visual appeal

Guidelines for Use

Dosage:

The recommended dosage of MasterPel 100 admixture is in the range of 3–8 fl oz/cwt (195–520 mL/100 kg) of cementitious materials depending on the desired benefits.

The dosage for optimum water repellency is determined through mix evaluation and testing procedures. Please consult with your local sales representative if dosages outside of the listed ranges are being considered.

Mixing: For maximum efficiency, add MasterPel 100 admixture early in the sequencing procedure. Best results typically occur by adding the MasterPel 100 admixture during the prewet process (with at least 70-80% of the required mix water), before adding the cementitious materials. Allow a minimum of 90 seconds of additional mixing time after all components have been dispensed.

Product Notes

Design and Construction Considerations: Design and construction details must observe all applicable design codes, incorporating the recommendations of NCMA.

MasterPel 100 admixture will not compensate for flaws in design, materials, mix proportions, improper production procedures or improper construction methods. Master Builders Solutions is not responsible for inappropriate use of MasterPel 100 admixture.

Storage and Handling

Storage Temperature: MasterPel 100 admixture must be stored at temperatures above 40 °F (4 °C) and below 105 °F (42 °C). MasterPel 100 admixture should not be used after it freezes.

Shelf Life: When properly stored, MasterPel 100 admixture has a shelf life of 12 months. Please contact your local sales representative regarding suitability for use and dosage recommendations if the shelf life of MasterPel 100 admixture has been exceeded.

Recirculation: Proper recirculation is required to maintain the integrity of the product. A low pressure pump is recommended for recirculation. **Do not use pressurized air to recirculate.** Please consult your local sales representative for additional information on recirculation.

Packaging

MasterPel 100 admixture is available in 5 gal (18.9 L) pails, 55 gal (208 L) drums and 275 gal (1041 L) totes.

Related Documents

Safety Data Sheets: MasterPel 100 admixture

Additional Information

For additional information on MasterPel 100 admixture or its use in developing concrete mixtures with special performance characteristics, contact your local sales representative.

Master Builders Solutions, a brand of MBCC Group, is a global leader of innovative chemistry systems and formulations for construction, maintenance, repair and restoration of structures. The Admixture Systems business provides advanced products, solutions and expertise that improve durability, water resistance, energy efficiency, safety, sustainability and aesthetics of concrete structures, above and below ground, helping customers to achieve reduced operating costs, improved efficiency and enhanced finished products.

Utilizing worldwide resources, the Master Builders Solutions community of experts are passionate about providing solutions to challenges within all stages of construction, as well as the life cycle of a structure. At Master Builders Solutions we create sustainable solutions for construction around the globe.

Limited Warranty Notice

Master Builders Solutions Admixtures US, LLC ("Master Builders Solutions") warrants this product to be free from manufacturing defects and to meet the technical properties on the current Technical Data Guide, if used as directed within shelf life. Satisfactory results depend not only on quality products but also upon many factors beyond our control. MASTER BUILDERS SOLUTIONS MAKES NO OTHER WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO ITS PRODUCTS. The sole and exclusive remedy of Purchaser for any claim concerning this product, including but not limited to, claims alleging breach of warranty, negligence, strict liability or otherwise, is shipment to purchaser of product equal to the amount of product that fails to meet this warranty or refund of the original purchase price of product that fails to meet this warranty, at the sole option of Master Builders Solutions. Any claims concerning this product must be received in writing within one (1) year from the date of shipment and any claims not presented within that period are waived by Purchaser. MASTER BUILDERS SOLUTIONS WILL NOT BE RESPONSIBLE FOR ANY SPECIAL, INCIDENTAL, CONSEQUENTIAL (INCLUDING LOST PROFITS) OR PUNITIVE DAMAGES OF ANY KIND.

Purchaser must determine the suitability of the products for the intended use and assumes all risks and liabilities in connection therewith. This information and all further technical advice are based on Master Builders Solutions' present knowledge and experience. However, Master Builders Solutions assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights, nor shall any legal relationship be created by or arise from the provision of such information and advice. Master Builders Solutions reserves the right to make any changes according to technological progress or further developments. The Purchaser of the Product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with a full application of the product(s). Performance of the product described herein should be verified by testing and carried out by qualified experts.