

**MasterSeal 350 light gray PART A**

Version 2.0      Revision Date: 06/03/2021      SDS Number: 000000911504      Date of last issue: 10/13/2020  
Date of first issue: 10/13/2020

---

**SECTION 1. IDENTIFICATION**

Product name : MasterSeal 350 light gray PART A  
Product code : 000000000050607237 000000000050607237  
Other means of identification : MSeal 350 Light Grey PTA

**Manufacturer or supplier's details**

Company name of supplier : Colorbiotics, LLC  
Address : 23700 CHAGRIN BLVD  
Beachwood OH 44122  
Emergency telephone : ChemTel: +1-813-248-0585

**Recommended use of the chemical and restrictions on use**



Recommended use : Product for construction chemicals  
Restrictions on use : Reserved for industrial and professional use.  
National Emergency Telephone Number : USA: +1-800-255-3924 ChemTel contract no. MIS9240420

---

**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)**

Skin irritation : Category 2  
Eye irritation : Category 2A  
Skin sensitization : Category 1  
Specific target organ toxicity - single exposure : Category 3 (Respiratory system)  
Short-term (acute) aquatic hazard : Category 2  
Long-term (chronic) aquatic hazard : Category 2

**GHS label elements**

Hazard pictograms :  

Signal Word : Warning

## MasterSeal 350 light gray PART A

Version	Revision Date:	SDS Number:	Date of last issue: 10/13/2020
2.0	06/03/2021	000000911504	Date of first issue: 10/13/2020

Hazard Statements : H315 Causes skin irritation.  
 H317 May cause an allergic skin reaction.  
 H319 Causes serious eye irritation.  
 H335 May cause respiratory irritation.  
 H401 Toxic to aquatic life.  
 H411 Toxic to aquatic life with long lasting effects.

Precautionary Statements : **Prevention:**  
 P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.  
 P264 Wash skin thoroughly after handling.  
 P271 Use only outdoors or in a well-ventilated area.  
 P272 Contaminated work clothing must not be allowed out of the workplace.  
 P273 Avoid release to the environment.  
 P280 Wear protective gloves/ eye protection/ face protection.

**Response:**  
 P302 + P352 IF ON SKIN: Wash with plenty of soap and water.  
 P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.  
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  
 P337 + P313 If eye irritation persists: Get medical advice/ attention.  
 P362 Take off contaminated clothing and wash before reuse.  
 P391 Collect spillage.

**Storage:**  
 P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
 P405 Store locked up.

**Disposal:**  
 P501 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical nature : Epoxy constituents

**Components**

Chemical name	CAS-No.	Concentration (% w/w)
Reaction product: bisphenol-A-(epichlorhydrin)-Epoxy resin (number average molecular weight <= 700)	25068-38-6	>= 50 - < 70
RP: bisphenol-A-(epichlorhydrin)	25068-38-6	>= 20 - < 30

## MasterSeal 350 light gray PART A

Version 2.0      Revision Date: 06/03/2021      SDS Number: 000000911504      Date of last issue: 10/13/2020  
 Date of first issue: 10/13/2020

epoxy resin MW <=700		
Alkyl (C12-C14) glycidyl ether	68609-97-2	>= 10 - < 20
Titanium dioxide	13463-67-7	>= 1 - < 5
2,3-epoxypropyl o-tolyl ether	2210-79-9	>= 0.1 - < 1

Actual concentration is withheld as a trade secret

### SECTION 4. FIRST AID MEASURES

- General advice : First aid personnel should pay attention to their own safety. Immediately remove contaminated clothing.
- If inhaled : If difficulties occur after vapour/aerosol has been inhaled, remove to fresh air and seek medical attention.
- In case of skin contact : After contact with skin, wash immediately with plenty of water and soap. Under no circumstances should organic solvent be used. If irritation develops, seek medical attention.
- In case of eye contact : Hold eyes open and rinse slowly and gently with water for 15 to 20 minutes. Remove contact lenses, if present, after first 5 minutes, then continue rinsing. If eye irritation persists, consult a specialist.
- If swallowed : Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention. Do NOT induce vomiting.
- Most important symptoms and effects, both acute and delayed : Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause respiratory irritation.
- Notes to physician : Treat symptomatically.

### SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Foam  
Water spray  
Dry powder  
Carbon dioxide (CO<sub>2</sub>)
- Unsuitable extinguishing media : water jet
- Specific hazards during fire fighting : See SDS section 10 - Stability and reactivity.
- Hazardous combustion products : harmful vapours  
nitrogen oxides  
fumes/smoke  
carbon black  
carbon oxides

**MasterSeal 350 light gray PART A**

Version	Revision Date:	SDS Number:	Date of last issue: 10/13/2020
2.0	06/03/2021	000000911504	Date of first issue: 10/13/2020

---

- Further information : The degree of risk is governed by the burning substance and the fire conditions.  
If exposed to fire, keep containers cool by spraying with water. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems. Contaminated extinguishing water must be disposed of in accordance with official regulations.
- Special protective equipment for fire-fighters : Wear a self-contained breathing apparatus.
- 

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Do not breathe vapour/aerosol/spray mists.  
Wear eye/face protection.  
If exposed to high vapour concentration, leave area immediately.  
Use personal protective clothing.  
Handle in accordance with good building materials hygiene and safety practice.
- Environmental precautions : Contain contaminated water/firefighting water.  
Do not discharge into drains/surface waters/groundwater.
- Methods and materials for containment and cleaning up : Large spills should be collected mechanically (remove by pumping) for disposal.  
Pick up with inert absorbent material (e.g. sand, earth etc.).  
Spilled product should be disposed in accordance with all applicable government regulations.
- 

**SECTION 7. HANDLING AND STORAGE**

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : Avoid aerosol formation.  
Avoid inhalation of mists/vapours.  
Avoid skin contact.  
Avoid contact with eyes.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage conditions : Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame.  
Protect from direct sunlight.
-

## MasterSeal 350 light gray PART A

Version 2.0      Revision Date: 06/03/2021      SDS Number: 000000911504      Date of last issue: 10/13/2020  
 Date of first issue: 10/13/2020

Recommended storage temperature : 60 - 80 °F / 16 - 27 °C

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Titanium dioxide	13463-67-7	TWA (total dust)	15 mg/m <sup>3</sup>	OSHA Z-1
		TWA (Total dust)	10 mg/m <sup>3</sup>	OSHA P0
		TWA	10 mg/m <sup>3</sup> (Titanium dioxide)	ACGIH

**Engineering measures** : Ensure adequate ventilation.

#### Personal protective equipment

**Respiratory protection** : When workers are facing concentrations above the occupational exposure limits they must use appropriate certified respirators.  
 Use NIOSH approved respiratory protection.

**Hand protection**

**Remarks** : Wear chemical resistant protective gloves. Manufacturer's directions for use should be observed because of great diversity of types.

**Eye protection** : Wear safety glasses with side shields or goggles.

**Skin and body protection** : Body protection must be chosen depending on activity and possible exposure, e.g. head protection, apron, protective boots, chemical-protection suit.

**Protective measures** : Do not inhale gases/vapours/aerosols.  
 Avoid contact with the skin, eyes and clothing.  
 Avoid exposure - obtain special instructions before use.  
 Handle in accordance with good building materials hygiene and safety practice.  
 Wearing of closed work clothing is recommended.

**Hygiene measures** : When using, do not eat, drink or smoke.  
 Hands and/or face should be washed before breaks and at the end of the shift.  
 At the end of the shift the skin should be cleaned and skin-care agents applied.  
 Remove contaminated clothing immediately and clean before re-use or dispose it if necessary.  
 Gloves must be inspected regularly and prior to each use.  
 Replace if necessary (e.g. pinhole leaks).

**MasterSeal 350 light gray PART A**

Version 2.0      Revision Date: 06/03/2021      SDS Number: 000000911504      Date of last issue: 10/13/2020  
Date of first issue: 10/13/2020

---

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

Color : light gray

Odor : odorless

Odor Threshold : Not relevant

pH : No data available

Melting point : No data available

Boiling point : 199 °F / 93 °C

Flash point : 200.01 °F / 93.34 °C  
Method: closed cup

Evaporation rate : No data available

Flammability (liquids) : Not classified as a flammability hazard

Self-ignition : not self-igniting

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapor pressure : No data available

Relative vapor density : No data available

Relative density : No data available

Density : 1.1324 g/cm<sup>3</sup> (68 °F / 20 °C)  
9.34 lb/USg

Solubility(ies)  
Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Autoignition temperature : No data available

**MasterSeal 350 light gray PART A**

Version 2.0	Revision Date: 06/03/2021	SDS Number: 000000911504	Date of last issue: 10/13/2020 Date of first issue: 10/13/2020
----------------	------------------------------	-----------------------------	---

---

Decomposition temperature : No decomposition if stored and handled as prescribed/indicated.

Viscosity  
Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : Not an oxidizer.

Sublimation point : No data available

Molecular weight : No data available

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No hazardous reactions if stored and handled as prescribed/indicated.

Chemical stability : The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions : The product is stable if stored and handled as prescribed/indicated.

Conditions to avoid : See SDS section 7 - Handling and storage.

Incompatible materials : Strong acids  
Strong bases  
Strong oxidizing agents  
Strong reducing agents

Hazardous decomposition products : No hazardous decomposition products if stored and handled as prescribed/indicated.

---

**SECTION 11. TOXICOLOGICAL INFORMATION**

**Acute toxicity**  
Not classified based on available information.

**Skin corrosion/irritation**  
Causes skin irritation.

**Serious eye damage/eye irritation**  
Causes serious eye irritation.

**Respiratory or skin sensitization**

**Skin sensitization**  
May cause an allergic skin reaction.

**MasterSeal 350 light gray PART A**

Version	Revision Date:	SDS Number:	Date of last issue: 10/13/2020
2.0	06/03/2021	000000911504	Date of first issue: 10/13/2020

---

**Respiratory sensitization**

Not classified based on available information.

**Germ cell mutagenicity**

Not classified based on available information.

**Carcinogenicity**

Not classified based on available information.

<b>IARC</b>	Group 2B: Possibly carcinogenic to humans	
	Titanium dioxide	13463-67-7

**Reproductive toxicity**

Not classified based on available information.

**STOT-single exposure**

May cause respiratory irritation.

**STOT-repeated exposure**

Not classified based on available information.

**Aspiration toxicity**

Not classified based on available information.

**Further information**

**Product:**

Remarks	:	Health injuries are not known or expected under normal use. The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.
---------	---	---

---

**SECTION 12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

**Product:**

**Ecotoxicology Assessment**

Acute aquatic toxicity	:	Toxic to aquatic life.
------------------------	---	------------------------

Chronic aquatic toxicity	:	Toxic to aquatic life with long lasting effects.
--------------------------	---	--

**Persistence and degradability**

No data available

**Bioaccumulative potential**

No data available

**Mobility in soil**

No data available

**Other adverse effects**

**Product:**

Additional ecological infor-	:	Do not discharge product into the environment without control.
------------------------------	---	--



## MasterSeal 350 light gray PART A

Version	Revision Date:	SDS Number:	Date of last issue: 10/13/2020
2.0	06/03/2021	000000911504	Date of first issue: 10/13/2020

---

mation	The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.
--------	--

---

### SECTION 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

Waste from residues	: Dispose of in accordance with national, state and local regulations. Do not contaminate ponds, waterways or ditches with chemical or used container. Do not discharge into drains/surface waters/groundwater.
Contaminated packaging	: Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

---

### SECTION 14. TRANSPORT INFORMATION

#### International Regulations

##### UNRTDG

UN number	: UN 3082
Proper shipping name	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BISPHENOL-A-EPICHLORHYDRIN RESINS M <=700)
Class	: 9
Subsidiary risk	: EHSM
Packing group	: III
Labels	: 9 (EHSM)

##### IATA-DGR

UN/ID No.	: UN 3082
Proper shipping name	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BISPHENOL-A-EPICHLORHYDRIN RESINS M <=700)
Class	: 9
Subsidiary risk	: EHSM
Packing group	: III
Labels	: Miscellaneous, Environmentally hazardous
Packing instruction (cargo aircraft)	: 964
Packing instruction (passenger aircraft)	: 964

##### IMDG-Code

UN number	: UN 3082
Proper shipping name	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BISPHENOL-A-EPICHLORHYDRIN RESINS M <=700)
Class	: 9
Subsidiary risk	: EHSM
Packing group	: III

## MasterSeal 350 light gray PART A

Version	Revision Date:	SDS Number:	Date of last issue: 10/13/2020
2.0	06/03/2021	000000911504	Date of first issue: 10/13/2020

---

Labels : 9 (EHSM)  
 EmS Code : F-A, S-F  
 Marine pollutant : yes

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### Domestic regulation

#### 49 CFR

UN/ID/NA number : UN 3082  
 Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BISPHENOL-A-EPICHLORHYDRIN RESINS M <=700)  
 Class : 9  
 Subsidiary risk : EHSM  
 Packing group : III  
 Labels : CLASS 9, Environmentally hazardous  
 ERG Code : 171  
 Marine pollutant : no

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

---

## SECTION 15. REGULATORY INFORMATION

### US State Regulations

#### Pennsylvania Right To Know

Titanium dioxide	13463-67-7
Copper chlorophthalocyanine	12239-87-1

#### New Jersey Right To Know

Titanium dioxide	13463-67-7
------------------	------------

#### California Prop. 65

WARNING: This product can expose you to chemicals including Titanium dioxide, which is/are known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

### The ingredients of this product are reported in the following inventories:

TSCA : All chemical substances in this product are either listed as active on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

DSL : All components of this product are on the Canadian DSL


---

## SECTION 16. OTHER INFORMATION

### Further information

## MasterSeal 350 light gray PART A

Version 2.0      Revision Date: 06/03/2021      SDS Number: 000000911504      Date of last issue: 10/13/2020  
 Date of first issue: 10/13/2020

**NFPA 704:****HMIS® IV:**

<b>HEALTH</b>		
<b>FLAMMABILITY</b>		
<b>PHYSICAL HAZARD</b>		

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

**Full text of other abbreviations**

ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
 OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000  
 OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants  
 ACGIH / TWA : 8-hour, time-weighted average  
 OSHA P0 / TWA : 8-hour time weighted average  
 OSHA Z-1 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances

**MasterSeal 350 light gray PART A**

Version	Revision Date:	SDS Number:	Date of last issue: 10/13/2020
2.0	06/03/2021	000000911504	Date of first issue: 10/13/2020

---

es; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 06/03/2021

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN