



We create chemistry

Date: January 1, 2014

**MasterSeal® TC 225 (Formerly Sonoguard Top Coat)  
Product Information Statement for LEED® 2009 Credit Documentation**

MasterSeal® TC 225 is a polyurethane waterproofing sealer used in conjunction with MasterSeal® basecoats for interior or exterior use

BASF Corporation certifies the following information for MasterSeal® TC 225:

**Recycled Content**

MasterSeal® TC 225 recycled content is not available at this time and should be assumed to be 0% for the purposes of LEED reporting.

**Regional Materials**

MasterSeal® TC 225 is manufactured in **Brighton, CO 80216**. Extraction and processing location is not available at this time.

**Solar Reflective Index**

MasterSeal® TC 225 Gray has a Solar Reflective Index (SRI) **greater than 29**.  
MasterSeal® TC 225 White has a Solar Reflective Index (SRI) **greater than 78**.

**VOC Content**

MasterSeal® TC 225 has a VOC (Volatile Organic Compound) content of 209 g/L.

Based upon the above information, BASF Corporation certifies that MasterSeal® TC 225 could contribute to the following LEED NC Credits:

**SS Credit 7.1:** Heat Island Effect: Non-Roof

**SS Credit 7.2:** Heat Island Effect: Roof

**EQ Credit 4.2:** Low-Emitting Materials: Paints & Coatings

Respectfully,  
LEED Administrator  
BASF Corporation  
Tel: 800-243-6739



"LEED" is a trademark of the U.S. Green Building Council

BASF Corporation  
Construction Systems  
889 Valley Park Drive  
Shakopee, MN 55379

