



The Chemical Company

Date: August 30, 2016

MasterSeal® TC 235
Product Information Statement for LEED® 2009 Credit Documentation

MasterSeal® TC 235 is a low VOC polyurethane waterproofing sealer used in conjunction with MasterSeal® basecoats for interior or exterior use

BASF Corporation certifies the following information for MasterSeal® TC 235:

Recycled Content

MasterSeal® TC 235 recycled content is not available at this time and should be assumed to be 0% for the purposes of LEED reporting.

Regional Materials

MasterSeal® TC 235 is manufactured in **Brighton, CO 80216**. Extraction and processing location is not available at this time.

Solar Reflective Index

MasterSeal® TC 235 Gray has a Solar Reflective Index (SRI) **greater than 29**.
MasterSeal® TC 235 White has a Solar Reflective Index (SRI) **greater than 78**.

VOC Content

MasterSeal® TC 235 has a VOC (Volatile Organic Compound) content of 95 g/L.

Based upon the above information, BASF Corporation certifies that MasterSeal® TC 235 could contribute to the following LEED NC Credits:

SS Credit 7.1: Heat Island Effect: Non-Roof

SS Credit 7.2: Heat Island Effect: Roof

EQ Credit 4.2: Low-Emitting Materials: Paints & Coatings

Respectfully,
LEED Administrator
BASF Corporation
Tel: 800-243-6739



"LEED" is a trademark of the U.S. Green Building Council

BASF Corporation
Construction Systems
889 Valley Park Drive
Shakopee, MN 55379

MASTER®
» BUILDERS
SOLUTIONS