

## MasterSeal TC 275 PART B

Version            Revision Date:            SDS Number:            Date of last issue: 04/27/2020  
 1.1                07/27/2020                000000534220            Date of first issue: 04/27/2020

---

**SECTION 1. IDENTIFICATION**

Product name                : MasterSeal TC 275 PART B  
 Product code                : 000000000055352976 000000000055352976

**Manufacturer or supplier's details**

Company name of supplier   : Master Builders-Admixtures US,LLC  
 Address                        : 23700 CHAGRIN BLVD  
                                       Beachwood OH 44122  
 Emergency telephone        : ChemTel: +1-813-248-0585 USA: +1-800-255-3924 Contract  
                                       Number MIS9240420

**Recommended use of the chemical and restrictions on use**


Restrictions on use            : Reserved for industrial and professional use.

---

**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with 29 CFR 1910.1200**

Acute toxicity (Inhalation)    : Category 4  
 Skin corrosion/irritation     : Category 2  
 Serious eye damage/eye  
 irritation                        : Category 2A  
 Respiratory sensitization     : Category 1  
 Skin sensitization             : Category 1  
 Specific target organ toxicity : Category 3 (Respiratory system)  
 - single exposure  
 Specific target organ toxicity : Category 2 (Olfactory organs)  
 - repeated exposure

**GHS label elements**

Hazard pictograms            : 

Signal Word                    : Danger

Hazard Statements            : H319 Causes serious eye irritation.  
 H315 Causes skin irritation.  
 H332 Harmful if inhaled.  
 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
 H317 May cause an allergic skin reaction.  
 H335 May cause respiratory irritation.  
 H373 May cause damage to organs (Olfactory organs) through prolonged or repeated exposure.

## MasterSeal TC 275 PART B

Version 1.1      Revision Date: 07/27/2020      SDS Number: 000000534220      Date of last issue: 04/27/2020  
 Date of first issue: 04/27/2020

## Precautionary Statements

: **Prevention:**

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P271 Use only outdoors or in a well-ventilated area.

P260 Do not breathe dust or mist.

P261 Avoid breathing mist.

P284 In case of inadequate ventilation wear respiratory protection.

P272 Contaminated work clothing should not be allowed out of the workplace.

P264 Wash face, hands and any exposed skin thoroughly after handling.

**Response:**

P312 Call a POISON CENTER/ doctor/ .?/ if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P314 Get medical advice/ attention if you feel unwell.

P303 + P352 IF ON SKIN (or hair): Wash with plenty of soap and water.

P333 + P311 If skin irritation or rash occurs: Call a POISON CENTER or doctor/physician.

P332 + P313 If skin irritation occurs: Get medical advice/ attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P337 + P311 If eye irritation persists: Call a POISON CENTER or doctor/physician.

**Storage:**

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

**Disposal:**

P501 Dispose of contents/container to appropriate hazardous waste collection point.

**Other hazards**

No applicable information available.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical nature : Sealant

**Components**

Chemical name	CAS-No.	Concentration (% w/w)
Diphenylmethane-4,4'-diisocyanate (MDI)	101-68-8	>= 50 - < 75
Isocyanic acid, polymethylenepolyphenylene ester (P-MDI)	9016-87-9	>= 25 - < 50

## MasterSeal TC 275 PART B

Version 1.1      Revision Date: 07/27/2020      SDS Number: 000000534220      Date of last issue: 04/27/2020  
 Date of first issue: 04/27/2020

methylenediphenyl diisocyanate	26447-40-5	$\geq 7 - < 15$
Isocyanic acid, polymethylenepolyphenylene ester, polymer with.alpha.-hydro-.omega.-hydroxypoly(oxy-1,2-ethanediyl)	57636-09-6	$\geq 1 - < 3$
2,4-Dioxo-1,3-diazetidone-1,3-diylbis[p-phenylenemethylene-p-phenylene] diisocyanate	17589-24-1	$\geq 0.3 - < 1$

## SECTION 4. FIRST AID MEASURES

- General advice : Remove contaminated clothing.
- If inhaled : Remove the affected individual into fresh air and keep the person calm.  
 Assist in breathing if necessary.  
 Immediate medical attention required.
- In case of skin contact : Wash affected areas thoroughly with soap and water.  
 If irritation develops, seek medical attention.
- In case of eye contact : In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water.  
 Immediate medical attention required.
- If swallowed : Rinse mouth and then drink 200-300 ml of water.  
 Do NOT induce vomiting.  
 Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions.  
 Immediate medical attention required.
- Most important symptoms and effects, both acute and delayed : Causes skin irritation.  
 May cause an allergic skin reaction.  
 Causes serious eye irritation.  
 Harmful if inhaled.  
 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
 May cause respiratory irritation.
- Notes to physician : Treat symptomatically.

## SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Foam  
 Water spray  
 Dry powder  
 Carbon dioxide (CO<sub>2</sub>)
- Unsuitable extinguishing media : water jet
- Hazardous combustion products : nitrous gases  
 fumes/smoke  
 isocyanate  
 vapor
- Further information : Standard procedure for chemical fires.  
 Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Special protective equipment for fire-fighters : Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

## MasterSeal TC 275 PART B

Version            Revision Date:            SDS Number:            Date of last issue: 04/27/2020  
 1.1                07/27/2020                000000534220            Date of first issue: 04/27/2020

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures : Clear area.  
 Ensure adequate ventilation.  
 Wear suitable personal protective clothing and equipment.

Environmental precautions : Do not discharge into drains/surface waters/groundwater.

Methods and materials for containment and cleaning up : Dike spillage.

**SECTION 7. HANDLING AND STORAGE**

Advice on protection against fire and explosion : No explosion proofing necessary.

Advice on safe handling : Mix thoroughly before use.  
 If bulging of drum occurs, transfer to well ventilated area, puncture to relieve pressure, open vent and let stand for 48 hours before resealing.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.  
 Observe label precautions.  
 Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Formation of CO<sub>2</sub> and build up of pressure possible.  
 Keep container tightly closed and in a well-ventilated place.  
 Outage of containers should be filled with dry inert gas at atmospheric pressure to avoid reaction with moisture.

Materials to avoid : Segregate from bases.

Recommended storage temperature : 61 - 81 °F / 16 - 27 °C

Further information on storage stability : No decomposition if stored and applied as directed.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION****Ingredients with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Diphenylmethane-4,4'-diisocyanate (MDI)	101-68-8	TWA value	0.005 ppm	ACGIHTLV
		REL value	0.005 ppm 0.05 mg/m <sup>3</sup>	NIOSH
		Ceil_Time	0.020 ppm 0.2 mg/m <sup>3</sup>	NIOSH
		CLV	0.02 ppm 0.2 mg/m <sup>3</sup>	29 CFR 1910.1000 (Table Z-1)
		CLV	0.02 ppm	29 CFR

## MasterSeal TC 275 PART B

Version 1.1      Revision Date: 07/27/2020      SDS Number: 000000534220      Date of last issue: 04/27/2020  
 Date of first issue: 04/27/2020

			0.2 mg/m <sup>3</sup>	1910.1000 (Table Z-1-A)
		TWA	0.005 ppm	ACGIH
		C	0.02 ppm 0.2 mg/m <sup>3</sup>	OSHA Z-1
		C	0.02 ppm 0.2 mg/m <sup>3</sup>	OSHA P0
		TWA	0.005 ppm 0.05 mg/m <sup>3</sup>	NIOSH REL
		C	0.02 ppm 0.2 mg/m <sup>3</sup>	NIOSH REL
Isocyanic acid, polymethylenepolyphenylene ester (P-MDI)	9016-87-9	C	0.02 ppm 0.2 mg/m <sup>3</sup>	OSHA Z-1
		C	0.02 ppm 0.2 mg/m <sup>3</sup>	OSHA P0
		TWA	0.005 ppm 0.05 mg/m <sup>3</sup>	NIOSH REL
		C	0.02 ppm 0.2 mg/m <sup>3</sup>	NIOSH REL

## Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
carbon monoxide	630-08-0	TWA value	25 ppm	ACGIHTLV
		REL value	35 ppm 40 mg/m <sup>3</sup>	NIOSH
		Ceil_Time	200 ppm 229 mg/m <sup>3</sup>	NIOSH
		PEL	50 ppm 55 mg/m <sup>3</sup>	29 CFR 1910.1000 (Table Z-1)
		TWA value	35 ppm 40 mg/m <sup>3</sup>	29 CFR 1910.1000 (Table Z-1-A)
		CLV	200 ppm 229 mg/m <sup>3</sup>	29 CFR 1910.1000 (Table Z-1-A)
		TWA	25 ppm	ACGIH
		TWA	35 ppm 40 mg/m <sup>3</sup>	NIOSH REL
		C	200 ppm 229 mg/m <sup>3</sup>	NIOSH REL
		TWA	50 ppm 55 mg/m <sup>3</sup>	OSHA Z-1
hydrogen cyanide	74-90-8	TWA	35 ppm 40 mg/m <sup>3</sup>	OSHA P0
		C	200 ppm 229 mg/m <sup>3</sup>	OSHA P0
		CLV	4.7 ppm (CN)	ACGIHTLV
		C	4.7 ppm (Cyanide)	ACGIH

## MasterSeal TC 275 PART B

Version 1.1      Revision Date: 07/27/2020      SDS Number: 000000534220      Date of last issue: 04/27/2020  
 Date of first issue: 04/27/2020

		ST	4.7 ppm 5 mg/m <sup>3</sup>	NIOSH REL
		TWA	10 ppm 11 mg/m <sup>3</sup>	OSHA Z-1
		STEL	4.7 ppm 5 mg/m <sup>3</sup>	OSHA P0

**Engineering measures** : Provide local exhaust ventilation to maintain recommended P.E.L.

**Personal protective equipment**

**Respiratory protection** : When workers are facing concentrations above the occupational exposure limits they must use appropriate certified respirators.  
 When atmospheric levels may exceed the occupational exposure limit (PEL or TLV) NIOSH-certified air-purifying respirators equipped with an organic vapor sorbent and particulate filter can be used as long as appropriate precautions and change out schedules are in place.  
 Wear a NIOSH-certified (or equivalent) TC19C positive pressure air supplied respirator.  
 For emergency or non-routine, high exposure situations, including confined space entry, use a NIOSH-certified full facepiece pressure demand self-contained breathing apparatus (SCBA) or a full facepiece pressure demand supplied-air respirator (SAR) with escape provisions.

**Hand protection**

**Remarks** : Chemical resistant protective gloves Suitable materials chloroprene rubber (Neoprene) chlorinated polyethylene polyvinylchloride (Pylox) butyl rubber fluoroelastomer (Viton) nitrile rubber (Buna N)

**Eye protection** : Tightly fitting safety goggles (chemical goggles).  
 Wear face shield if splashing hazard exists.

**Skin and body protection** : Suitable materials  
 saran-coated material

**Protective measures** : Wear protective clothing as necessary to prevent contact.  
 Eye wash fountains and safety showers must be easily accessible.  
 Observe the appropriate PEL value.

**Hygiene measures** : Wash soiled clothing immediately.  
 Remove contaminated clothing immediately and clean before re-use or dispose it if necessary.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

**Appearance** : liquid  
**Color** : black  
**Odor** : faintly aromatic  
**pH** : not applicable  
**Freezing point** : approx. 35.60 °F / 2.00 °C

## MasterSeal TC 275 PART B

Version	Revision Date:	SDS Number:	Date of last issue: 04/27/2020
1.1	07/27/2020	000000534220	Date of first issue: 04/27/2020

---

Boiling point	:	392 °F / 200 °C (6.666 hPa)
Flash point	:	> 392 °F / > 200 °C  Method: open cup
Evaporation rate	:	No applicable information available.
Flammability (solid, gas)	:	not determined
Self-ignition	:	Based on its structural properties the product is not classified as self-igniting.
Vapor pressure	:	0.0001000 mmHg (77.00 °F / 25.00 °C)
Relative vapor density	:	No applicable information available.
Relative density	:	No applicable information available.
Density	:	10.1000 lb/USg (77.00 °F / 25.00 °C)
Solubility(ies)	:	
Water solubility	:	hydrolyzes
Solubility in other solvents	:	No applicable information available.
Partition coefficient: n-octanol/water	:	No applicable information available.
Autoignition temperature	:	> 878 °F / > 470 °C
Viscosity	:	
Viscosity, dynamic	:	No applicable information available.
Viscosity, kinematic	:	No applicable information available.
Explosive properties	:	Not explosive
Oxidizing properties	:	Not an oxidizer.
Sublimation point	:	No applicable information available.
Molecular weight	:	No data available.
Metal corrosion rate	:	No corrosive effect on metal.

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	:	No applicable information available. No decomposition if stored and applied as directed.
Chemical stability	:	The product is stable if stored and handled as prescribed/indicated. No decomposition if stored and applied as directed.

## MasterSeal TC 275 PART B

Version	Revision Date:	SDS Number:	Date of last issue: 04/27/2020
1.1	07/27/2020	000000534220	Date of first issue: 04/27/2020

---

Possibility of hazardous reactions	:	Reacts with water, with formation of carbon dioxide. Risk of bursting. Reacts with alcohols. Reacts with acids. Reacts with alkalies. Reacts with amines. Risk of exothermic reaction. Risk of violent reaction. Risk of polymerization. Contact with certain rubbers and plastics can cause brittleness of the substance/product with subsequent loss in strength. The product is chemically stable.
Conditions to avoid	:	Avoid moisture.
Incompatible materials	:	Water Alcohols Strong bases Substances/products that react with isocyanates.
Hazardous decomposition products	:	nitrogen oxides Aromatic isocyanates gases/vapours

---

**SECTION 11. TOXICOLOGICAL INFORMATION****Acute toxicity**

Harmful if inhaled.

**Product:**

Acute inhalation toxicity : 1.01 mg/l

**Skin corrosion/irritation**

Causes skin irritation.

**Serious eye damage/eye irritation**

Causes serious eye irritation.

**Respiratory or skin sensitization****Skin sensitization**

May cause an allergic skin reaction.

**Respiratory sensitization**

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

**Germ cell mutagenicity**

Not classified based on available information.

**Carcinogenicity**

Not classified based on available information.

**Reproductive toxicity**

Not classified based on available information.

**STOT-single exposure**

May cause respiratory irritation.



## MasterSeal TC 275 PART B

Version	Revision Date:	SDS Number:	Date of last issue: 04/27/2020
1.1	07/27/2020	000000534220	Date of first issue: 04/27/2020

---

**STOT-repeated exposure**

May cause damage to organs (Olfactory organ) through prolonged or repeated exposure.

**Aspiration toxicity**

Not classified based on available information.

**Further information****Product:**

Remarks : The product has not been tested. The statement has been derived from the properties of the individual components.

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity**

No data available

**Persistence and degradability**

No data available

**Bioaccumulative potential****Components:****Diphenylmethane-4,4'-diisocyanate (MDI):**

Partition coefficient: n-octanol/water : log Pow: 4.51 (72 °F / 22 °C)  
pH: 7  
Method: Partition coefficient (n-octanol/water), HPLC method.  
GLP: no

**methylenediphenyl diisocyanate:**

Partition coefficient: n-octanol/water : log Pow: 4.51 (72 °F / 22 °C)  
pH: 7  
Method: Partition coefficient (n-octanol/water), HPLC method.  
GLP: no

**2,4-Dioxo-1,3-diazetidino-1,3-diylbis[p-phenylenemethylene-p-phenylene] diisocyanate:**

Partition coefficient: n-octanol/water : Remarks: not applicable

**Mobility in soil**

No data available

**Other adverse effects****Product:**

Additional ecological information : There is a high probability that the product is not acutely harmful to aquatic organisms.  
The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

## MasterSeal TC 275 PART B

Version	Revision Date:	SDS Number:	Date of last issue: 04/27/2020
1.1	07/27/2020	000000534220	Date of first issue: 04/27/2020

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues : Dispose of in accordance with national, state and local regulations.  
Do not discharge into drains/surface waters/groundwater.  
Do not contaminate ponds, waterways or ditches with chemical or used container.

Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

**SECTION 14. TRANSPORT INFORMATION****International Regulations****UNRTDG**

Not regulated as a dangerous good

**IATA-DGR**

Not regulated as a dangerous good

**IMDG-Code**

Not regulated as a dangerous good

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**Domestic regulation****49 CFR**

Not regulated as a dangerous good

**SECTION 15. REGULATORY INFORMATION****EPCRA - Emergency Planning and Community Right-to-Know****CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Diphenylmethane-4,4'-diisocyanate (MDI)	101-68-8	5000	9197
Diphenylmethane-4,4'-diisocyanate (MDI)	101-68-8	5000	9197

**US State Regulations****Pennsylvania Right To Know**

Diphenylmethane-4,4'-diisocyanate (MDI)	101-68-8
Isocyanic acid, polymethylenepolyphenylene ester (P-MDI) listed	9016-87-9

**New Jersey Right To Know**

methylenediphenyl diisocyanate	26447-40-5
Isocyanic acid, polymethylenepolyphenylene ester (P-MDI)	9016-87-9
Diphenylmethane-4,4'-diisocyanate (MDI)	101-68-8

**MasterSeal TC 275 PART B**

Version 1.1      Revision Date: 07/27/2020      SDS Number: 000000534220      Date of last issue: 04/27/2020  
 Date of first issue: 04/27/2020

listed


**The ingredients of this product are reported in the following inventories:**

TSCA : On the inventory, or in compliance with the inventory

**SECTION 16. OTHER INFORMATION**

**Further information**

**NFPA 704:**



**HMIS® IV:**

<b>HEALTH</b>		
<b>FLAMMABILITY</b>		
<b>PHYSICAL HAZARD</b>		

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

**Full text of other abbreviations**

- 29 CFR 1910.1000 (Table Z-1-A) : OSHA - Table Z-1-A (29 CFR 1910.1000)
- 29 CFR 1910.1000 (Table Z-1) : OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR 1910.1000
- ACGIH : USA. ACGIH Threshold Limit Values (TLV)
- ACGIHTLV : American Conference of Governmental Industrial Hygienists - threshold limit values (US)
- NIOSH : NIOSH Pocket Guide to Chemical Hazards (US)
- NIOSH REL : USA. NIOSH Recommended Exposure Limits
- OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
- OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
- 29 CFR 1910.1000 (Table Z-1-A) / CLV : Ceiling Limit Value:
- 29 CFR 1910.1000 (Table Z-1-A) / TWA value : Time Weighted Average (TWA):
- 29 CFR 1910.1000 (Table Z-1) / CLV : Ceiling Limit Value:
- 29 CFR 1910.1000 (Table Z-1) / PEL : Permissible exposure limit
- ACGIH / TWA : 8-hour, time-weighted average
- ACGIH / C : Ceiling limit

## MasterSeal TC 275 PART B

Version	Revision Date:	SDS Number:	Date of last issue: 04/27/2020
1.1	07/27/2020	000000534220	Date of first issue: 04/27/2020

ACGIHTLV / CLV	:	Ceiling Limit Value:
ACGIHTLV / TWA value	:	Time Weighted Average (TWA):
NIOSH / Ceil_Time	:	Ceiling Limit Value and Time Period (if specified):
NIOSH / REL value	:	Recommended exposure limit (REL):
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
NIOSH REL / C	:	Ceiling value not be exceeded at any time.
OSHA P0 / TWA	:	8-hour time weighted average
OSHA P0 / STEL	:	Short-term exposure limit
OSHA P0 / C	:	Ceiling limit
OSHA Z-1 / TWA	:	8-hour time weighted average
OSHA Z-1 / C	:	Ceiling

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 07/27/2020

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our com-

**MasterSeal TC 275 PART B**

Version	Revision Date:	SDS Number:	Date of last issue: 04/27/2020
1.1	07/27/2020	000000534220	Date of first issue: 04/27/2020

---

mitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

US / EN