

MasterTop GP 500 light grey

Version 1.0 Revision Date: 09/01/2020 SDS Number: 000000260714 Date of last issue: -
Date of first issue: 09/01/2020

SECTION 1. IDENTIFICATION

Product name : MasterTop GP 500 light grey
Product code : 000000000051652675 000000000051652675

Manufacturer or supplier's details

Company name of supplier : Master Builders-Admixtures US,LLC
Address : 23700 CHAGRIN BLVD
Beachwood OH 44122
Emergency telephone : ChemTel: +1-813-248-0585 USA: +1-800-255-3924 Contract
Number MIS9240420


Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals
Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with 29 CFR 1910.1200**

Skin corrosion/irritation : 2
Serious eye damage/eye irritation : Category 2A
Skin sensitization : Category 1
Short-term (acute) aquatic hazard : 2
Long-term (chronic) aquatic hazard : 2

GHS label elements

Hazard pictograms : 

Signal Word : Warning

Hazard Statements : H319 Causes serious eye irritation.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H401 Toxic to aquatic life.
H411 Toxic to aquatic life with long lasting effects.

Precautionary Statements : **Prevention:**
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P273 Avoid release to the environment.
P272 Contaminated work clothing should not be allowed out of

MasterTop GP 500 light grey

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/01/2020	000000260714	Date of first issue: 09/01/2020

the workplace.
P264 Wash face, hands and any exposed skin thoroughly after handling.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P303 + P352 IF ON SKIN (or hair): Wash with plenty of soap and water.

P333 + P311 If skin irritation or rash occurs: Call a POISON CENTER or doctor/physician.

P332 + P313 If skin irritation occurs: Get medical advice/attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P391 Collect spillage.

P337 + P311 If eye irritation persists: Call a POISON CENTER or doctor/physician.

Disposal:

P501 Dispose of contents/container to appropriate hazardous waste collection point.

Other hazards

No data available.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : No data available.

Components

Chemical name	CAS-No.	Concentration (% w/w)
Reaction product: bisphenol-A-(epichlorhydrin)-Epoxy resin (number average molecular weight <= 700)	25068-38-6	>= 0 - < 100
bisphenol A-epichlorohydrin resin	25068-38-6	>= 0 - < 100
Titanium dioxide	13463-67-7	>= 3 - < 5
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	68609-97-2	>= 1 - < 3
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	28961-43-5	>= 1 - < 3
Distillates (petroleum), hydrotreated light	64742-47-8	>= 0.1 - < 0.2

SECTION 4. FIRST AID MEASURES

General advice : Remove contaminated clothing.
Move out of dangerous area.
Show this material safety data sheet to the doctor in attendance.
Do not leave the victim unattended.

If inhaled : Keep patient calm, remove to fresh air, seek medical atten-

MasterTop GP 500 light grey

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/01/2020	000000260714	Date of first issue: 09/01/2020

- tion.
If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : Wash thoroughly with soap and water
If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.
Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.
Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
- Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Foam
Dry powder
Carbon dioxide (CO₂)
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

MasterTop GP 500 light grey

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/01/2020	000000260714	Date of first issue: 09/01/2020

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Product is not explosive.

Normal measures for preventive fire protection.

Advice on safe handling : Do not breathe vapors/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Dispose of rinse water in accordance with local and national regulations.
Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame.
Protect from direct sunlight.

Materials to avoid : Observe VCI storage rules.

Further information on storage stability : No data available

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Ingredients with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Titanium dioxide	13463-67-7	TWA value	10 mg/m ³	ACGIHTLV
		PEL (Total dust)	15 mg/m ³	29 CFR 1910.1000 (Table Z-1)
		TWA value (Total dust)	10 mg/m ³	29 CFR 1910.1000 (Table Z-1-A)
		TWA (total dust)	15 mg/m ³	OSHA Z-1

MasterTop GP 500 light grey

Version 1.0 Revision Date: 09/01/2020 SDS Number: 000000260714 Date of last issue: -
 Date of first issue: 09/01/2020

		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA	10 mg/m3 (Titanium dioxide)	ACGIH
Distillates (petroleum), hydrotreated light	64742-47-8	TWA value (Non-aerosol)	200 mg/m3 (total hydrocarbon vapor)	ACGIHTLV
		Skin Designation (Non-aerosol)		ACGIHTLV
		REL value	100 mg/m3	NIOSH
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA	200 mg/m3 (total hydrocarbon vapor)	ACGIH
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL

Engineering measures : No applicable information available.

Personal protective equipment

Respiratory protection : When workers are facing concentrations above the occupational exposure limits they must use appropriate certified respirators.

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Protective measures : Do not inhale gases/vapours/aerosols.
Avoid contact with the skin, eyes and clothing.
Avoid exposure - obtain special instructions before use.
Handle in accordance with good building materials hygiene and safety practice.
Wearing of closed work clothing is recommended.

Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid
 Color : pigmented
 Odor : mild, sweetish
 Odor Threshold : No data available

MasterTop GP 500 light grey

Version 1.0 Revision Date: 09/01/2020 SDS Number: 000000260714 Date of last issue: -
Date of first issue: 09/01/2020

pH	:	neutral to slightly alkaline
Melting point	:	No applicable information available.
Boiling point	:	approx. 300 °F / 149 °C
Flash point	:	210 °F / 99 °C Method: Flash-Point by Pensky-Martens Closed Cup Tester.
Evaporation rate	:	No applicable information available.
Flammability (solid, gas)	:	not highly flammable Method: derived from flash point
Upper explosion limit / Upper flammability limit	:	No data available.
Lower explosion limit / Lower flammability limit	:	No data available.
Vapor pressure	:	No applicable information available.
Relative density	:	No applicable information available.
Density	:	approx. 1.20 g/cm ³ (68 °F / 20 °C)
Solubility(ies)		
Water solubility	:	insoluble (68 °F / 20 °C)
Solubility in other solvents	:	No applicable information available.
Partition coefficient: n-octanol/water	:	No applicable information available.
Autoignition temperature	:	No data available
Decomposition temperature	:	No decomposition if stored and handled as prescribed/indicated.
Viscosity		
Viscosity, dynamic	:	No applicable information available.
Viscosity, kinematic	:	No applicable information available.
Explosive properties	:	Not explosive Not explosive
Oxidizing properties	:	Based on its structural properties the product is not classified as oxidizing.
Sublimation point	:	No applicable information available.
Molecular weight	:	No data available

MasterTop GP 500 light grey

Version 1.0 Revision Date: 09/01/2020 SDS Number: 000000260714 Date of last issue: -
Date of first issue: 09/01/2020

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration hazard expected.

Further information**Product:**

Remarks : No data available

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity**

No data available

Persistence and degradability

No data available

Bioaccumulative potential**Components:****Titanium dioxide:**

Partition coefficient: n-octanol/water : Remarks: not applicable

oxirane, mono[(C12-14-alkyloxy)methyl] derivs.:

Partition coefficient: n-octanol/water : log Pow: 7.25 (77 °F / 25 °C)
Method: other (calculated)
GLP: no

Propylidynetrimethanol, ethoxylated, esters with acrylic acid:

Partition coefficient: n-octanol/water : log Pow: 2.89 (73 °F / 23 °C)
pH: 8.1
Method: Partition coefficient (n-octanol/water), Shake-flask method
GLP: no

Distillates (petroleum), hydrotreated light:

Partition coefficient: n-octanol/water : log Pow: > 3.0

MasterTop GP 500 light grey

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/01/2020	000000260714	Date of first issue: 09/01/2020

Labels : 9 (EHSM)
 EmS Code : F-A, S-F
 Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation**49 CFR**

Not regulated as a dangerous good

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION**US State Regulations****Pennsylvania Right To Know**

Titanium dioxide listed	13463-67-7
-------------------------	------------

New Jersey Right To Know

Titanium dioxide listed	13463-67-7
-------------------------	------------

The ingredients of this product are reported in the following inventories:


TSCA : On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION**Further information**

MasterTop GP 500 light grey

Version 1.0 Revision Date: 09/01/2020 SDS Number: 000000260714 Date of last issue: -
Date of first issue: 09/01/2020

NFPA 704:



HMIS® IV:

HEALTH		
FLAMMABILITY		
PHYSICAL HAZARD		

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

29 CFR 1910.1000 (Table Z-1-A)	: OSHA - Table Z-1-A (29 CFR 1910.1000)
29 CFR 1910.1000 (Table Z-1)	: OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR 1910.1000
ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
ACGIHTLV	: American Conference of Governmental Industrial Hygienists - threshold limit values (US)
NIOSH	: NIOSH Pocket Guide to Chemical Hazards (US)
NIOSH REL	: USA. NIOSH Recommended Exposure Limits
OSHA P0	: USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
OSHA Z-1	: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
29 CFR 1910.1000 (Table Z-1-A) / TWA value	: Time Weighted Average (TWA):
29 CFR 1910.1000 (Table Z-1) / PEL	: Permissible exposure limit
ACGIH / TWA	: 8-hour, time-weighted average
ACGIHTLV / Skin Designation	: Skin Designation:
ACGIHTLV / TWA value	: Time Weighted Average (TWA):
NIOSH / REL value	: Recommended exposure limit (REL):
NIOSH REL / TWA	: Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	: STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA P0 / TWA	: 8-hour time weighted average
OSHA Z-1 / TWA	: 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic

MasterTop GP 500 light grey

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/01/2020	000000260714	Date of first issue: 09/01/2020

Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 09/01/2020

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND

MasterTop GP 500 light grey

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/01/2020	000000260714	Date of first issue: 09/01/2020

INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

US / EN