

MasterWeld 948 gray

Version 1.0 Revision Date: 12/04/2020 SDS Number: 000000260127 Date of last issue: -
Date of first issue: 12/04/2020

SECTION 1. IDENTIFICATION

Product name : MasterWeld 948 gray
Product code : 000000000055353983 000000000055353983

Manufacturer or supplier's details

Company name of supplier : Master Builders-Admixtures US,LLC
Address : 23700 CHAGRIN BLVD
Beachwood OH 44122
Emergency telephone : ChemTel: +1-813-248-0585 USA: +1-800-255-3924 Contract
Number MIS9240420


Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals
Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with 29 CFR 1910.1200**

Acute toxicity (Inhalation) : Category 4
Skin corrosion/irritation : Category 2
Serious eye damage/eye irritation : Category 2A
Respiratory sensitization : Category 1
Skin sensitization : Category 1
Skin sensitization : Category 1B
Specific target organ toxicity - single exposure : Category 3
Specific target organ toxicity - repeated exposure (Inhalation) : Category 2 (Olfactory organs)

GHS label elements

Hazard pictograms : 

Signal Word : Danger

Hazard Statements : H320 Causes eye irritation.
H315 Causes skin irritation.
H332 Harmful if inhaled.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317 May cause an allergic skin reaction.

MasterWeld 948 gray

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	12/04/2020	000000260127	Date of first issue: 12/04/2020

H335 May cause respiratory irritation.
H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary Statements :

Prevention:

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P271 Use only outdoors or in a well-ventilated area.
P201 Obtain special instructions before use.
P260 Do not breathe dust or mist.
P261 Avoid breathing mist.
P202 Do not handle until all safety precautions have been read and understood.
P284 In case of inadequate ventilation wear respiratory protection.
P272 Contaminated work clothing should not be allowed out of the workplace.
P264 Wash face, hands and any exposed skin thoroughly after handling.

Response:

P308 + P311 IF exposed or concerned: Call a POISON CENTER/ doctor.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P314 Get medical advice/ attention if you feel unwell.
P303 + P352 IF ON SKIN (or hair): Wash with plenty of soap and water.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P337 + P311 If eye irritation persists: Call a POISON CENTER or doctor/physician.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.

Disposal:

P501 Dispose of contents/container to appropriate hazardous waste collection point.

Other hazards

CONTAINS ISOCYANATES. INHALATION OF ISOCYANATE MISTS OR VAPORS MAY CAUSE RESPIRATORY IRRITATION, BREATHLESSNESS, CHEST DISCOMFORT AND REDUCED PULMONARY FUNCTION. OVEREXPOSURE WELL ABOVE THE PEL MAY RESULT IN BRONCHITIS, BRONCHIAL SPASMS AND PULMONARY EDEMA. LONG-TERM EXPOSURE TO ISOCYANATES HAS BEEN REPORTED TO CAUSE LUNG DAMAGE, INCLUDING REDUCED LUNG FUNCTION WHICH MAY BE PERMANENT. ACUTE OR

MasterWeld 948 gray

Version 1.0 Revision Date: 12/04/2020 SDS Number: 000000260127 Date of last issue: -
Date of first issue: 12/04/2020

CHRONIC OVEREXPOSURE TO ISOCYANATES MAY CAUSE SENSITIZATION IN SOME INDIVIDUALS, RESULTING IN ALLERGIC RESPIRATORY REACTIONS INCLUDING WHEEZING, SHORTNESS OF BREATH AND DIFFICULTY BREATHING. ANIMAL TESTS INDICATE THAT SKIN CONTACT MAY PLAY A ROLE IN CAUSING RESPIRATORY SENSITIZATION.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : No data available.

Components

Chemical name	CAS-No.	Concentration (% w/w)
Isocyanic acid, polymethylenepolyphenylene ester, polymer with methoxirane polymer with oxirane ether with 2-ethyl-2-(hydroxymethyl)-1,3-propanediol (3:1)	58228-06-1	>= 25 - < 50
talc	14807-96-6	>= 25 - < 50
Diphenylmethane-4,4'-diisocyanate (MDI)	101-68-8	>= 10 - < 15
Distillates (petroleum), hydrotreated middle	64742-46-7	>= 7 - < 10
methylenediphenyl diisocyanate	26447-40-5	>= 3 - < 5
Isocyanic acid, polymethylenepolyphenylene ester (P-MDI)	9016-87-9	>= 1 - < 3
Polymethylene polyphenylisocyanate, polyethylene glycol polymer	57636-09-6	>= 0.1 - < 0.2

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Show this material safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : Remove the affected individual into fresh air and keep the person calm.
Assist in breathing if necessary.
Immediate medical attention required.
Call a physician or poison control center immediately.
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : Wash affected areas thoroughly with soap and water.
If irritation develops, seek medical attention.
If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water.
Immediate medical attention required.
Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.

MasterWeld 948 gray

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	12/04/2020	000000260127	Date of first issue: 12/04/2020

If swallowed	:	<p>Keep eye wide open while rinsing. If eye irritation persists, consult a specialist. Rinse mouth and then drink 200-300 ml of water. Do NOT induce vomiting. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Immediate medical attention required. Induce vomiting immediately and call a physician. Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.</p>
Most important symptoms and effects, both acute and delayed	:	<p>Causes skin and eye irritation. May cause an allergic skin reaction. Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure.</p>
Notes to physician	:	Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	<p>Foam Dry powder Water spray Carbon dioxide (CO₂)</p>
Unsuitable extinguishing media	:	High volume water jet
Hazardous combustion products	:	<p>nitrous gases fumes/smoke isocyanate vapor</p>
Further information	:	<p>Keep containers cool by spraying with water if exposed to fire. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations. Standard procedure for chemical fires. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.</p>
Special protective equipment for fire-fighters	:	<p>Firefighters should be equipped with self-contained breathing apparatus and turn-out gear. Wear self-contained breathing apparatus for firefighting if necessary.</p>

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	:	<p>Clear area. Ensure adequate ventilation. Wear suitable personal protective clothing and equipment. Use personal protective equipment. Avoid dust formation. Avoid breathing dust.</p>
---	---	--

MasterWeld 948 gray

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	12/04/2020	000000260127	Date of first issue: 12/04/2020

- Ensure adequate ventilation.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Dike spillage.
- Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Avoid dust formation.
Provide appropriate exhaust ventilation at places where dust is formed.
- Advice on safe handling : Provide suitable exhaust ventilation at the processing machines.
Ensure thorough ventilation of stores and work areas.
Avoid aerosol formation.
When handling heated product, vapours of the product should be ventilated, and respiratory protection used.
Wear respiratory protection when spraying.
Danger of bursting when sealed gastight.
Protect against moisture.
If bulging of drum occurs, transfer to well ventilated area, puncture to relieve pressure, open vent and let stand for 48 hours before resealing.
Avoid formation of respirable particles.
Do not breathe vapors/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Provide sufficient air exchange and/or exhaust in work rooms.
Dispose of rinse water in accordance with local and national regulations.
Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage conditions : Keep only in the original container in a cool, well-ventilated place.
Protect from direct sunlight.
Store protected against freezing.

MasterWeld 948 gray

Version 1.0 Revision Date: 12/04/2020 SDS Number: 000000260127 Date of last issue: -
 Date of first issue: 12/04/2020

Materials to avoid : Observe VCI storage rules.

Further information on storage stability : No data available

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Diphenylmethane-4,4'-diisocyanate (MDI)	101-68-8	TWA value	0.005 ppm	ACGIHTLV
		REL value	0.005 ppm 0.05 mg/m ³	NIOSH
		Ceil_Time	0.020 ppm 0.2 mg/m ³	NIOSH
		CLV	0.02 ppm 0.2 mg/m ³	29 CFR 1910.1000 (Table Z-1)
		CLV	0.02 ppm 0.2 mg/m ³	29 CFR 1910.1000 (Table Z-1-A)
		TWA	0.005 ppm	ACGIH
		C	0.02 ppm 0.2 mg/m ³	OSHA Z-1
		C	0.02 ppm 0.2 mg/m ³	OSHA P0
		TWA	0.005 ppm 0.05 mg/m ³	NIOSH REL
		C	0.02 ppm 0.2 mg/m ³	NIOSH REL
Isocyanic acid, polymethylenepolyphenylene ester (P-MDI)	9016-87-9	C	0.02 ppm 0.2 mg/m ³	OSHA Z-1
		C	0.02 ppm 0.2 mg/m ³	OSHA P0
		TWA	0.005 ppm 0.05 mg/m ³	NIOSH REL
		C	0.02 ppm 0.2 mg/m ³	NIOSH REL
		TWA	0.005 ppm 0.05 mg/m ³	NIOSH REL
talc	14807-96-6	TWA value (Respirable fraction)	2 mg/m ³	ACGIHTLV
		TWA (Dust)	20 Million particles per cubic foot	OSHA Z-3
		TWA (respirable dust fraction)	2 mg/m ³	OSHA P0
		TWA (Respirable)	2 mg/m ³	NIOSH REL
		TWA	0.1 fibres per cubic centimeter	ACGIH

MasterWeld 948 gray

Version 1.0 Revision Date: 12/04/2020 SDS Number: 000000260127 Date of last issue: -
 Date of first issue: 12/04/2020

		TWA (Respirable particulate matter)	2 mg/m ³	ACGIH
Distillates (petroleum), hydrotreated middle	64742-46-7	TWA value (Inhalable fraction)	5 mg/m ³	ACGIH TLV
		STEL value (Mist)	10 mg/m ³	NIOSH
		REL value (Mist)	5 mg/m ³	NIOSH
		PEL (Mist)	5 mg/m ³	29 CFR 1910.1000 (Table Z-1)
		TWA value (Mist)	5 mg/m ³	29 CFR 1910.1000 (Table Z-1-A)
		TWA (Mist)	5 mg/m ³	OSHA Z-1
		TWA (Mist)	5 mg/m ³	OSHA P0
		TWA (Mist)	5 mg/m ³	NIOSH REL
		ST (Mist)	10 mg/m ³	NIOSH REL

Engineering measures : No applicable information available.

Personal protective equipment

Respiratory protection : When workers are facing concentrations above the occupational exposure limits they must use appropriate certified respirators.
 When atmospheric levels may exceed the occupational exposure limit (PEL or TLV) NIOSH-certified air-purifying respirators equipped with an organic vapor sorbent and particulate filter can be used as long as appropriate precautions and change out schedules are in place.
 For emergency or non-routine, high exposure situations, including confined space entry, use a NIOSH-certified full facepiece pressure demand self-contained breathing apparatus (SCBA) or a full facepiece pressure demand supplied-air respirator (SAR) with escape provisions.

Hand protection

Remarks : Chemical resistant protective gloves should be worn to prevent all skin contact. Suitable materials may include chloroprene rubber (Neoprene) nitrile rubber (Buna N) chlorinated polyethylene polyvinylchloride (Pylox) butyl rubber depending upon conditions of use.
 The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Tightly fitting safety goggles (chemical goggles).
 Wear face shield if splashing hazard exists.
 Eye wash bottle with pure water
 Tightly fitting safety goggles
 Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection : Cover as much of the exposed skin as possible to prevent all

MasterWeld 948 gray

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	12/04/2020	000000260127	Date of first issue: 12/04/2020

skin contact.
Suitable materials may include saran-coated material depending upon conditions of use.
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Protective measures : Wear protective clothing as necessary to prevent contact. Eye wash fountains and safety showers must be easily accessible.

Hygiene measures : Observe the appropriate PEL or TLV value.
Wash soiled clothing immediately. Remove contaminated clothing immediately and clean before re-use or dispose it if necessary. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : paste

Color : tan

Odor : oily, mild

Odor Threshold : No data available

pH : neutral to slightly alkaline

Melting point : No applicable information available.

Boiling point : 342.00 - 514.00 °F / 172.22 - 267.78 °C

Flash point : 250.00 °F / 121.11 °C

Evaporation rate : No applicable information available.

Flammability (solid, gas) : not highly flammable
Method: derived from flash point

Self-ignition : not self-igniting

Upper explosion limit / Upper flammability limit : 10.2 %(V)

Lower explosion limit / Lower flammability limit : 1.6 %(V)

Vapor pressure : No data available.

Relative vapor density : Heavier than air.

Relative density : 1.26

MasterWeld 948 gray

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	12/04/2020	000000260127	Date of first issue: 12/04/2020

Bulk density	:	1,800 - 2,400 kg/m ³
Solubility(ies)	:	
Water solubility	:	slightly soluble
	:	No applicable information available.
Solubility in other solvents	:	slightly soluble
Partition coefficient: n-octanol/water	:	No data available.
Autoignition temperature	:	No data available.
Decomposition temperature	:	No decomposition if stored and handled as prescribed/indicated.
Viscosity	:	
Viscosity, dynamic	:	No data available.
Viscosity, kinematic	:	No applicable information available.
Explosive properties	:	Not explosive Not explosive
Oxidizing properties	:	Based on its structural properties the product is not classified as oxidizing.
Self-heating substances	:	No data available
Sublimation point	:	No applicable information available.
Molecular weight	:	No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	No decomposition if stored and applied as directed.
Conditions to avoid	:	See SDS section 7 - Handling and storage.
Incompatible materials	:	Strong oxidizing agents Strong bases Strong acids
Hazardous decomposition products	:	No hazardous decomposition products if stored and handled as prescribed/indicated.

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity**

Harmful if inhaled.

Product:

Acute oral toxicity : Remarks: No applicable information available.

MasterWeld 948 gray

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	12/04/2020	000000260127	Date of first issue: 12/04/2020

Acute inhalation toxicity : ATE: 3.45 mg/l
Remarks: Determined for mist

Acute dermal toxicity : Remarks: No data available.

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks : May cause skin irritation and/or dermatitis.

Serious eye damage/eye irritation

Causes eye irritation.

Product:

Remarks : May cause irreversible eye damage.

Respiratory or skin sensitization**Skin sensitization**

May cause an allergic skin reaction.

Respiratory sensitization

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Product:

Remarks : Causes sensitization.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

Product:

Study scientifically not justified.

Further information**Product:**

Remarks : No data available

MasterWeld 948 gray

Version 1.0 Revision Date: 12/04/2020 SDS Number: 000000260127 Date of last issue: -
Date of first issue: 12/04/2020

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity**

No data available

Persistence and degradability

No data available

Bioaccumulative potential**Components:****Diphenylmethane-4,4'-diisocyanate (MDI):**

Partition coefficient: n-octanol/water : log Pow: 4.51 (72 °F / 22 °C)
pH: 7
Method: Partition coefficient (n-octanol/water), HPLC method.
GLP: no

Distillates (petroleum), hydrotreated middle:

Partition coefficient: n-octanol/water : Remarks: No data available.

methylenediphenyl diisocyanate:

Partition coefficient: n-octanol/water : log Pow: 4.51 (72 °F / 22 °C)
pH: 7
Method: Partition coefficient (n-octanol/water), HPLC method.
GLP: no

Mobility in soil

No data available

Other adverse effects**Product:**

Additional ecological information : There is a high probability that the product is not acutely harmful to aquatic organisms.
The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Dispose of in accordance with national, state and local regulations.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

MasterWeld 948 gray

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	12/04/2020	000000260127	Date of first issue: 12/04/2020

SECTION 14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation**49 CFR**

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

Diphenylmethane-4,4'-diisocyanate (MDI)	101-68-8
---	----------

Isocyanic acid, polymethylene-polyphenylene ester (P-MDI)	9016-87-9
---	-----------

US State Regulations**Pennsylvania Right To Know**

Diphenylmethane-4,4'-diisocyanate (MDI)	101-68-8
Isocyanic acid, polymethylenepolyphenylene ester (P-MDI)	9016-87-9
talc	14807-96-6
Distillates (petroleum), hydrotreated middle	64742-46-7

New Jersey Right To Know

Diphenylmethane-4,4'-diisocyanate (MDI)	101-68-8
Isocyanic acid, polymethylenepolyphenylene ester (P-MDI)	9016-87-9
talc	14807-96-6
methylenediphenyl diisocyanate	26447-40-5
Distillates (petroleum), hydrotreated middle	64742-46-7

California Prop. 65

WARNING: This product can expose you to chemicals including Titanium dioxide, Carbon black, which is/are known to the State of California to cause cancer, and

MasterWeld 948 gray

Version 1.0 Revision Date: 12/04/2020 SDS Number: 000000260127 Date of last issue: -
 Date of first issue: 12/04/2020

toluene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.


The ingredients of this product are reported in the following inventories:

TSCA : On the inventory, or in compliance with the inventory


SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

- 29 CFR 1910.1000 (Table Z-1-A) : OSHA - Table Z-1-A (29 CFR 1910.1000)
- 29 CFR 1910.1000 (Table Z-1) : OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR 1910.1000
- ACGIH : USA. ACGIH Threshold Limit Values (TLV)
- ACGIHTLV : American Conference of Governmental Industrial Hygienists - threshold limit values (US)
- NIOSH : NIOSH Pocket Guide to Chemical Hazards (US)
- NIOSH REL : USA. NIOSH Recommended Exposure Limits
- OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
- OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
- OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
- 29 CFR 1910.1000 (Table Z-1-A) / CLV : Ceiling Limit Value:
- 29 CFR 1910.1000 (Table Z-1-A) / TWA value : Time Weighted Average (TWA):
- 29 CFR 1910.1000 (Table Z-1) / CLV : Ceiling Limit Value:
- 29 CFR 1910.1000 (Table Z-) : Permissible exposure limit

MasterWeld 948 gray

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	12/04/2020	000000260127	Date of first issue: 12/04/2020

1) / PEL
 ACGIH / TWA : 8-hour, time-weighted average
 ACGIHTLV / TWA value : Time Weighted Average (TWA):
 NIOSH / Ceil_Time : Ceiling Limit Value and Time Period (if specified):
 NIOSH / REL value : Recommended exposure limit (REL):
 NIOSH / STEL value : Short Term Exposure Limit (STEL):
 NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour
 workday during a 40-hour workweek
 NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded
 at any time during a workday
 NIOSH REL / C : Ceiling value not be exceeded at any time.
 OSHA P0 / TWA : 8-hour time weighted average
 OSHA P0 / C : Ceiling limit
 OSHA Z-1 / TWA : 8-hour time weighted average
 OSHA Z-1 / C : Ceiling
 OSHA Z-3 / TWA : 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 12/04/2020

MasterWeld 948 gray

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	12/04/2020	000000260127	Date of first issue: 12/04/2020

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

US / EN