

MasterFinish[®] RL 200

Water-based form release agent

Description

MasterFinish RL 200 form release agent offers a safe, cost-effective alternative to traditional oil-based release agents. When applied to most forms and form liners, it is formulated to enhance the surface appearance of precast, prestressed and cast-in-place concrete.

MasterFinish RL 200 form release agent significantly reduces labor cost through its ease of use.

Applications

Recommended for use in:

- Cast-in-place concrete
- Precast concrete

Substrate

- Steel forms
- Fiberglass forms
- Concrete forms
- Wood forms

Features

- Ready-to-use
- Assists in controlling surface appearance
- Non-staining
- Spray-applied
- Water-based
- Significantly reduces form cleaning

Benefits

- Permits match casting of intricate details
- Minimizes surface voids (bug holes)
- Reduces overall production costs
- No mixing required
- No solvent, no odor; no fume or flammability problems
- Environmentally preferable and biodegradable

Guidelines for Use

Yield: Up to 1,500 ft²/gal (35 m²/L). Coverage rates depend on form or form liner's texture and absorption rate.

Surface Preparation:

1. Forms must be smooth, clean and dry before applying form release agent.
2. MasterFinish RL 200 form release agent is specifically developed to work at the form surface and cement paste interface. The performance of this product will be significantly hindered by oil contaminants and cement paste build-up. Forms having residue such as this can be wire brushed and wiped with solvent and then, a dry rag before applying MasterFinish RL 200 form release agent.
3. Once thoroughly cleaned, forms will be maintained in this condition through the use of MasterFinish RL 200 form release agent and will also produce more visually appealing products as a result.

Application:

1. When spraying MasterFinish RL 200 form release agent, hold the spray tip at a distance of 2 – 3 feet (60 – 90 cm) from the form surface being treated to achieve proper coverage.
2. When properly treated forms are required to have a uniform thin film, with a slight waxy feel.
3. MasterFinish RL 200 form release agent may also be wiped, mopped, rolled or brush applied. However, the potential for over-application is greater when using these methods. Over-application can result in surface dusting or surface tearing.
4. A white residue may be visible on the forms after application, which is normal for many water-based form release agents.
5. Excessive rain after application prior to concrete placement may require re-application.

Spray Equipment: MasterFinish RL 200 form release agent should be applied to forms and form liners with spray equipment of the type recommended by Master Builders Solutions. A spray device with an air pressure capacity of approximately 80 psi (0.5 MPa) has been found to produce the best results. A spray tip with an orifice of 0.021 in. (0.53 mm) delivering an oval spray pattern is recommended for smaller, intricate formwork. For large forms (wall panels, structural units, etc.) a spray tip with an orifice size of 0.036 in. (0.91 mm) delivering a tall, narrow fan spray pattern is recommended. For information regarding sprayer sources, contact your local sales representative.

Cleaning: Clean spray equipment, brushes, and rollers with soap and water before they dry.

For Best Performance

- MasterFinish RL 200 form release agent is compatible with most forms and form liners with the exception of those made of styrene or latex.
- Make certain the most current versions of product data sheet and Safety Data Sheet are being used; call your local sales representative to verify the most current versions.

Storage and Handling

Storage Temperature: Store in unopened container in a cool, clean, dry area between 40 and 85 °F (4 and 30 °C). Keep containers tightly sealed after opening to maintain shelf life freshness. Protect from freezing. Do not store in direct sunlight.

Shelf Life: 1 year when properly stored.

Packaging

- 5 gal (18.9 L) pails
- 55 gal (208 L) drums
- 275 gal (1041 L) totes

Related Documents

Safety Data Sheets: MasterFinish RL 200 form release agent

Additional Information

For suggested specification information or for additional product data on MasterFinish RL 200 form release agent, contact your local sales representative.

Master Builders Solutions, a brand of MBCC Group, is a global leader of innovative chemistry systems and formulations for construction, maintenance, repair and restoration of structures. The Admixture Systems business provides advanced products, solutions and expertise that improve durability, water resistance, energy efficiency, safety, sustainability and aesthetics of concrete structures, above and below ground, helping customers to achieve reduced operating costs, improved efficiency and enhanced finished products.

Utilizing worldwide resources, the Master Builders Solutions community of experts are passionate about providing solutions to challenges within all stages of construction, as well as the life cycle of a structure. At Master Builders Solutions we create sustainable solutions for construction around the globe.

Limited Warranty Notice

Master Builders Solutions Admixtures US, LLC ("Master Builders Solutions") warrants this product to be free from manufacturing defects and to meet the technical properties on the current Technical Data Guide, if used as directed within shelf life. Satisfactory results depend not only on quality products but also upon many factors beyond our control. Master Builders Solutions MAKES NO OTHER WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO ITS PRODUCTS. The sole and exclusive remedy of Purchaser for any claim concerning this product, including but not limited to, claims alleging breach of warranty, negligence, strict liability or otherwise, is shipment to purchaser of product equal to the amount of product that fails to meet this warranty or refund of the original purchase price of product that fails to meet this warranty, at the sole option of Master Builders Solutions. Any claims concerning this product must be received in writing within one (1) year from the date of shipment and any claims not presented within that period are waived by Purchaser. Master Builders Solutions WILL NOT BE RESPONSIBLE FOR ANY SPECIAL, INCIDENTAL, CONSEQUENTIAL (INCLUDING LOST PROFITS) OR PUNITIVE DAMAGES OF ANY KIND.

Purchaser must determine the suitability of the products for the intended use and assumes all risks and liabilities in connection therewith. This information and all further technical advice are based on Master Builders Solutions' present knowledge and experience. However, Master Builders Solutions assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights, nor shall any legal relationship be created by or arise from the provision of such information and advice. Master Builders Solutions reserves the right to make any changes according to technological progress or further developments. The Purchaser of the Product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with a full application of the product(s). Performance of the product described herein should be verified by testing and carried out by qualified experts.