

Coral Stone Rendering

Acrylic finishes styled to create the look of cut coral

COLORS

Available in a wide variety of standard and custom colors.

For the appearance of added depth, it is recommended that the Rough Swirl Finish be tinted to a slightly darker color than the Finetex Finish.

PACKAGING

31.7-kg per 19-liter pail
(70-lbs per 5-gallon pail)

COVERAGE

Varies depending on application technique and surface condition.

Rough Swirl Finish:
Approximately 90 ft² (8.3 m²) per pail

Finetex Finish:
Approximately 150 ft² (13.9 m²) per pail for estimating purposes



DESCRIPTION

Coral Stone finish is a finish technique utilizing two textured acrylic finishes to create the look of cut coral in a lightweight, easily installed architectural wall finish.

FEATURES	BENEFITS
Coral look	The look of natural cut coral in an acrylic based finish
Lightweight	The look and feel of natural cut coral at a fraction of the weight
100% acrylic polymer chemistry	Long-term durability and weather resistance, dirt pick-up resistance
Integral color	Reduced maintenance and recoating; lasting color uniformity
Weather resistant	Repels water and resists wind-driven rain

USES

1. Provides an aesthetically pleasing surface color and texture for Finestone Wall Systems.
2. Can also be utilized as a textured finish for poured concrete or unit masonry, conventional stucco, Finestone Stucco Wall System, Finestone Cement-Board Stucco, certain insulating concrete forms, and interior veneer plaster or gypsum wallboard.
3. Can be utilized on quoins, arches and reliefs.

MIXING

1. Individually mix the factory-prepared Rough Swirl Finish and Finetex Finish finishes with a mixer until thoroughly blended. (Clean mixing paddle thoroughly between mixing of the two textures.)
2. A small amount of clean, potable water may be added to adjust workability.
3. Additives are not permitted.
4. Close container when not in use.
5. Clean tools with soap and water immediately after use.

APPLICATION

1. Substrate shall be dry, clean, sound and free of releasing agents, paint or other residue or coatings. Verify substrate is flat, free of fins or planar irregularities greater than 6.4 mm in 3 m (1/4" in 10').
2. Apply Rough Swirl Finish directly to the substrate with a clean, stainless steel trowel.
3. Apply and level Rough Swirl Finish to the thickness of the largest aggregate.
4. Float the Rough Swirl Finish with a plastic float in random counter clockwise circles, to a consistent look.
5. Allow the Rough Swirl Finish to take up (dry a little) to the point the finish is firm, but not fully dry.
6. Apply the prepared Finetex Finish using a stainless steel venetian trowel in a heavy skip trowel technique.
7. Allow the Finetex Finish to take up before leveling the Finetex Finish over the Rough Swirl Finish. The leveling technique will begin to close up the large open voids. This step or appearance depends entirely on the finished look you are trying to create.

8. Alternate: If an antiqued appearance is required, the AnticoGlaze should be sprayed on randomly during the leveling of the Finetex Finish.
9. Alternate: If scoring mortar joints are the objective, level & scoring tools will be required.
 - Determine the block layout before starting.
 - Determine the size of the mortar joint. It may be necessary to make your own scoring tools out of steel packing bands or other materials.
 - Place the level onto the firm but not dry finish surface after the Finetex Finish and AnticoGlaze have been applied.
 - Cut/score the horizontal mortar joints from the underside of the level. This allows the cut finish to fall away. During scoring, do not attempt to score down to the base coat.

LIMITATIONS

1. Protect Finestone materials during transportation and installation to avoid physical damage.
2. Store Finestone materials in a cool, dry place protected from freezing. Store at no less than 4 °C (40 °F). Protect from extreme heat and direct sunlight. Shelf life is two years when unopened and stored as directed.
3. Do not apply Finestone materials in ambient temperatures below 4 °C (40 °F). Provide supplementary heat during installation and drying period (at least 24 hours after installation and until dry) when temperatures less than 4 °C (40 °F) prevail.
4. Do not apply Finestone materials to frozen surfaces.
5. Samples for job approval must be made in the field by the applicator, and approved prior to ordering.

VOC CONTENT

See respective product bulletins for specific VOC information.

HEALTH, SAFETY AND ENVIRONMENTAL

Read, understand and follow all Safety Data Sheets and product label information for this product prior to use. The SDS can be obtained by visiting finestone.master-builders-solutions.com/en, e-mailing your request to mbsbscst@mbcc-group.com or calling +1 (800) 433-9517. Use only as directed.

IN CASE OF EMERGENCY: Call CHEMTEL +1 (800) 255-3924 or if outside the US or Canada, +1 (813) 248-0585.

LIMITED WARRANTY NOTICE

Master Builders Solutions Construction Systems US, LLC ("Master Builders") warrants this product to be free from manufacturing defects and to meet the technical properties on the current Technical Data Guide, if used as directed within shelf life. Satisfactory results depend not only on quality products but also upon many factors beyond our control. MASTER BUILDERS MAKES NO OTHER WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO ITS PRODUCTS. The sole and exclusive remedy of Purchaser for any claim concerning this product, including but not limited to, claims alleging breach of warranty, negligence, strict liability or otherwise, is shipment to purchaser of product equal to the amount of product that fails to meet this warranty or refund of the original purchase price of product that fails to meet this warranty, at the sole option of Master Builders. Any claims concerning this product must be received in writing within one (1) year from the date of shipment and any claims not presented within that period are waived by Purchaser. MASTER BUILDERS WILL NOT BE RESPONSIBLE FOR ANY SPECIAL, INCIDENTAL, CONSEQUENTIAL (INCLUDING LOST PROFITS) OR PUNITIVE DAMAGES OF ANY KIND.

Purchaser must determine the suitability of the products for the intended use and assumes all risks and liabilities in connection therewith. This information and all further technical advice are based on Master Builders' present knowledge and experience. However, Master Builders assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights, nor shall any legal relationship be created by or arise from the provision of such information and advice. Master Builders reserves the right to make any changes according to technological progress or further developments. The Purchaser of the Product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with a full application of the product(s). Performance of the product described herein should be verified by testing and carried out by qualified experts.

FOR PROFESSIONAL USE ONLY. NOT FOR SALE TO OR USE BY THE GENERAL PUBLIC.

For the most current version of this literature, please visit our website at finestone.master-builders-solutions.com/en.