

# Encausto Verona Finish

100% acrylic polymer finish coat

#### COLORS


Available in a wide variety of standard and custom colors.

#### PACKAGING

31.7-kg per 19-liter pail  
(70-lbs per 5-gallon pail)

#### COVERAGE

Approximately 23 m<sup>2</sup> (250 ft<sup>2</sup>) per pail, applied in two coats. Actual coverage depends on application technique, substrate type and conditions.



#### DESCRIPTION

A factory mixed, 100% acrylic polymer finish coat. Available in Encausto Verona Finish utilizes uniformly sized aggregates to achieve a free-formed, flat texture. A mottled look (as shown) can be achieved by combining multiple colors.

#### FEATURES

Ability to incorporate multiple colors

100% Acrylic polymer chemistry

Does not require a sealer

Weather resistant

Breathable

#### BENEFITS

Unlimited tone on tone designs

Long-term durability and weather resistance

Save time and money

Repels water and resists wind-driven rain

Doesn't blister, peel or flake

#### USES

1. Provides a protective, weather-resistant and aesthetically pleasing surface color and texture for the Finestone Wall Systems.
2. Can also be utilized as a textured finish for poured concrete or unit masonry, conventional stucco, Finestone Stucco Wall System, Finestone Cement-Board Stucco, certain insulating concrete forms, and interior veneer plaster or gypsum wallboard.

#### MIXING

1. Thoroughly mix the factory-prepared Encausto Verona Finish with a mixer until thoroughly blended.
2. A small amount of clean, potable water may be added to adjust workability.
3. Additives are not permitted.
4. Close container when not in use.
5. Clean tools with soap and water immediately after use.

#### APPLICATION

1. Substrate shall be dry, clean sound and free of releasing agents, paint or other residue or coatings. Verify substrate is flat, free of fins or planar irregularities greater than 6.4 mm in 3 m (1/4" in 10').
2. Apply a tight coat of Encausto Verona Finish directly to the Finestone Base Coat/Reinforcing Mesh with a clean stainless steel trowel.
3. Maintain a wet edge on Encausto Verona Finish by applying and leveling continually over the wall surface.
4. Work Encausto Verona Finish to corners, joints or other natural breaks and do not allow material to set up within an uninterrupted wall area. Allow to set until surface is completely dry prior to application of second coat.
5. Use a stainless steel trowel and apply the second coat of Encausto Verona Finish.
6. Float Encausto Verona Finish to achieve final texture.

**NOTE: A color sample must be approved prior to product shipment. Also, slight color or texture variations may occur. Over time, and depending on its exposure, Encausto Verona's appearance will achieve a soft, weathered patina. This Finish will not hide imperfections in the Base Coat surface. Built-up applications are not recommended as craze cracking can result.**

#### LIMITATIONS

1. Protect Encausto Verona Finish during transportation and installation to avoid physical damage.
2. Store Finestone materials in a cool dry place protected by freezing. Store at no less than 4 °C (40 °F). Protect from extreme heat and direct sunlight. Shelf life is two years when unopened and stored as directed.
3. Do not apply Finestone materials in ambient temperatures below 4 °C (40 °F). Provide supplementary heat during installation and drying period (at least 24 hours after installation and until dry) when temperatures less than 4 °C (40 °F) prevail.
4. Do not apply Finestone materials to frozen surfaces.
5. A one-gallon wet sample of Encausto Verona Finish may be ordered. Standard 7"x7" Encausto Verona Finish samples are not available.

#### TECHNICAL SUPPORT

Consult Master Builders Solutions Technical Services Department at +1 (800) 589-1336 for specific recommendations concerning all other applications. Consult the Wall Systems website at [finestone.master-builders-solutions.com/en](http://finestone.master-builders-solutions.com/en), for additional information about products and systems and for updated literature.

#### HEALTH, SAFETY AND ENVIRONMENTAL

Read, understand and follow all Safety Data Sheets and product label information for this product prior to use. The SDS can be obtained by visiting [finestone.master-builders-solutions.com/en](http://finestone.master-builders-solutions.com/en), e-mailing your request to [mbsbscst@mbcc-group.com](mailto:mbsbscst@mbcc-group.com) or calling +1 (800) 433-9517. Use only as directed.

**IN CASE OF EMERGENCY: Call CHEMTEL +1 (800) 255-3924 or if outside the US or Canada, +1 (813) 248-0585.**

#### VOC CONTENT

0 g/l, or 0 lbs/gal less water and exempt solvents.

#### LIMITED WARRANTY NOTICE

Master Builders Solutions Construction Systems US, LLC ("Master Builders") warrants this product to be free from manufacturing defects and to meet the technical properties on the current Technical Data Guide, if used as directed within shelf life. Satisfactory results depend not only

on quality products but also upon many factors beyond our control. MASTER BUILDERS MAKES NO OTHER WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO ITS PRODUCTS. The sole and exclusive remedy of Purchaser for any claim concerning this product, including but not limited to, claims alleging breach of warranty, negligence, strict liability or otherwise, is shipment to purchaser of product equal to the amount of product that fails to meet this warranty or refund of the original purchase price of product that fails to meet this warranty, at the sole option of Master Builders. Any claims concerning this product must be received in writing within one (1) year from the date of shipment and any claims not presented within that period are waived by Purchaser. MASTER BUILDERS WILL NOT BE RESPONSIBLE FOR ANY SPECIAL, INCIDENTAL, CONSEQUENTIAL (INCLUDING LOST PROFITS) OR PUNITIVE DAMAGES OF ANY KIND.

Purchaser must determine the suitability of the products for the intended use and assumes all risks and liabilities in connection therewith. This information and all further technical advice are based on Master Builders' present knowledge and experience. However, Master Builders assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights, nor shall any legal relationship be created by or arise from the provision of such information and advice. Master Builders reserves the right to make any changes according to technological progress or further developments. The Purchaser of the Product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with a full application of the product(s). Performance of the product described herein should be verified by testing and carried out by qualified experts.

**FOR PROFESSIONAL USE ONLY. NOT FOR SALE TO OR USE BY THE GENERAL PUBLIC.**

For the most current version of this literature, please visit our website at [finestone.master-builders-solutions.com/en](http://finestone.master-builders-solutions.com/en).