

Finetex Finish

100% acrylic polymer finish coat

Product Bulletin

DESCRIPTION

Factory-mixed, 100% acrylic polymer finish coat. FINETEX Finish can achieve a wide variety of free-formed, texture appearances, including stipple, skip-trowel and Limestone Rendering (see specific Product Bulletin for details on how to perform the technique).

PACKAGING

31.7-kg per 19-liter pail
(70-lbs. per 5-gallon pail)

COVERAGE

Varies depending upon texture

For smooth finish application:
Approximately 400 ft² per coat,
per pail (minimum 2 coats)

For skip trowel:
Approximately 170 ft² per pail

COLORS

Available in a wide variety of
standard colors

HEALTH, SAFETY AND ENVIRONMENTAL

Read, understand and follow all
Safety Data Sheets and product
label information for this product
prior to use. The SDS can
be obtained by visiting
www.finestone.basf.com. Use only
as directed.

TECHNICAL SUPPORT

Consult our Technical Services
Department for specific
recommendations concerning all
other applications. Consult the
web site, www.finestone.basf.com
for additional information and for
updated literature.



USES

1. FINETEX Finish provides an aesthetically pleasing surface color and texture for the Finestone Wall Systems.
2. FINETEX Finish can also be utilized as a texture coating for poured concrete or unit masonry, veneer plaster or gypsum wallboard (interior applications only), conventional stucco, Finestone Stucco Wall System and certain insulating concrete forms.

NOTE: If a “smooth application is required, multiple coats and skillful applications techniques will be required. Over trowelling or “burnishing” may create changes in color.

Finetex Finish

MIXING

1. Thoroughly mix the factory-prepared FINETEX Finish with a mixer until thoroughly blended.
2. A small amount of clean, potable water may be added to adjust workability.
3. Additives are not permitted.
4. Close container when not in use.
5. Clean tools with soap and water immediately after use.

APPLICATION

1. Substrate shall be dry, clean, sound and free of releasing agents, paint or other residue or coatings. Verify substrate is flat, free of fins or planar irregularities greater than 6.4 mm in 3 m (1/4" in 10').
2. Apply FINETEX Finish directly to the Finestone Base Coat/Reinforcing Mesh with a clean, stainless steel trowel.
3. Apply and level FINETEX Finish during the same operation, to obtain minimum 1.6 mm (1/16") thickness uniform coverage.
4. Maintain a wet edge on FINETEX Finish by applying and texturing continually over the wall surface.
5. Work FINETEX Finish to corners, joints or other natural breaks and do not allow material to set up within an uninterrupted wall area.
6. Float FINETEX Finish to achieve final texture.

LIMITATIONS

1. Protect Finestone materials during transportation and installation to avoid physical damage.
2. Store Finestone materials in a cool, dry place protected from freezing. Store at no less than 4°C (40°F). Protect from extreme heat and direct sunlight. Shelf life is two years when unopened and stored as directed.
3. Do not apply Finestone materials in ambient temperatures below 4°C (40°F). Provide supplementary heat during installation and drying period (at least 24 hours after installation and until dry) when temperatures less than 4°C (40°F) prevail. If using a thicker application of FINETEX Finish, longer drying period will be required.
4. Do not apply Finestone materials to frozen surfaces.
5. Samples of FINETEX Finish are available from Finestone for color approval only. Samples for job approval must be made in the field by the applicator, and approved prior to ordering.

WARRANTY

BASF warrants this product to be free from manufacturing defects and to meet the technical properties on the current Product Bulletin, if used as directed within shelf life. Satisfactory results depend not only on quality products but also upon many factors beyond our control. **BASF MAKES NO OTHER WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO ITS PRODUCTS.** The sole and exclusive remedy of Purchaser for any claim concerning this product, including but not limited to, claims alleging breach of warranty, negligence, strict liability or otherwise, is shipment to purchaser of product equal to the amount of product that fails to meet this warranty or refund of the original purchase price of product that fails to meet this warranty, at the sole option of BASF. In the absence of an extended warranty issued by BASF, any claims concerning this product must be received in writing within one (1) year from the date of shipment and any claims not presented within that period are waived by Purchaser. **BASF WILL NOT BE RESPONSIBLE FOR ANY SPECIAL, INCIDENTAL, CONSEQUENTIAL (INCLUDING LOST PROFITS) OR PUNITIVE DAMAGES OF ANY KIND.**

Purchaser must determine the suitability of the products for the intended use and assumes all risks and liabilities in connection therewith. This information and all further technical advice are based on BASF's present knowledge and experience. However, BASF assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights, nor shall any legal relationship be created by or arise from the provision of such information and advice. BASF reserves the right to make any changes according to technological progress or further developments. The Purchaser of the Product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with a full application of the product(s). Performance of the product described herein should be verified by testing and carried out by qualified experts.

Features	Benefits
Ability to create unique surface textures	Achieve a wide variety of appearances including stipple, skip-trowel, and Limestone Rendering technique (see specific Product Bulletin for more details)
100% Acrylic polymer chemistry	Long-term durability and weather resistance
Does not require a sealer	Save time and money
Weather resistant	Repels water and resists wind-driven rain
Breathable	Doesn't blister, peel or flake

For the most current version of this literature, please visit our website at www.finestone.basf.com.