

Stucco Prime

Product Bulletin

DESCRIPTION

100% acrylic-based primer for stucco

PACKAGING

24.9 kg per 19-liter pail
(55 lbs per 5-gallon pail)

COVERAGE

Approximate coverage rate: 69.6–116.1 m² (750–1,250 ft²) per pail. Coverage will vary greatly depending on porosity and condition of surface.

USES

STUCCO PRIME is used when preparing conventional stucco (brown coat), STUCCOBASE, STUCCOBASE PREMIX, Poured Concrete or Unit Masonry prior to the application of the BASF Wall Systems Finish Coat to help alleviate shadowing and enhance the performance of the Stucco Wall System.

MIXING

1. Thoroughly mix the factory-prepared STUCCO PRIME with a paddle and drill to a uniform consistency.
2. A small amount of clean, potable water may be added to adjust workability.
3. Additives are not permitted.
4. Close container when not in use.
5. Clean tools with soap and water immediately after use.

APPLICATION

1. Substrate shall be clean, dry, sound and free of paint, contaminants or other residue or coatings. Verify substrate is flat, free of fins or planar irregularities greater than 6.4 mm in 3 m (1/4" in 10').
2. Ensure stucco has been cured a minimum of 6 days prior to application of STUCCO PRIME.
3. Apply STUCCO PRIME to substrate with a sprayer, 10 mm (3/8") nap roller, or good quality latex paint brush at a rate of approximately 3.6–6.1 m² per liter (150–250 ft² per gallon).
4. STUCCO PRIME shall be dry to the touch before proceeding to the BASF Wall Systems Finish Coat application.

LIMITATIONS

1. Protect BASF Wall Systems materials during transportation and installation to avoid physical damage.
2. Store BASF Wall Systems materials in a cool, dry place protected from freezing. Store at no less than 4°C (40°F). Protect from extreme heat and direct sunlight. Shelf life is two years when unopened and stored as directed.
3. Do not apply BASF Wall Systems materials in ambient temperatures below 4°C (40°F). Provide supplementary heat during installation and drying period (at least 24 hours after installation and until dry) when temperatures less than 4°C (40°F) prevail.
4. Do not apply BASF Wall Systems materials to frozen surfaces.

TECHNICAL SUPPORT

Consult our Technical Services Department for specific recommendations concerning all other applications. Consult the web site, www.wallsystems.basf.com for additional information and for updated literature.

HEALTH, SAFETY AND ENVIRONMENTAL

Read, understand and follow all Safety Data Sheets and product label information for this product prior to use. The SDS can be obtained by visiting www.wallsystems.basf.com. Use only as directed.

Advantages

Reduces suction of cement base coats and cementitious substrates; improves workability of Finish Coat application

Reduces chances of efflorescence in stucco and other cementitious substrates

Stucco Prime

WARRANTY

BASF warrants this product to be free from manufacturing defects and to meet the technical properties on the current Product Bulletin, if used as directed within shelf life. Satisfactory results depend not only on quality products but also upon many factors beyond our control. BASF MAKES NO OTHER WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO ITS PRODUCTS. The sole and exclusive remedy of Purchaser for any claim concerning this product, including but not limited to, claims alleging breach of warranty, negligence, strict liability or otherwise, is shipment to purchaser of product equal to the amount of product that fails to meet this warranty or refund of the original purchase price of product that fails to meet this warranty, at the sole option of BASF. In the absence of an extended warranty issued by BASF, any claims concerning this product must be received in writing within one (1) year from the date of shipment and any claims not presented within that period are waived by Purchaser. BASF WILL NOT BE RESPONSIBLE FOR ANY SPECIAL, INCIDENTAL, CONSEQUENTIAL (INCLUDING LOST PROFITS) OR PUNITIVE DAMAGES OF ANY KIND.

Purchaser must determine the suitability of the products for the intended use and assumes all risks and liabilities in connection therewith. This information and all further technical advice are based on BASF's present knowledge and experience. However, BASF assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights, nor shall any legal relationship be created by or arise from the provision of such information and advice. BASF reserves the right to make any changes according to technological progress or further developments. The Purchaser of the Product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with a full application of the product(s). Performance of the product described herein should be verified by testing and carried out by qualified experts.

For the most current version of this literature, please visit our website at www.wallsystems.basf.com.

BASF Corporation - Wall Systems | 3550 St Johns Bluff Rd South Jacksonville, Florida 32224 P: 800.221.9255 F: 904.996.6300 www.wallsystems.basf.com

© 2016 BASF Corporation rev 160427