

Project:

One World Trade Center

Location:

New York City, New York

Owner/s:

Port Authority of New York/New Jersey

Concrete Contractor:

Collavino Construction Company

Concrete Producer:

*Eastern Concrete Materials, a U.S.
Concrete Company*

Products Used*:

*MasterSure® Z 60 workability-retaining
admixture*

*MasterGlenium® 7500 high-range
water-reducing admixture*

*MasterSet® DELVO hydration-
controlling admixture*

MasterLife® SF 100 silica fume

Market Sector:

Ready-mixed concrete

Project Profile

Environmentally Preferable Concrete

One World Trade Center



The Background

Soaring to a height of 1,776 feet (540-meters), the 2.6-million-square-foot (242,000-square-meter) skyscraper known as One World Trade Center in the lower Manhattan district of New York City is a marvel of design and engineering. Construction of the building, previously called the Freedom Tower, began in April 2006 and it is now the tallest building in the United States.

One World Trade Center

The Challenge

Sustainable design was a central theme to One World Trade Center's development, with the Port Authority of New York/ New Jersey imposing a strict requirement for the replacement of portland cement with recycled materials. In addition, extremely high-performance concrete was necessary to meet the compressive strength requirements of the steel and concrete structural columns, which ranged from 14,000 psi (97 MPa) to 12,000 psi (83 MPa) for the lower 40 floors and 10,000 psi (69 MPa) to 8,600 psi (59 MPa) for the upper floors.

The 12,000 psi (83 MPa) concrete phase of the project was the most challenging, with the engineers, owners and contractors all having their own requirements and specifications.

Engineering Requirements:

- Compressive strength: 12,000 psi (83 MPa) @ 56 days
- Over-design for safety: 1,900 psi (13 MPa)
- Modulus of elasticity: 7.0 million psi (48 GPa)
- Heat of hydration: Not to exceed 160 °F (70 °C)
- Non-air-entrained

Port Authority of New York/New Jersey Requirements:

- Quantity of portland cement in the mixture: Less than 400 lb/yd³ (240 kg/m³)

Contractor Requirements:

- Slump flow: 24 - 28 inches (610 - 710 mm)
- Ability to pump to at least 40 floors
- No loss in concrete workability during transit and placement
- Aesthetically pleasing

To achieve these concrete properties which, combined, would be a groundbreaking feat, concrete producer Eastern Concrete Materials, Elmwood Park, NJ partnered with admixture supplier BASF Construction Chemicals, Beachwood, OH.





The Results

Through BASF's Green Sense Concrete mixture optimization service, Eastern Concrete Materials was able to proportion an EF Technology® concrete mixture with 71% cement replacement. The mixture replaced portland cement with the recycled materials, non-cementitious fillers and specialized admixtures to exceed all the performance targets specified by the One World Trade Center project stakeholders. This EF Technology mixture was used for the 38,000 yd³ (29,000 m³) of concrete needed for the columns through the first 40 floors.

To quantify the environmental impact of sustainable concrete for the structure, an Eco-Efficiency Analysis was conducted, using a methodology validated by NSF International, to compare the specialized EF Technology mixture to a reference mixture. The results of this cradle-to-gate analysis are included in Chart 1. Some practical equivalents for these savings are:

- Water savings equal to 1,177,329 half-liter bottles of water
- Reduced carbon footprint equal to 1,835,494 gallons of gasoline
- Fossil fuel savings equal to 29,872 barrels of oil

Chart 1. Environmental impact of sustainable concrete for One World Trade Center, as compared to a standard reference mixture.

Environmental Impacts	Environmental Savings
 Energy usage	25,400,000 kWh (91,440,000 MJ)
 Greenhouse gas emissions	34,800,000 lb CO ₂ eq (15,785,000 kg)
 Water emissions	5,247,000 gal (19,862,000 L)
 Solid waste	1,720,000 lb (780,178 kg)

Based on 145,000 yd³ (110,900 m³) of concrete developed for six compressive strengths.

More Information

The Master Builders Solutions brand brings all of BASF's expertise together to create chemical solutions for new construction, maintenance, repair and renovation of structures. Master Builders Solutions is built on the experience gained from more than a century in the construction industry.

The know-how and experience of a global community of BASF construction experts form the core of Master Builders Solutions. We combine the right elements from our portfolio to solve your specific construction challenges. We collaborate across areas of expertise and regions and draw on the experience gained from countless construction projects worldwide. We leverage global BASF technologies, as well as our in-depth knowledge of local building needs, to develop innovations that help make you more successful and drive sustainable construction.

The comprehensive portfolio under the Master Builders Solutions brand encompasses concrete admixtures, cement additives, chemical solutions for underground construction, waterproofing solutions, sealants, concrete repair & protection solutions, performance grouts, performance flooring solutions.

*Effective January 1, 2014, the names of BASF's Master Builders Solutions brand products have changed: RheoTEC Z-60 became MasterSure Z 60
Glenium 7500 became MasterGlenium 7500
DELVO Stabilizer became MasterSet DELVO
Rheomac SF 100 became MasterLife SF 100

Contact

United States
23700 Chagrin Boulevard
Cleveland, Ohio 44122-5544
Tel: 800 628-9990 ■ Fax: 216 839-8821

Canada
1800 Clark Boulevard
Brampton, Ontario L6T 4M7
Tel: 800 387-5862 ■ Fax: 905 792-0651