

DECLARATION OF PERFORMANCE n° IT0252/01 MasterPel 790

1) Unique identification code of the product-type EN 934-2 Table 9

2) Intended use or uses

Water resisting admixture

3) Manufacturer

Master Builders Solutions Italia SpA via Vicinale delle Corti 21, 31100 Treviso

4) System or systems of assessment and verification of constancy of performance (AVCP)

System 2+

5) Harmonized standard:

EN 934-2: 2012

6) Notified body/ies7) Declared performances

ICMQ SpA, identification number 1305

Essential characteristics	Performance	Harmonized technical specification
Chloride ion content	<= 0,1% by mass	
Alkali content (Na2O equivalent)	<= 2,5%	
Corrosion behaviour	Contains component only from EN 934-1: 2008 Annex A.1	
Compressive strength	28 days >= 85%	
Air content	<= 2,0 %	
Air content (entrained air)	NPD	
Air void characteristic	NPD	
Water reduction	NPD	EN 934-2: 2012
Bleeding	NPD	
Setting Time	NPD	
Hardening time/ strength development	NPD	
Capillary absorption	7 days curing, 7 days tested <= 50%	
	90 days curing, 28 days tested <= 60%	
Consistency	NPD	
Dangerous substances	See MSDS	
Segregated portion (SR)	NPD	

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued in accordance with Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: Dario Micheletto Resp. Quality Control Treviso, 03 May 2023

MichelettoDar

Page 1 of 1