

MasterLife WP 1000

Self-healing, integral crystalline waterproofing admixture in powder for durable concrete.

Material description

MasterLife WP 1000 is a specific integral crystalline waterproofing admix to be added to the concrete mix, to impart waterproofing properties due to active chemicals that react with the moisture in fresh concrete to generates a non-soluble crystalline formation throughout the capillary pores of cement matrix.

MasterLife WP 1000 consists of Portland cement, selected filler and fine sand and various active, proprietary chemicals that react with water and moisture higher that 95% closing and sealing capillary porosity and micro-cracks lower that 0,4 mm. The use of MasterLife WP 1000 is advised where a waterproof concrete is required, durable to deterioration due to harsh environmental conditions that resists to hydrostatic pressure from either positive or negative surface of the concrete slabs.


Fields of application

The use of MasterLife WP 1000 is recommended in the following applications:

- reservoirs of potable and non potable water;
- swimming pools;
- underwater structures;
- depurators;
- foundation work, slabs and retaining walls;
- · residential and non residential parking structures;
- dams and dykes;
- · harbors and docks;
- sewers, tunnels and canals;
- tunnels and subway systems.


Features and benefits

MasterLife WP 1000 becomes an integral part of the cement matrix giving waterproofing properties to concrete, thanks to a crystalline formation throughout the capillary pores. Reaction proceed in water since the early stages from 7 to 28 days and on, with the closing and sealing of micro-cracks, reducing permeability and improving the durability of concrete.



Self healing properties of MasterLife WP 1000 during time, in water.

In compliance with the European Regulation (EU No 305/2011 and EU No. 574/2014) the product is provided with the CE marking according to UNI EN 934-2 and the relative DoP (Declaration of Performance).



Dosage

The dosage of MasterLife WP 1000 can range from 1 to 2 kg by weight of cement.

Other dosages may be recommended in special cases according to specific job site conditions.

In such cases please consult our Technical Service Department for advice.

Packaging

MasterLife WP 1000 is available in 20 kg bags.



MasterLife WP 1000

Self-healing, integral crystalline waterproofing admixture in powder for durable concrete.

Technical Information	
Form	Grey powder
Bulk Density (g/cm³)	2.670 – 2.870
Uncompacted Bulk Density (g/cm³)	0.850 – I.050
Essential characteristic in accordance to EN 934-2	Performance
Chloride ion content	≤ 0.1% by mass
Alkali content (Na₂O equivalent)	≤ 25%
Corrosion behaviuor	Contains only components from EN 934-1 2008 Annex 1
Compressive strength	28 days ≥ 85%
Air content	≤ 2%
Capillary absorption	7 days curing, 7 days tested ≤ 50% 90 days curing, 28 days tested ≤ 60%

Storage

Store the product in a dry and sheltered place. Do not use the product if bag is damaged.

If stored in unopened bags the shelf life is 18 months.

Directions for use

MasterLife WP 1000 can be loaded preferably during the aggregates load on the loading belt in the ready-mix plant. We advise to mix for 5 min. in order to assure a homogeneous concrete. Avoid the addition on premixed-wet concrete.

Compatibility

MasterLife WP 1000 is compatible with all admixtures of MasterPozzolith, MasterRheobuild, MasterGlenium, MasterEase, MasterSure and MasterCO2re series.

Safety instruction

It is recommended that gloves be worn when using the product. For information on the correct and safe use, transport, storage and disposal of the product, consult the most recent Safety Data Sheet.



MasterLife WP 1000

Self-healing, integral crystalline waterproofing admixture in powder for durable concrete.

Other services

For additional technical information, brochures, references, technical reports and technical support please visit www.master-builders-solutions.com/it-it or alternatively contact infomac@masterbuilders.com.

Scan QR code to visit the product page and download the latest version of this technical data sheet and any additional documentation.



Disclaimer

Since 16/12/1992, Master Builders Solutions Italia Spa has been operating under a Certified Quality System compliant with the UNI EN ISO 9001 Standard. Furthermore, the Environmental Management System is certified according to the UNI EN ISO 14001 Standard and the Safety Management System is certified according to the UNI ISO 45001 Standard.

For further information, please consult the local Technician of Master Builders Solutions. The technical advice on how to use our products, either written or verbally given, are based on the current state of our scientific and practical expertise, and does not imply the assumption of any guarantee and/or responsibility for the final results of works executed using our products.

Therefore, the customer is not exempted from the exclusive task and responsibility of verifying the suitability of our products for the intended use and purposes.

This version supersedes all the previous ones.

Master Builders Solutions Italia Spa

Via Vicinale delle Corti, 21 – 31100 Treviso – Italia T +39 0422 429200 F +39 0422 421802 www.master-builders-solutions.com/it-it e-mail: infomac@masterbuilders.com