




ENVIRONMENTAL PRODUCT DECLARATION

IN ACCORDANCE WITH EN 15804+A2 & ISO 14025


Master X-Seed 130

Master Builders Solutions



EPD HUB, HUB-0920

Publishing date 06 December 2023, last updated on 06 December 2023, valid until 06 December 2028.







GENERAL INFORMATION

MANUFACTURER

Manufacturer	Master Builders Solutions
Address	Metallvägen 42, 195 72 Rosersberg, Sweden
Contact details	Sustainability-team@masterbuilders.com
Website	www.master-builders-solutions.com

EPD STANDARDS, SCOPE AND VERIFICATION

Program operator	EPD Hub, hub@epdhub.com
Reference standard	EN 15804+A2:2019 and ISO 14025
PCR	EPD Hub Core PCR version 1.0, 1 Feb 2022
Sector	Construction product
Category of EPD	Third party verified EPD
Scope of the EPD	Cradle to gate with options, A5, and modules C1-C4 and D
EPD author	Shirin Fataei - Master Builders Solutions
EPD verification	Independent verification of this EPD and data, according to ISO 14025: ☐ Internal certification ☑ External verification
EPD verifier	Haiha Nguyen, as an authorized verifier acting for EPD Hub Limited


The manufacturer has the sole ownership, liability, and responsibility for the EPD. EPDs within the same product category but from different programs may not be comparable. EPDs of construction products may not be comparable if they do not comply with EN 15804 and if they are not compared in a building context.

PRODUCT

Product name	Master X-Seed 130
Place of production	Rosersberg, Sweden
Period for data	2022
Averaging in EPD	No averaging

ENVIRONMENTAL DATA SUMMARY

Declared unit	1 kg
Declared unit mass	1 kg
GWP-fossil, A1-A3 (kgCO2e)	1.09
GWP-total, A1-A3 (kgCO2e)	1.09
Secondary material, inputs (%)	0.3
Secondary material, outputs (%)	52.7
Total energy use, A1-A3 (kWh)	3.76
Total water use, A1-A3 (m3e)	0.171







PRODUCT AND MANUFACTURER

ABOUT THE MANUFACTURER

Master Builders Solutions is one of the leading suppliers of concrete admixtures and underground construction solutions worldwide. With over a century of experience in the construction industry, we leverage cuttingedge technologies, a global community of experts at the core of our business, as well as in-depth knowledge of local building needs to provide innovative and sustainable solutions.

PRODUCT DESCRIPTION

Master X-Seed 130 contains a suspension of crystals consisting of nanoparticles specially designed to accelerate the hydration of the concrete in its early stages (6-16 hours). The product is based on a unique and innovative grain formation technology where the growth of hydrated crystals of calcium silicate is greatly accelerated.

Master X-Seed 130 promotes concrete curing at low, normal and even high heat curing temperatures. Unlike the traditional acceleration methods and thanks to the unique mode of action — the practically barrier-free crystal growth of the grains between the cement grains — an early strength development is accelerated while the microstructure of the concrete acquires equivalent or improved properties. Master X-Seed 130 can affect the open time of the concrete. Works very well where the concrete has a lower starting temperature.

Master X-Seed 130 has been optimized for all types of concrete, especially for precast concrete elements in which a high early strength development is an important success factor for the manufacturer. Master X-Seed 130 is a relevant alternative to heat curing and especially the highly accelerated hydration means that binders with a lower clinker content can be used.

Further information can be found at www.master-builders-solutions.com

PRODUCT RAW MATERIAL MAIN COMPOSITION

Raw material category	Amount, mass- %	Material origin
Metals	-	-
Minerals	>74	Germany, EU
Fossil materials	<26	Germany, EU
Bio-based materials	-	-

BIOGENIC CARBON CONTENT

Product's biogenic carbon content at the factory gate.


Biogenic carbon content in product, kg C	0
Biogenic carbon content in packaging, kg C	0

FUNCTIONAL UNIT AND SERVICE LIFE

Declared unit	1 kg	
Mass per declared unit	1 kg	
Reference service life		

SUBSTANCES, REACH - VERY HIGH CONCERN

The product does not contain any REACH SVHC substances in amounts greater than 0,1 % (1000 ppm).







PRODUCT LIFE-CYCLE

SYSTEM BOUNDARY

This EPD covers the life-cycle modules listed in the following table.

	rodu		Asse sta	mbly ige			U	lse stag	End of life stage				Beyond the system boundaries					
A1	A2	А3	A4	A5	B1 B2 B3 B4 B5 B6 B7 C1 C								C2	СЗ	C4		D	
x	x	x	MND	x	MND	D MND MND MND MND MND X X X X								x				
Raw materials	Transport	Manufacturing	Transport	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	Deconstr./demol.	Transport	Waste processing	Disposal	Reuse	Recovery	Recycling

Modules not declared = MND. Modules not relevant = MNR.

MANUFACTURING AND PACKAGING (A1-A3)

The environmental impacts considered for the product stage cover the manufacturing of raw materials used in the production as well as packaging materials and other ancillary materials. Also, fuels used by machines, and handling of waste formed in the production processes at the manufacturing facilities are included in this stage. The study also considers the material losses occurring during the manufacturing processes as well as losses during electricity transmission.

Concrete admixtures are manufactured by mixing the ingredients (together) in batch mode, and then poured in containers or pumped into the truck tankers.

Most of the products is shipped with tanker trucks to customers. According to the 2022 company data, only 10% is shipped using intermediate bulk containers (IBC). The IBC consists of 20 kg steel cages, 21 kg HDPE integrated pallet and 15 kg HDPE "bottle" (the holding volume). IBC contains a total of 1140 kg of Master X-Seed product. It was assumed that the IBC is reused 3 times.

TRANSPORT AND INSTALLATION (A4-A5)

Transportation impacts occurred from final product delivery to the construction site (A4) is not modelled. During concrete manufacture, concrete admixtures are usually added along with the mixing water or included in premixed concrete. The material loss during installation is therefore 0% for admixtures. Since 10% of the product is shipped in IBC packaging, the treatment of the packaging waste is as well modelled in A5.

PRODUCT USE AND MAINTENANCE (B1-B7)


This EPD does not cover the use phase.

Air, soil, and water impacts during the use phase have not been studied.

PRODUCT END OF LIFE (C1-C4, D)

The admixture becomes an inseparable part of the concrete, and therefore it undergoes a similar end of life scenario. The deconstruction of concrete takes place in C1 module which considers energy for dismantling, particulate matter emissions from dismantling and handling. After the demolition, the debris are transported to the end-of-life processing (C2) where all the impacts related to the transport processes are considered. According to the regional data, 52.7% of the waste concrete is treated to be reused as recycled aggregates (C3) and the rest (47.3%) is treated as inert material for landfill (C4).


The benefits and loads of recycled aggregates (from C3) as well as benefits and loads of the packaging (IBC) waste (from A5) are modelled and included beyond the system boundary (D).







MANUFACTURING PROCESS







LIFE-CYCLE ASSESSMENT

CUT-OFF CRITERIA

The study does not exclude any modules or processes which are stated mandatory in the reference standard and the applied PCR. The study does not exclude any hazardous materials or substances. The study includes all major raw material and energy consumption. All inputs and outputs of the unit processes, for which data is available for, are included in the calculation. There is no neglected unit process more than 1% of total mass or energy flows. The module specific total neglected input and output flows also do not exceed 5% of energy usage or mass.

ALLOCATION, ESTIMATES AND ASSUMPTIONS

Allocation is required if some material, energy, and waste data cannot be measured separately for the product under investigation. All allocations are done as per the reference standards and the applied PCR. In this study, allocation has been done in the following ways:

Data type	Allocation
Raw materials	No allocation
Packaging materials	Allocated by mass or volume
Ancillary materials	Not applicable
Manufacturing energy and waste	Allocated by mass or volume

The following assumptions were made:

- Transport distance for packaging waste (A5) and concrete waste at the end-of-life (C2) is considered 100 km as the worst-case scenario.
- Consumed energy for demolition (C1) is 0.07 MJ / kg [Source: <u>EUR</u>
 29123 EN Model for Life Cycle Assessment (LCA) of buildings].

- End-of-life waste processing ratio for Sweden is considered 52.7% as recycling concrete and 47.3% as landfill (C3 and C4) [Source: Bygg-och-rivningsavfall from The Swedish Environmental Protection Agency].
- The steel cage of the IBC is produced from 42.4% steel scrap and 57.6% from virgin material [Source: World Steel in Figures from WorldSteel Association].
- Waste processing ratios for HDPE part of the IBC are 34.6% for recycling and reuse as plastic, 42.0% for incineration with 73% efficiency, and 23.4% sanitary landfill (A5) [Sources: <a href="Energy Recovery from Waste Incineration—The Importance of Technology Data and System Boundaries on CO2 Emissions by Eriksson O., Finnveden G. (2017)]</sup>
- Waste processing ratios for steel cage of the IBC are 85% recycling and reuse and 15% landfill [Source: The Global Life Cycle of Stainless Steel].

AVERAGES AND VARIABILITY


Type of average	No averaging
Averaging method	Not applicable
Variation in GWP-fossil for A1-A3	-

This EPD is product and factory specific and does not contain average calculations.

LCA SOFTWARE AND BIBLIOGRAPHY

This EPD has been created using One Click LCA EPD Generator. The LCA and EPD have been prepared according to the reference standards and ISO 14040/14044. Ecoinvent 3.8 and One Click LCA databases were used as sources of environmental data. Further EPDs to Ecoinvent databases are:

 EPD for "Hardening accelerator for concrete, Master X-Seed 100" (EPD number: HUB-0037).







ENVIRONMENTAL IMPACT DATA

CORE ENVIRONMENTAL IMPACT INDICATORS – EN 15804+A2, PEF


Impact category	Unit	A1	A2	А3	A1-A3	A4	A5	B1	B2	В3	B4	B5	В6	В7	C1	C2	С3	C4	D
GWP – total ¹⁾	kg CO₂e	9.22E-01	1.63E-01	4.46E-03	1.09E+00	MND	1.46E-03	MND	6.44E-03	9.39E-03	5.56E-04	1.09E-03	-5.90E-03						
GWP – fossil	kg CO₂e	9.19E-01	1.63E-01	4.41E-03	1.09E+00	MND	1.46E-03	MND	6.44E-03	9.38E-03	2.12E-03	2.49E-03	-5.89E-03						
GWP – biogenic	kg CO₂e	2.96E-03	0.00E+00	1.24E-06	2.96E-03	MND	-1.24E-06	MND	0.00E+00	0.00E+00	-1.56E-03	-1.40E-03	-1.69E-06						
GWP – LULUC	kg CO₂e	4.11E-04	6.03E-05	5.46E-05	5.26E-04	MND	6.46E-08	MND	6.41E-07	3.46E-06	2.11E-07	2.35E-06	-5.92E-06						
Ozone depletion pot.	kg CFC-11e	9.79E-08	3.76E-08	8.40E-10	1.36E-07	MND	8.18E-12	MND	1.38E-09	2.16E-09	4.53E-10	1.01E-09	-4.37E-10						
Acidification potential	mol H⁺e	3.93E-03	6.92E-04	1.67E-05	4.63E-03	MND	5.05E-07	MND	6.69E-05	3.97E-05	2.20E-05	2.34E-05	-3.17E-05						
EP-freshwater ²⁾	kg Pe	6.24E-06	1.34E-06	1.95E-07	7.77E-06	MND	1.70E-09	MND	2.13E-08	7.68E-08	7.01E-09	2.61E-08	-2.57E-07						
EP-marine	kg Ne	1.69E-03	2.06E-04	3.37E-06	1.90E-03	MND	1.75E-07	MND	2.96E-05	1.18E-05	9.74E-06	8.11E-06	-6.79E-06						
EP-terrestrial	mol Ne	1.05E-02	2.27E-03	3.87E-05	1.28E-02	MND	1.85E-06	MND	3.25E-04	1.30E-04	1.07E-04	8.92E-05	-8.69E-05						
POCP ("smog")3)	kg NMVOCe	2.10E-03	7.25E-04	1.43E-05	2.84E-03	MND	5.06E-07	MND	8.93E-05	4.17E-05	2.94E-05	2.59E-05	-2.47E-05						
ADP-minerals & metals ⁴⁾	kg Sbe	1.59E-05	3.83E-07	2.85E-08	1.63E-05	MND	1.91E-09	MND	3.26E-09	2.20E-08	1.08E-09	5.72E-09	-4.55E-08						
ADP-fossil resources	MJ	1.34E+01	2.45E+00	1.27E-01	1.60E+01	MND	7.57E-04	MND	8.66E-02	1.41E-01	2.85E-02	6.83E-02	-9.87E-02						
Water use ⁵⁾	m³e depr.	3.83E-01	1.10E-02	6.86E-03	4.01E-01	MND	5.08E-05	MND	2.33E-04	6.31E-04	7.66E-05	2.17E-04	-8.50E-03						

¹⁾ GWP = Global Warming Potential; 2) EP = Eutrophication potential; 3) POCP = Photochemical ozone formation; 4) ADP = Abiotic depletion potential

ADDITIONAL ENVIRONMENTAL IMPACT INDICATORS - EN 15804+A2, PEF

Impact category	Unit	A1	A2	А3	A1-A3	A4	A5	B1	B2	В3	B4	В5	В6	В7	C1	C2	СЗ	C4	D
Particulate matter	Incidence	1.44E-07	1.88E-08	2.02E-10	1.63E-07	MND	7.59E-12	MND	1.79E-09	1.08E-09	4.51E-09	4.72E-10	-3.96E-10						
Ionizing radiation ⁶⁾	kBq U235e	5.10E-02	1.17E-02	9.16E-03	7.18E-02	MND	5.28E-06	MND	3.98E-04	6.71E-04	1.31E-04	3.09E-04	-8.99E-04						
Ecotoxicity (freshwater)	CTUe	1.48E+01	2.21E+00	7.90E-02	1.71E+01	MND	1.81E-03	MND	5.20E-02	1.27E-01	1.71E-02	4.46E-02	-9.04E-02						
Human toxicity, cancer	CTUh	1.05E-09	5.42E-11	1.29E-11	1.11E-09	MND	1.58E-13	MND	1.99E-12	3.11E-12	6.56E-13	1.11E-12	-4.25E-13						
Human tox. non-cancer	CTUh	9.21E-09	2.18E-09	5.63E-11	1.15E-08	MND	3.64E-12	MND	3.76E-11	1.25E-10	1.24E-11	2.91E-11	-8.93E-11						
SQP ⁷⁾	-	2.13E+00	2.83E+00	3.41E-02	5.00E+00	MND	1.12E-03	MND	1.13E-02	1.62E-01	3.70E-03	1.46E-01	-5.99E-02						

⁶⁾ EN 15804+A2 disclaimer for lonizing radiation, human health: This impact category deals mainly with the eventual impact of low dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor due to radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, from radon and from some construction materials is also not measured by this indicator ⁷⁾ SQP = Land use related impacts/soil quality



For EP-freshwater, the required characterization method and data are in kg P-eq. Multiply by 3,07 to get PO4e

^{4.5)} EN 15804+A2 disclaimer for Abiotic depletion and Water use and optional indicators except Particulate matter and Ionizing radiation, human health: The results of these environmental impact indicators shall be used with care as the uncertainties on these results are high or as there is limited experienced with the indicator





USE OF NATURAL RESOURCES

Impact category	Unit	A1	A2	А3	A1-A3	A4	A5	B1	B2	В3	B4	B5	В6	В7	C1	C2	С3	C4	D
Renew. PER as energy ⁸⁾	MJ	6.86E-01	2.76E-02	4.69E-02	7.60E-01	MND	5.44E-05	MND	4.95E-04	1.59E-03	1.63E-04	5.93E-04	-5.54E-03						
Renew. PER as material	MJ	9.18E-03	0.00E+00	0.00E+00	9.18E-03	MND	0.00E+00	MND	0.00E+00	0.00E+00	-4.84E-03	-4.34E-03	0.00E+00						
Total use of renew. PER	MJ	6.95E-01	2.76E-02	4.69E-02	7.70E-01	MND	5.44E-05	MND	4.95E-04	1.59E-03	-4.68E-03	-3.75E-03	-5.54E-03						
Non-re. PER as energy	MJ	1.02E+01	2.45E+00	1.53E-01	1.28E+01	MND	7.57E-04	MND	8.66E-02	1.41E-01	2.85E-02	6.83E-02	-8.35E-02						
Non-re. PER as material	MJ	3.23E+00	0.00E+00	5.03E-02	3.28E+00	MND	-5.03E-02	MND	0.00E+00	0.00E+00	-1.70E+00	-1.53E+00	0.00E+00						
Total use of non-re. PER	MJ	1.34E+01	2.45E+00	2.03E-01	1.60E+01	MND	-4.96E-02	MND	8.66E-02	1.41E-01	-1.67E+00	-1.46E+00	-8.35E-02						
Secondary materials	kg	3.00E-03	6.81E-04	3.68E-04	4.05E-03	MND	1.65E-06	MND	3.39E-05	3.91E-05	1.11E-05	1.44E-05	5.33E-04						
Renew. secondary fuels	MJ	4.95E-06	6.87E-06	3.68E-05	4.86E-05	MND	2.08E-08	MND	1.11E-07	3.95E-07	3.64E-08	3.75E-07	-4.72E-07						
Non-ren. secondary fuels	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	MND	0.00E+00	MND	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00						
Use of net fresh water	m³	1.37E-01	3.18E-04	3.37E-02	1.71E-01	MND	5.13E-07	MND	5.26E-06	1.83E-05	1.73E-06	7.48E-05	-2.04E-04						

⁸⁾ PER = Primary energy resources.

END OF LIFE – WASTE

Impact category	Unit	A1	A2	А3	A1-A3	A4	A5	B1	B2	В3	B4	В5	В6	В7	C1	C2	C3	C4	D
Hazardous waste	kg	2.73E-02	3.25E-03	5.42E-04	3.11E-02	MND	5.23E-06	MND	1.16E-04	1.87E-04	3.81E-05	0.00E+00	-3.57E-04						
Non-hazardous waste	kg	9.67E-01	5.34E-02	6.31E-03	1.03E+00	MND	8.70E-04	MND	8.14E-04	3.07E-03	2.68E-04	4.73E-01	-1.11E-02						
Radioactive waste	kg	8.09E-05	1.64E-05	1.70E-06	9.90E-05	MND	3.23E-09	MND	6.10E-07	9.43E-07	2.01E-07	0.00E+00	-3.07E-07						


END OF LIFE – OUTPUT FLOWS

Impact category	Unit	A1	A2	А3	A1-A3	A4	A5	B1	B2	В3	B4	В5	В6	В7	C1	C2	C3	C4	D
Components for re-use	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	MND	0.00E+00	MND	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00						
Materials for recycling	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	MND	8.61E-04	MND	0.00E+00	0.00E+00	5.27E-01	0.00E+00	0.00E+00						
Materials for energy rec	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	MND	0.00E+00	MND	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00						
Exported energy	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	MND	1.54E-02	MND	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00						

ENVIRONMENTAL IMPACTS – GWP-GHG - THE INTERNATIONAL EPD SYSTEM

Impact category	Unit	A1	A2	А3	A1-A3	A4	A5	B1	B2	В3	B4	B5	В6	В7	C1	C2	C3	C4	D
GWP-GHG ⁹⁾	kg CO₂e	9.19E-01	1.63E-01	4.41E-03	1.09E+00	MND	1.46E-03	MND	6,44E-03	9,38E-03	2,12E-03	2,49E-03	-5.89E-03						

⁹⁾ This indicator includes all greenhouse gases excluding biogenic carbon dioxide uptake and emissions and biogenic carbon stored in the product as defined by IPCC AR 5 (IPCC 2013). In addition. the characterisation factors for the flows - CH4 fossil. CH4 biogenic and Dinitrogen monoxide - were updated in line with the guidance of IES PCR 1.2.5 Annex 1. This indicator is identical to the GWP-total of EN 15804:2012+A2:2019 except that the characterization factor for biogenic CO2 is set to zero.







VERIFICATION STATEMENT

VERIFICATION PROCESS FOR THIS EPD

This EPD has been verified in accordance with ISO 14025 by an independent, third-party verifier by reviewing results, documents and compliancy with reference standard, ISO 14025 and ISO 14040/14044, following the process and checklists of the program operator for:

- This Environmental Product Declaration
- The Life-Cycle Assessment used in this EPD
- The digital background data for this EPD

Why does verification transparency matter? Read more online This EPD has been generated by One Click LCA EPD generator, which has been verified and approved by the ED Hub.

THIRD-PARTY VERIFICATION STATEMENT

I hereby confirm that, following detailed examination, I have not established any relevant deviations by the studied Environmental Product Declaration (EPD), its LCA and project report, in terms of the data collected and used in the LCA calculations, the way the LCA-based calculations have been carried out, the presentation of environmental data in the EPD, and other additional environmental information, as present with respect to the procedural and methodological requirements in ISO 14025:2010 and reference standard.

I confirm that the company-specific data has been examined as regards plausibility and consistency; the declaration owner is responsible for its factual integrity and legal compliance.

I confirm that I have sufficient knowledge and experience of construction products, this specific product category, the construction industry, relevant standards, and the geographical area of the EPD to carry out this verification.

I confirm my independence in my role as verifier; I have not been involved in the execution of the LCA or in the development of the declaration and have no conflicts of interest regarding this verification.

HaiHa Nguyen, as an authorized verifier acting for EPD Hub Limited 06.12.2023



